

Wheelchairs, like people, come in all shapes and sizes. Height, location and accessible route are important elements for successful accommodations.



Section 11-4.32 Fixed or Builtin Seating and Tables

- If seating for people in wheelchairs is provided at tables or counters, knee spaces at least 27 inches high, 30 inches wide and 19 inches deep shall be provided 11-4.32.3
- Tops of accessible tables and counters can range from 28 inches to 34 inches

6/20/03

When more than one accessible seat is necessary, they shall be dispersed throughout the facility.

Remember that vertical accessibility is required in Florida for all levels over ½ inch. In restaurants this would include upstairs, outside eating areas, mezzanines, raised platforms and sunken areas.

Exercise – in a 100 seat restaurant how many accessible units are required? Answer (5 seats)

Time: 5 min.



Section 11-4.32 Fixed or Builtin Seating and Tables

- At least 5% but not less than 1 of the fixed seating areas or tables shall comply with 11-4.32 (11-4.1.3.(18))
- Seating shall be on an accessible route
 36 inches wide minimum, 44 inches
 for means of egress 11-4.1.3(18)



Accessible Seating Table: 11-4.1.3(19)

- Capacity of SeatingNumber of Required in Assembly Areas
 - Wheelchair Locations

4

• 1 to 25

• 26 to 50

• 51 to 100

For all remaining fixed seats, there shall be not less than one such accessible and usable space for each 100 fixed seats or fraction thereof

6/20/03

Review the fixed seating requirements in auditoriums, sport complexes and other fixed seat venues. Review the differences and similar requirements.

Section 11-4.33 Assembly Areas

- Stadium style seating must comply with vertical accessibility requirements; otherwise a waiver is required from the Florida Building Commission
- Waiver forms available at www.floridabuilding.org
- Listening systems located within 50 feet of stage or screen


6/20/03

11-4.1.3(19)(b) - This paragraph applies to assembly areas where audible communications are integral to the use of the space (e.g., concert and lecture halls, playhouses and movie theatres, meeting rooms, etc.). Such assembly areas, if (1) they accommodate at least 50 persons, or if they have audio-amplification systems, and (2) they have fixed seating, shall have a permanently installed assistive listening system complying with 11-4.33. For other assembly areas, a permanently installed assistive listening system or an adequate number of electrical outlets or other supplementary wiring necessary to support a portable assistive listening system shall be provided. The minimum number of receivers to be provided shall be equal to 4 percent of the total number of seats, but in no case less than two. Signage complying with applicable provisions of 11-4.30 shall be installed to notify patrons of the availability of a listening system.

Note to Instructor: Review waiver application process. Go to www.floridabuilding.org, and click on the second button: "Florida Building Code." Click on the "Accessibility Waivers" tab at the top of the page.


(Actual URL)

http://www.dca.state.fl.us/fhcd/fbc/committees/accessibility/aac/aac_waiver_form/1 aac waiver form.htm




This fixed seat location has two seats at the same location.

Exercise: What complies with code in this picture? What does not comply with code in the picture?




Fixed desk – classroom or assembly area.

Note: The accessible seating shall be dispersed throughout the facility.



Seating in a large stadium. There is wheelchair and companion seating. If the wheelchair box is 48 inches deep and there should be a minimum of a 3 feet access aisle behind – how much room should there be from front of box to rear? (answer – 7 feet minimum)



An example of a good try at providing disabled and companion seating at a stadium.



Section 11-4.34 Automated Teller

 Automated teller shall be located so that clear floor space complying with 11-4.2.4 (30 inches by 48 inches) is provided to allow a person using a wheelchair to make a forward approach, a parallel approach, or both

6/20/03

Time: 0



Section 11-4.34 Automated Teller




- Forward approach only operable parts mounted in accordance with 11-4.2.5
- Parallel approach only not more than 10 inches, controls mounted no higher than 54 inches

1:



Section 11-4.34 Automated Teller

- Reach depth in accordance with table in 11-4.34.3
- Instructions and all information for use shall be made accessible to and independently usable by persons with vision impairments 11-4.34.5





Section 11-4.35 Dressing & Fitting Rooms

- Provide an area that allows a person using a wheelchair to make a 180 degree turn. No door shall swing into the turning space
- Doors must comply with Section 11-4.13

6/20/03

Time: 2 min.



Section 11-4.35 Dressing & Fitting Rooms

 Every accessible dressing room shall have a 24 inch by 48 inch bench fixed to a wall along the longer dimension. The bench shall be mounted 17 inches to 19 inches above the finished floor



6/20/03

15

Note: Some people in wheelchairs do not dress in their chairs but prefer to put their clothes on while laying down. This bench also benefits people that use walkers, crutches, braces and other assistive devices.

Clear floor space shall be provided beside the bench to allow for transfer.



Section 11-4.35 Dressing & Fitting Rooms

 Where mirrors are provided, then, a full-length mirror, measuring at least 18 inches wide by 54 inches high, shall be mounted in a position affording a view to a person on the bench as well as a person standing



6/20/03

The mirror is to be mounted so the measurements are to the edge of the reflective surface, not necessarily to the bottom of the mirror.



• Where fixed tables (or dining counters where food is consumed but there is no service) are provided, at least 5%, but not less than one, of the fixed tables (or a portion of the dining counter) shall be accessible and shall comply with 11-4.32 as required in 11-4.1.3.18. (11-5.1)



 In new construction, and where practicable in alterations, accessible fixed tables (or counters) shall be distributed throughout the space or facility (11-5.1)



• Where food and drink is served at counters exceeding 34 inches in height for consumption by customers seated on stools or standing at counter, a portion of the main counter which is 60 inches in length minimum shall be provided in compliance with 11-4.32 or service shall be available at accessible tables within the same area.





- All dining areas, including raised or sunken dining areas, loggias, and outdoor seating areas, shall be accessible (11-5.4)
- Self-service shelves and dispensing devices for tableware, dishware, condiments, food and beverages shall be installed to comply with 11-4.2



Food service lines shall have a minimum clear width of 36 inches, with a preferred clear width of 42 inches. Tray slides shall be mounted no higher than 34 inches above the floor. If selfservice shelves are provided, at least 50% of each type shall be within reach ranges specified in 11-4.2.5 and 11-4.2.6





Section 11-5 Restaurants & Cafeterias — Raised Platforms 11-5.7

In banquet rooms or spaces where a head table or speaker's lectern is located on a raised platform, the platform shall be accessible in compliance with 11-4.8 or 11-4.11. Open edges of a raised platform shall be protected by placement of tables or by a curb.



 Hospitals – general purpose hospitals, psychiatric facilities, detoxification facilities – At least 10 percent of patient bedrooms and toilets, and all public use and common use areas are required to be designed and constructed to be accessible. (11-6.1.1)



Hospitals and rehabilitation facilities
 that specialize in treating conditions
 that affect mobility, or units within
 either that specialize in treating
 conditions that affect mobility – All
 patient bedrooms and toilets, and all
 public use and common use areas are
 required to be designed and
 constructed to be accessible. (11-6.1.2)



Long term care facilities, nursing homes

 At least 50 percent of patient
 bedrooms and toilets, and all public use
 and common use areas are required to
 be designed and constructed to be
 accessible. (11-6.1.3)



 At facilities providing medical care and other services for person with mobility impairments, parking spaces complying with 11-4.6 shall be provided in accordance with 11-4.4.1.2(5)(a) except as follows:



- (i) Outpatient units and facilities: 10 percent of the total number of parking spaces provided serving each such outpatient unit or facility;
- (ii) Units and facilities that specialize in treatment of services for persons with mobility impairments; 20 percent of the total number of parking spaces provided serving each such unit or facility.



Each patient bedroom shall have a door that complies with 11-4.13: except entry doors to acute care hospital bedrooms for in-patients shall be exempted from the requirement in 11-4.13.6 for maneuvering space at the latch side of the door if the door is at least 44 inches wide.



Section 11-7 Business and Mercantile

 Department and retail stores where counters have cash registers and are provided for the sale and distribution of goods or services at least one of each type shall have a portion of the counter which is at least 36 inches wide with a maximum height of 36 in (11-7.2.1)











Section 11-7 Business and Mercantile

Ticketing counters, teller stations in a bank, registration at hotels and motels, box office ticket counters, and other counters that may not have a cash register but at which goods or services are sold either: 36 inches wide by 36 inches high counter; or and auxiliary counter with max height of 36 inches; or an equivalent facilitation (11-7.2.2)



Section 11-8 Libraries

 At least 5% or a min. of one of each element of fixed seating, tables, or study carrels shall comply with 11-4.4.2 and 11-4.32.



Section 11-8 Libraries

- Card catalogs must comply with Figure 55
- Stacks Min. clear aisle width between stacks shall comply with 11-4.3, with a min. clear aisle width of 42 inches preferred



- Hotels, Motels, Inns, Boarding Houses, Dormitories, Resorts and Other similar Places of Transient Lodging.
 - All public use and common use areas are required to be designed and constructed to comply with section 11-4.

6/20/03


One of the most misunderstood and missed areas is accessibility compliance in the Hotel/Motel industry. Care shall be exercised for compliance with the regulations for these types of occupancies. Failure to comply results in difficulty for people with disabilities and their companions. Particular attention should be paid when renovations are made.

In Instructor Guide: Review Manual for Commentary.



Accessible sleeping rooms or suites that comply with the requirements of 11-9.2.1 to 11-9.2.2 shall be provided in conformance with the table to follow. In addition, in hotels, of 50 or more sleeping rooms or suites, additional accessible sleeping rooms or suites that include a roll-in shower shall be provided (see Figure 57a & b)

6/20/03 4



Section 11-9 Accessible Transient Lodging				
	_	s. with Roll-In shower	s FL 5%	
1 to 25	1			
26 to 50	2			
51 to 75	3	1		
76 to 100	4	1		
101 to 150	5	2		
151 to 200	6	2	See 11-9.1.2 shaded	
201 to 300	7	3		
301 to 400	8	4		
401 to 500	9	4, plus one for each additional 100 over 400		
501 to 1000	2% of total			
1001 to over	•	20 plus 1 for each 100 over 1000		
6/20/03			42	

Instructor Notes: Mention that the two columns for room numbers and roll in showers are cumulative total for accessible rooms.

Exercise: Hotel Room Calculation.

Time: 2 min.



- Sleeping rooms for persons with hearing impairments
- In addition to those accessible sleeping rooms and suites sleeping rooms that comply with 11-9.3 shall be provided in conformance with the following table:

6/20/03 43

Note: This is a frequently missed requirement. Remember that requirements for people with hearing impairments shall be included in the required accessible rooms and in the sleeping accommodations for persons with hearing impairments. This is over and above the requirements for people with other physical disabilities.

Section 11-9 Accessible **Transient Lodging** Number of Elements and Accessible Elements 1 to 25 26 to 50 2 51 to 75 3 76 to 100 4 5 101 to 150 6 151 to 200 201 to 300 7 301 to 400 8 9 401 to 500 501 to 1000 2% of total 1001 and over 20 plus 1 for each 100 over 1000 6/20/03

Exercise: Do calculations.



- 11-9.1.4 Classes of Sleeping Accommodations
 - Sleeping rooms required to be accessible by 11-9.1.2 shall be dispersed among the various classes of sleeping accommodations. Factors to consider include room size, cost, amenities provided, and number of beds.

6/20/03 4

Equivalent facilitation – If the operator of the facility elects to limit construction of accessible rooms to those intended for multiple occupancy it shall deemed equivalent facilitation provided that such rooms are made available at the cost of a single occupancy room to an individual with disabilities who request single-occupancy rooms.



- 11-9.2 Requirements for Accessible Units, Sleeping Rooms and Suites
- An accessible unit, sleeping room or suite shall be on an accessible route
- Accessible rooms shall have a 36 inch clear width maneuvering space located along both sides of a bed (except when two beds are provided)
- An accessible route shall connect all accessible spaces and elements, including telephones, within the unit, sleeping room or suite

6/20/03 46



- 11-9.2.3 Hotel, Motel and Condominium Special Accessibility Feature
- At least 5% of rooms, in addition the accessible rooms, shall have grab rails in bathrooms and toilet rooms, open frame beds, all standard water closet seats shall be 15 inches with a portable or attached raised toilet seat in designated accessible rooms (11-9.2.3)

6/20/03 47





Section 11-10 Transportation Facilities

Every station, bus stop, bus stop pad, terminal, building or other transportation facility, shall comply with the applicable provisions of 11-4.1 through 11-4.35, sections 11-5 through 11-9, and applicable provisions of this section



Section 11-11 Residential Buildings

- Single family houses, duplexes, triplexes, condominiums and townhouses shall provide:
- One bathroom located with max privacy on grade level with a door that has a 29 inch clear opening.

6/20/03

Instructor shall have a copy of Fair Housing Act Design Manual to show. Refer to Fair Housing for additional requirements for multi-family dwelling units Chapter 11-B.



Section 11-12 Theme Park or an Entertainment Complex

- In lieu of Florida parking space design (11-4.6) provide parking spaces that comply with the alternative design of Figure 9b (96 wide, 5 feet access aisle)
- When the alternative parking space designs are used, van accessible spaces shall be provided in compliance with 11-4.1.2.5.b




Section 11-12 Theme Park or an Entertainment Complex

 When several lots or areas are provided a single lot may be designated for parking by persons with disabilities



Requirements for recreation facilities are being finalized by the Access Board. Most of the large facilities are currently making their rides accessible.





A Very Special Thanks!!!

Accessibility Training Course Builders:

Diana Richardson, Neil Melick, Johnny Long, JR Harding, Larry Schneider, Pam Dorwarth, Leonard Lipka, Bob Leonard, Steve Corn, Jeffrey Gross, Sharon Mignardi, Bunny Armstrong, Steve Sensakovic, Tom Ricci, Andrea Williamson, Mary-Kathryn Smith, Bruce Ketcham, and Verda La Rue.