#### To: Energy TAC Re: Technical Advisory Manual Follow-up

FSEC submitted the revised TAM to Mo Madani on Dec. 15.

The revised TAM includes new blower door testing and duct testing reports. We have simplified to one report with appropriate check boxes and blanks for information related to performance or prescriptive. We worked with Tim Smith representing BOAF on this issue. This required a few times back and forth. For the next code cycle we should consider putting these test forms in the code itself.

Since Dec. 15 FSEC and BOAF have found two changes to recommend. This includes a field for whether an air handler is installed on the duct test form and the correct numerical reference on the envelope leakage test from [R402.4.1.2 vs. our old one which was missing a period R402.4.12]. We are attaching the updated forms for inclusion in the TAM.

We also greatly revised the ERI testing requirements in the Dec. 15 TAM. We removed the ERI range test and added the HERS tests as Wrightsoft suggested. We have updated the reference home characteristics reporting requirements to include "HERS Reference Home Auto-Generation Tests" minimum reporting requirement. This was added to make it consistent with the HERS test to be a requirement as suggested by WrightSoft. The latest reference document that we used for this is found in the link below. <a href="http://www.resnet.us/programs/FDS-01Pub002-2017\_final.pdf">http://www.resnet.us/programs/FDS-01Pub002-2017\_final.pdf</a>.

We maintained a spreadsheet that looks for specific pass/fail consequences based on Florida's specific ERI level of compliance and Florida's mandatory requirements based on having solar or not having solar. Some of the tests required for ERI are duplicated from the performance method so a software vendor applying for both methods should not be too encumbered.

We also made any changes pointed out by staff regarding section numbers, etc. I believe this should cover the requests and concerns made by the TAC.

One of the requests of the TAC was to not use the ERI form provided but to just provide the requirements given in the code for an ERI form. The Dec. 15 revised TAM removed the form and provided instructions to software vendors as to what to include. This is different than other residential methods but similar to the commercial building report submittal requirements.

#### Comments Received since Submitting the Revised Dec. 15 Technical Assistance Manual

Arlene Stewart pointed out that the code requires a checklist. The R405 form has historically had a location for an inspector to check off each item on the report. This was accidently omitted from the 2017 TAM. We are attaching a revised **Input Summary Checklist Report**. Based on Ms. Stewart's comments we have added the word "Checklist" to the title of the report. It is our strong recommendation that there not be a report and a separate checklist document that are repetitive. One document should continue to serve both purposes as has been done in the past.

Bill Wright has expressed concern that having software vendors create their own ERI report forms will create confusion and would prefer that the TAM include a suggested form. Mo has requested the TAC meet to determine its preference on these issues. There may not be many people submitting ERI method for permits during this code cycle so this may be something that can be modified again during the code cycle. Three suggestions for the current advice to software vendors:

- 1) Leave the TAM as is and reports may look different.
- 2) Keep the general format of the <u>RESNET developed report</u> but remove references to RESNET and make sure Florida specific changes are provided.
- 3) Use the report suggested by Mr. Wright. FSEC staff has made a few recommended modifications to be consistent with other reports but it keeps the general features and formatting suggested (See attached example). Some of the differences of the revised report:
  - The heading and footer were changed to be more consistent with the other residential TAM reports.
  - b) The information at the top of the page was formatted a little different to fit in an R406 Specific Requirements Section which provides the three requirements unique to the ERI method. The simulated location was also added as it tends to be an input officials examine. The climate label should state "Florida climate zone" as Florida has modified climate zones 1 & 2 from IECC.
  - c) The pie chart includes a break up of cost by end use instead of simply by fuel. Using fuel only would result in a pie chart showing 100% electric for the majority of Florida new homes.
  - d) Caveats for the cost breakdown were added to indicate the costs are based on standard operating conditions, the source of the energy price, and that on-site solar production is credited based on net-metering (or however the software credits it in the total).
  - e) The signature block at the bottom left includes a header titled 3<sup>rd</sup> Party Verifier to be consistent with Florida Statute.
  - f) Depending on the home's inputs, the report will include notes similar to the first page of the R405 performance report regarding any non-default entries for air handler leakage, air tightness entry, duct tightness entry and roof absorptance and emittance.
  - g) The ERI reports of our original November submitted TAM, RESNET and Mr. Wright show a 2<sup>nd</sup> page of abbreviated list of mandatory features verified by software. Concern was raised at FSEC that any partial list of mandatory items may be interpreted as a complete list. To address this potential issue, the revised report includes those elements that are specific to R406 requirements on page 1 of the ERI report. The TAM still requires software vendors to include the same Input Summary Checklist Report, Mandatory Requirements Report, Air Barrier Report and EPL display card that are required for other compliance methods. We believe Building Officials prefer seeing the same format report for these common items.
  - h) Mr. Wright attached a sample report for the HERS reference home components. We have included two options for TAC consideration. A one-page component document similar to the one suggested by Mr. Wright and one that mimics the input summary checklist report. The TAC should decide which one vendors will be required to provide. This report must be provided for permits upon request of a building official. We have also attached a rated home characteristic report that could be similarly requested. This could also take either format.

### **INPUT SUMMARY CHECKLIST REPORT**

PROJECT									
Title: Building Type: Owner Name: # of Units: Builder Name: Permit Office: Jurisdiction: Family Type: New/Existing: Comment:	Bedrooms: Conditioned Area: Total Stories: Worst Case: Rotate Angle: Cross Ventilation: Whole House Fan:		Address Type: Lot # Block/Subdivision: PlatBook: Street: County: City, State, Zip:						
CLIMATE									
Design Location		Design Temp Int Design 7.5 % 2.5 % Winter		Design Daily Temp loisture Range					
	BLOG	CKS							
√ Number Name	Area Volume								
1	, wed voiding								
SPACES									
√ Number Name 1	Area Volume Kitchen	Occupants Bedrooms	Infil ID Finished	Cooled Heated					
	FLOC	ORS							
√ # Floor Type ———	Space Perimeter	R-Value Area	Tile	Wood Carpet					
	ROO	OF							
√ # Type	Roof Gab Materials Area Are		SA Emitt Em Tested Test						
	ТТА	ГІС							
√ # Type	Ventilation Vent Ra	atio (1 in) Area	RBS IRCC						
	CEIL	ING							
# Ceiling Type	Space R-Val	ue Ins Type Are	a Framing Frac	Truss Type					

### **INPUT SUMMARY CHECKLIST REPORT**

					WAI	LLS					
	Orn	Adjacent ut To Wall :	Туре	Space	Cavity R-Value	Width Et In	Height Et In	Area_	Sheathing R-Value	Framing Sol Fraction Abs	ar Below or. Grade%
DOORS											
	#	Ornt	Door Type	Space		Storms	s U-Valu	e F	Width t In	Height Ft In	Area
					WIND	-014/8					
			(	Orientation sho			ed orientation				
	# 1 2	Wall Ornt ID Frame	Panes	NFRC	U-Factor S	SHGC Im	p Area	Ove Depth	erhang Separation	Int Shade	Screening
	3										
					GAR	AGE					
	#	Floor Area	Ceili	ing Area	Exposed W	all Perimeter	Avg. Wa	ll Height	Expose	d Wall Insulation	n
					INFILTE	RATION					
	#	Scope	Method	SLA	CFM 50	ELA	EqLA	ACH	ACH	150	
					HEATING	SYSTEM					
	#	System Type		Subtype		Efficier	ncy C	apacity		Block	Ducts
					COOLING	SYSTEM					
	#	System Type		Subtype		Efficiend	cy Capaci	ty A	Air Flow S	HR Block	Ducts

## **INPUT SUMMARY CHECKLIST REPORT**

OII FL	30ac												
					HOT W	ATER S	YSTEM						
$\sqrt{}$	#	System Type	SubType	Locati	on EF	С	ар	Use	SetPnt		Co	onservatio	n
				S	OLAR HO	T WATE	R SYSTI	EM					
$\checkmark$	FSEC				•					llecto		rage	
	Cert #	Company N	lame		System	Model #	C	ollector Mode	el# /	Area	Volu	ume	FEF
	None	None								ft²			
						DUCTS							
./		Sup			Return			Air	CFM 25	CFM			HVAC #
V	#	Location R	-Value Area	a Locat	ion Area	Leaka	ige Type	Handle	r TOT	OU	T QN	RLF	Heat Co
					TEM	PERATU	RES						
Program	nable The	rmostat: N			Ceiling Fan	s:							
Cooling Heating	[X] Ja [X] Ja [X] Ja	in [X] Feb in [X] Feb in [X] Feb	[X] Mar [X] Mar	[X] Apr [X] Apr [X] Apr	[X] May [X] May [X] May	[X] Jun [X] Jun [X] Jun	[X] Jul [X] Jul [X] Jul	[X] Aug [X] Aug [X] Aug	[X] Ser [X] Ser [X] Ser	2	[X] Oct [X] Oct [X] Oct	[X] Nov [X] Nov [X] Nov	[X] Dec [X] Dec [X] Dec
Venting	[X] Ja	in [X] Feb	[X] Mar	[X] Apr	[X] May	[X] Jun	[X] Jui	[X] Aug	[X] Ser	)	[X] Oct	[X] Nov	[X] Dec
Thermosta		ıle:						ours					
Schedule '	Туре		1	2	3 4	5	6	7	8	9	10	11	12
Cooling (V	VD)	AM PM	75 75	75 75	75 75 75 75	75 75	75 75	75 75	75 75	75 75	75 75	75 75	75 75
Cooling (V	VEH)	AM PM	75 75	75 75	75 75 75 75	75 75	75 75	75 75	75 75	75 75	75 75	75 75	75 75
Heating (V	VD)	AM PM	72 72	72 72	72 72 72 72	72 72	72 72	72 72	72 72	72 72	72 72	72 72	72 72
Heating (V	VEH)	AM PM	72 72	72 72	72 72 72 72	72 72	72 72	72 72	72 72	72 72	72 72	72 72	72 72

#### FLORIDA ENERGY EFFICIENCY CODE FOR BUILDING CONSTRUCTION

#### **Residential Energy Rating Index Method Compliance Alternative**

Permit Office: City Hall Jurisdiction: North Miami Beach Worst Case Orientation Calculation: No Permit Number: 12345678910 County: Miami-Dade

Florida Climate Zone: 1 Simulation Location: FL MIAMI INTL AP

**Property** 

Owner: Street Building Co.

25 Parkes Street

North Miami Beach, FL 33101

**R406 Specific Requirements** 

On-site Renewable Power? No

Envelope Levels Meet or Exceed: IECC-2009

R403.5.3 HW Pipe Insulation? Yes

Builder

Street Building Co.

2147 Southwest Barton Street

Miami FL 33101

Phone: 305-555-555

**ERI for this House** 

**50** 

**Maximum Allowed ERI** 

**PASS** 

**ERI of this House if Built to 2006 Code** 

100

## **Annual Energy Costs** by Use ■ Heating 28% Cooling 53% ■ Water Heating Lights and **Appliances**

#### Estimated Annual Energy Use Breakdown \*

Source	Use	Price**	Cost
Electricity	10942 kWh	\$ 0.1098/kWh	\$ 1201
Natural Gas	0 Therms	\$ 0.198/Therm	\$0
Oil	0 Gallons	NA	\$0
On-site power production	0 kWh	NA	\$ 0***
Total			\$ 1201

- \* Based on standard operating conditions
- \*\* Energy prices are 2016 state wide averages published by USDOE EIA
- \*\*\* Assumes net metering

#### 3rd Party Verifier:

This home is **projected** to meet the Energy Rating Index requirement of Section R406 of the Florida Building Code, Energy Conservation, 6th Edition (2017). Other mandatory measures must also be met.

Name: Joe Rater

Address: Liberty ERI Rating Co.

Phone: Signature:

Date:

Review of the plans and specifications covered by this calculation indicates compliance with the Florida Energy Code. Before construction is comple this building will be inspected for compliance with Section 553,908 Florida Statutes.

BUILDING OFFICIAL: DATE:

te	OF THE STATE
1	
GRE	
H	OD WE TRUST

- Compliance requires the air handler enclosure qualifies as certified factory-sealed in accordance with R403.3.2.1.
- Compliance requires air tightness test demonstrating an ACH50 <= 5.4 ACH50 conducted according to R402.4.1.2.
- ANSI/RESNET/ICC 380 compliance requires a duct leakage test report confirming a leakage rate to outdoors of <= 2.5 cfm/100ft<sup>2</sup>.
- ANSI/RESNET/ICC 301 compliance requires a tested roof absorptance of 0.76 and a tested roof emittance of 0.90.

#### ERI REFERENCE DESIGN BUILDING COMPONENT CHARACTERISTICS REPORT

PROJECT									
Title: Building Owner N # of Unit Builder N Permit C Jurisdict Family T New/Exi Commel	Name: ts: Name: Office: tion: Type: isting:		Bedrooms: Conditioned Area: Total Stories: Worst Case: Rotate Angle: Cross Ventilation: Whole House Fan:		Lot # Block/ PlatBo Street County				
CLIMATE									
$\sqrt{}$	Design Location	TMY Site		Design Temp 7.5 % 2.5 %	Int Design Temp Winter Summe		Design Daily Temp Moisture Range		
,			BLOC	CKS					
V	Number Name	Area	Volume						
	1								
,	SPACES								
	Number Name	Area \	/olume Kitchen	Occupants	Bedrooms Inf	il ID Finished	Cooled Heate		
			FLOC	RS					
	# Floor Type	Space	Perimeter	R-Value	Area U-Fa	ctor T	ile Wood Carpet		
			ROC	)F					
$\checkmark$	# Type	Materials	Roof Gab Area Are		Solar SA Absor. Tes		Emitt Deck Pitch ested Insul. (deg)		
			ATT	IC					
	# Туре	Ventilati	on Vent Rat	tio (1 in)	Area RBS	IRCC			
			CEILI	NG					
	# Ceiling Ty	pe Space	R-Value	Ins Type	Area U-Factor	Framing Frac	Truss Type		

### ERI REFERENCE DESIGN BUILDING COMPONENT CHARACTERISTICS REPORT

					WA	LLS					
#12345	Orn	Adjacent t To Wall	Туре	Space Cav	vity Width alue Ft	n Heigh In Ft In		U-Factor	Sheathing R-Value	Framing Sola Fraction Abso	ar Below or. Grade%
					DO	ORS					
$\overline{}$	#	Ornt	Door Type	Space		Storm	s U-Val	ue F	Width t In	Height Ft In	Area
	WINDOWS Orientation shown is the entered, Proposed orientation.										
	# 1 2 3 4	Wall Ornt ID Frame	Panes	NFRC	U-Factor			Ove	rhang Separation	Int Shade	Screening
					GAF	RAGE					
	#	Floor Area	Ce	eiling Area	Exposed \	Vall Perimeter	Avg. W	all Height	Expose	d Wall Insulation	า
					INFILT	RATION					
<u> </u>	#	Scope	Method	SLA	CFM 50	ELA	EqLA	ACH	ACH	50	
					HEATING	SYSTEM					
$\overline{}$	#	System Type		Subtype		Efficie	ncy	Capacity		Block	Ducts
/					COOLING	SYSTEM					
	#	System Type		Subtype		Efficien	cy Capac	city A	ir Flow Sh	HR Block	Ducts

### ERI REFERENCE DESIGN BUILDING COMPONENT CHARACTERISTICS REPORT

					HOT W	ATER SY	'STEM					
$\vee$	# 5	System Type	SubType	Location	on EF	C	ар	Use	SetPnt		Conservatio	n
				S	OLAR HO	T WATE	R SYSTE	EM .				
$\checkmark$	FSEC Cert #	Company Na	me		System	Model #	Co	llector Mode			torage olume	FEF
	None	None								ft²		
						DUCTS						
$\checkmark$	#	Suppl Location R-\	ly /alue Area		Return on Area	Leaka	де Туре	Air Handler		CFM25 OUT C	QN RLF	HVAC # Heat Cod
					TEM	PERATU	RES					
Program	nable Thern	nostat: N			Ceiling Fan	s:						
Cooling Heating Venting	[X] Jan [X] Jan [X] Jan	[X] Feb [X] Feb [X] Feb	[X] Mar [X] Mar [X] Mar	[X] Apr [X] Apr [X] Apr	[X] May [X] May [X] May	[X] Jun [X] Jun [X] Jun	[X] Jul [X] Jul [X] Jul	[X] Aug [X] Aug [X] Aug	[X] Sep [X] Sep [X] Sep	[X] Oct [X] Oct [X] Oct	[X] Nov [X] Nov [X] Nov	[X] Dec [X] Dec [X] Dec
Thermosta Schedule	at Schedule Type	:	1	2	3 4	5	Ho 6	ours 7	8	9 10	0 11	12
Cooling (V	VD)	AM PM	75 75	75 7 75 7	75 75 75 75	75 75	75 75	75 75	75 75	75 75 75 75	5 75 5 75	75 75
Cooling (V	VEH)	AM PM	75 75	75 7 75 7	75 75 75 75	75 75	75 75	75 75	75 75	75 75 75 75	5 75 5 75	75 75
Heating (V	VD)	AM PM	72 72	72 72	72 72 72 72	72 72	72 72	72 72	72 72	72 72 72 72	2 72 2 72	72 72
Heating (V	VEH)	AM PM	72 72	72 7 72 7	72 72 72 72	72 72	72 72	72 72	72 72	72 7: 72 7:	2 72 2 72	72 72

## **Building Component Characteristics Report**

[OWNER] [ADDRESS] [CITY], [STATE] [ZIP] Title:

TMY City:

ERI Reference Design

Above-grade Walls (Uo)

Above-grade Wall Solar Absorptance

Above-grade Wall Infrared Emittance

Basement Walls (Uo)

Above-grade Floors (Uo)

Slab Insulation R-Value

Ceilings (Uo)

Roof Solar Absorptance

Roof Infrared Emittance

Attic Vent Area (ft2)

Crawlspace Vent Area (ft2)

Exposed Masonry Floor Area (ft²)

Carpet & Pad R-Value

Door Area (ft2)

Door U-Factor

North Window Area (ft2)

South Window Area (ft2)

East Window Area (ft2)

West Window Area (ft2)

Window U-Factor

Window SHGC (Heating)

Window SHGC (Cooling)

ACH50

Internal Gains Sensible (Btu/day)

Internal Gains latent (Btu/day)

Internal Gains Total (Btu/day)

Labeled Heating System Rating and Efficiency

Labeled Cooling System Rating and Efficiency

Air Distribution System Efficiency

Thermostat Type

**Heating Thermostat Settings** 

Cooling Thermostat Settings

68.0, 68.0, 68.0, 68.0, 68.0, 68.0, 68.0, 68.0 68.0, 68.0, 68.0, 68.0, 68.0, 68.0, 68.0, 68.0 68.0, 68.0, 68.0, 68.0, 68.0, 68.0, 68.0, 68.0

78.0, 78.0, 78.0, 78.0, 78.0, 78.0, 78.0, 78.0

78.0, 78.0, 78.0, 78.0, 78.0, 78.0, 78.0, 78.0

78.0, 78.0, 78.0, 78.0, 78.0, 78.0, 78.0, 78.0

### **ERI RATED DESIGN BUILDING COMPONENT CHARACTERISTICS REPORT**

PROJECT								
Title: Building Type: Owner Name: # of Units: Builder Name: Permit Office: Jurisdiction: Family Type: New/Existing: Comment:	Cor Tota Wo Rot Cro	drooms: nditioned Area: al Stories: rst Case: ate Angle: ss Ventilation: ole House Fan:			Address Type: Lot # Block/Subdivis PlatBook: Street: County: City, State, Zip	sion:		
CLIMATE								
V Design Location	TMY Site		Design Temp 7.5 % 2.5 %	Int Design Winter S	Temp He ummer Degr		Design Da Noisture	ily Temp Range
		BLO	CKS					
√ Number Name	Area V	olume						
1								
,		SPAC	CES					
1 Number Name	Area Volun	ne Kitchen	Occupants	Bedrooms	Infil ID	Finished	Cooled	Heated
		FLOC	DRS					
√ # Floor Type	Space	Perimeter	R-Value	Area		Tile	Wood	Carpet
		ROC	OF					
√ # Type	Materials	Roof Gab Area Are		Solar Absor.	SA Tested	Emitt Em Test		Pitch (deg)
			-10					
		АТТ	IC					
# Type	Ventilation	Vent Ra	itio (1 in)	Area I	RBS IRC	CC		
		CEIL	ING					
√ # Ceiling Type	Spa	ace R-Valı	ue Ins Ty	pe Area	ı Fram	ning Frac	Truss Type	9

### **ERI RATED DESIGN BUILDING COMPONENT CHARACTERISTICS REPORT**

					WA	LLS					
1	Orn	Adjacent t To V	√all Type	Space	Cavity R-Value	Width Ft In	Height Ft In	Area	Sheathing R-Value	Framing So Fraction Abs	lar Below sor Grade%
2 3 4											
5											
					DO	DRS					
	#	Ornt	Door Type	Space		Storm	ns U-Valu	e F	Width ft In	Height Ft In	Area
				Orientation sho	WIND own is the en		ed orientation				
/	#	Wall Ornt ID Fra	me Panes	NFRC	U-Factor	SHGC Im	np Area		erhang Separation	Int Shade	Screening
	1						,				<u> </u>
	2										
	4										
					GAR	AGE					
$\overline{}$	#	Floor Are	ea Ce	eiling Area	Exposed W	all Perimeter	Avg. Wa	all Height	Expose	d Wall Insulation	on
					INFILT	RATION					
$\checkmark$	#	Scope	Method	SLA	CFM 50	ELA	EqLA	ACH	ACH	150	
					HEATING	SYSTEM					
	#	System Type		Subtype		Efficie	ency (	Capacity		Block	Ducts
					COOLING	SYSTEM					
	#	System Type		Subtype		Efficier	ncy Capaci	ty A	Air Flow S	HR Block	Ducts

### **ERI RATED DESIGN BUILDING COMPONENT CHARACTERISTICS REPORT**

					HOT W	ATER S	YSTEM						
$\vee$	#	System Type	SubType	Location	on EF	С	ар	Use	SetPnt		Co	onservatio	n
SOLAR HOT WATER SYSTEM													
$\checkmark$	FSEC Cert #	Company Na	ame		System	Model #	Co	ollector Mode		Collecto Area		rage ume	FEF
	None	None								ft²			
DUCTS													
$\checkmark$	#	Supp Location R-	•		Return on Area	Leaka	age Type	Air Handle	CFM 25 r TOT	OL.		RLF	HVAC # Heat Coo
					TEM	PERATU	RES						
Program	able Thei	rmostat: N			Ceiling Fan	s:							
Cooling Heating Venting	[X] Jar [X] Jar [X] Jar	n [X] Feb n [X] Feb n [X] Feb	[X] Mar [X] Mar [X] Mar	[X] Apr [X] Apr [X] Apr	[X] May [X] May [X] May	[X] Jun [X] Jun [X] Jun	[X] Jul [X] Jul [X] Jul	[X] Aug [X] Aug [X] Aug	[X] Se [X] Se [X] Se	ep ep ep	[X] Oct [X] Oct [X] Oct	[X] Nov [X] Nov [X] Nov	[X] Dec [X] Dec [X] Dec
Thermosta Schedule		le:	1	2	3 4	5	Ho 6	ours 7	8	9	10	11	12
Cooling (V	VD)	AM PM	75 75	75 7 75 7	75 75 75 75	75 75	75 75	75 75	75 75	75 75	75 75	75 75	75 75
Cooling (V	VEH)	AM PM	75 75	75 7 75 7	75 75 75 75	75 75	75 75	75 75	75 75	75 75	75 75	75 75	75 75
Heating (V	VD)	AM PM	72 72	72 72	72 72 72 72	72 72	72 72	72 72	72 72	72 72	72 72	72 72	72 72
Heating (V	VEH)	AM PM	72 72	72 7 72 7	72 72 72 72	72 72	72 72	72 72	72 72	72 72	72 72	72 72	72 72

# **Envelope Leakage Test Report** (Blower Door Test)

Residential Prescriptive, Performance or ERI Method Compliance 2017 Florida Building Code, Energy Conservation, 6th Edition

	Jurisdiction:	Permit #:
Job Ir	nformation	
Builde	er: Community:	Lot:
Addre	2SS:	Unit:
City:	State:	Zip:
Air Le	eakage Test Results Passing results must meet either the Per	formance, Prescriptive, or ERI Method
$\cdots$	<b>PRESCRIPTIVE METHOD-</b> The building or dwelling unit shall be tested ges per hour at a pressure of 0.2 inch w.g. (50 pascals) in Climate Zones	
$\cdots$	PERFORMANCE or ERI METHOD- The building or dwelling unit shall be elected ACH(50) value, as shown on FORM R405-2017 (Performance) or ACH(50) specified on Form R405-2017-Energy Calc (Perform	r R406-2017 (ERI), section labeled as Infiltration, sub-section ACH50.
mı	$ \begin{array}{cccccccccccccccccccccccccccccccccccc$	Method for calculating building volume:  Retrieved from architectural plans  Code software calculated  Field measured and calculated
Testin 489.10	<b>4.1.2 Testing.</b> Testing shall be conducted in accordance with ANSI/RES g shall be conducted by either individuals as defined in Section 553.99 05(3)(f), (g), or (i) or an approved third party. A written report of the resided to the <i>code official</i> . Testing shall be performed at any time after created to the code official.	93(5) or (7), <i>Florida Statues</i> , or individuals licensed as set forth in Section sults of the test shall be signed by the party conducting the test and
1.Extercontrol 2.Dam measu 3.Inter 4.Extercontrol 5.Hear	ol measures. npers including exhaust, intake, makeup air, back draft and flue damp	rned off.
Testii	ng Company	
I hereb	oany Name:	with the 2017 6th Edition Florida Building Code Energy
Signa	ture of Tester:	Date of Test:
	ed Name of Tester:	
Licen	se/Certification #:	Issuing Authority:

# **Duct Leakage Test Report**

Residential Prescriptive, Performance or ERI Method Compliance 2017 Florida Building Code, Energy Conservation, 6th Edition

	Jurisdiction:		Permit #:	
Job Information				
Builder: C		Community:	Lot:	
Address:			Unit:	
City:		State:	Zip:	
Duct Leakage Test Results				
System 1 cfm25  System 2 cfm25  System 3 cfm25  Sum of any additional systems cfm25  Total of all systems cfm25  Total of all systems cfm25  Total of all systems cfm25  PASS  Duct tightness shall be verified by testing in acco		To qualify as "sequal to 0.04 if installed, Qn To method meets  Is the air han  Perform To qualify using proposed duct  Leakage Ty R405-2017 (Er	Prescriptive Method cfm25 (Total)  To qualify as "substantially leak free" Qn Total must be less than or equal to 0.04 if air handler unit is installed. If air handler unit is not installed, Qn Total must be less than or equal to 0.03. This testing method meets the requirements in accordance with Section R403.3.3.  Is the air handler unit installed during testing? YES (\$\frac{\sigma_0}{\sigma_0}\$) \Rightarrow NO (\$\frac{\sigma_0}{\sigma_0}\$)  Performance / ERI Method cfm25 (Out or Total)  To qualify using this method, Qn must not be greater than the proposed duct leakage Qn specified on Form R405-2017 or R406-2017.  Leakage Type selected on Form (Energy Calc) or R406-2017 (Energy Calc) or R406-2017	
553.993(5) or (7), Florida Statutes, or individuals licensed as set forth in Section 489.105(3)(f), (g) or (i), Florida Statutes.  Testing Company				
Company Name:Phone:Phone:  I hereby verify that the above duct leakage testing results are in accordance with the 2017 6th Edition Florida Building Code Energy Conservation requirements according to the compliance method selected above.				
Signat	cure of Tester:		Date of Test:	
Printed Name of Tester:				
Licens	se/Certification #:	ls	Issuing Authority:	