

## CHAPTER 14

# EXTERIOR WALLS

### SECTION 1401 GENERAL

**1401.1 Scope.** The provisions of this chapter shall establish the minimum requirements for exterior walls; *exterior wall* coverings; *exterior wall* openings; exterior windows and doors; architectural *trim*; balconies and similar projections; and bay and oriel windows.

### SECTION 1402 DEFINITIONS

**1402.1 Definitions.** The following terms are defined in Chapter 2:

ADHERED MASONRY VENEER.

ANCHORED MASONRY VENEER.

BACKING.

EXTERIOR INSULATION AND FINISH SYSTEMS (EIFS).

EXTERIOR INSULATION AND FINISH SYSTEMS (EIFS) WITH DRAINAGE.

EXTERIOR WALL.

EXTERIOR WALL COVERING.

EXTERIOR WALL ENVELOPE.

FENESTRATION.

FIBER-CEMENT SIDING.

HIGH-PRESSURE DECORATIVE EXTERIOR-GRADE COMPACT LAMINATE (HPL).

HIGH-PRESSURE DECORATIVE EXTERIOR-GRADE COMPACT LAMINATE (HPL) SYSTEM.

METAL COMPOSITE MATERIAL (MCM).

METAL COMPOSITE MATERIAL (MCM) SYSTEM.

POLYPROPYLENE SIDING.

PORCELAIN TILE.

VENEER.

VINYL SIDING.

WATER-RESISTIVE BARRIER.

### SECTION 1403 PERFORMANCE REQUIREMENTS

**1403.1 General.** The provisions of this section shall apply to exterior walls, wall coverings and components thereof.

**1403.2 Weather protection.** Exterior walls shall provide the building with a weather-resistant *exterior wall envelope*. The *exterior wall envelope* shall include flashing, as described in Section 1405.4. The *exterior wall envelope* shall be designed and constructed in such a manner as to prevent the accumulation of water within the wall assembly by providing a *water-resistive barrier* behind the exterior veneer, as described in Section 1404.2, and a means for draining water that enters the assembly to the exterior. Protection against condensation in the *exterior wall* assembly shall be provided in accordance with Section 1405.3.

#### Exceptions:

1. A weather-resistant *exterior wall envelope* shall not be required over concrete or masonry walls designed in accordance with Chapters 19 and 21, respectively.
2. Compliance with the requirements for a means of drainage, and the requirements of Sections 1404.2 and 1405.4, shall not be required for an *exterior wall envelope* that has been demonstrated through testing to resist wind-driven rain, including joints, penetrations and intersections with dissimilar materials, in accordance with ASTM E331 under the following conditions:
  - 2.1. *Exterior wall envelope* test assemblies shall include at least one opening, one control joint, one wall/cave interface and one wall sill. Tested openings and penetrations shall be representative of the intended end-use configuration.
  - 2.2. *Exterior wall envelope* test assemblies shall be at least 4 feet by 8 feet (1219 mm by 2438 mm) in size.
  - 2.3. *Exterior wall envelope* assemblies shall be tested at a minimum differential pressure of 6.24 pounds per square foot (psf) (0.297 kN/m<sup>2</sup>).
  - 2.4. *Exterior wall envelope* assemblies shall be subjected to a minimum test exposure duration of 2 hours.

The *exterior wall envelope* design shall be considered to resist wind-driven rain where the results of testing indicate that water did not penetrate control joints in the *exterior wall envelope*, joints at the perimeter of openings or intersections of terminations with dissimilar materials.

3. Exterior insulation and finish systems (EIFS) complying with Section 1408.4.1.

## EXTERIOR WALLS

**[BS] 1403.3 Structural.** *Exterior walls*, and the associated openings, shall be designed and constructed to resist safely the superimposed loads required by Chapter 16.

**1403.4 Fire resistance.** *Exterior walls* shall be fire-resistance rated as required by other sections of this code with opening protection as required by Chapter 7.

**1403.5 Vertical and lateral flame propagation.** Exterior walls on buildings of Type I, II, III or IV construction that are greater than 40 feet (12 192 mm) in height above grade plane and contain a combustible *water-resistive barrier* shall be tested in accordance with and comply with the acceptance criteria of NFPA 285. For the purposes of this section, fenestration products and flashing of fenestration products shall not be considered part of the *water-resistive barrier*.

### Exceptions:

1. Walls in which the *water-resistive barrier* is the only combustible component and the *exterior wall* has a wall covering of brick, concrete, stone, terra cotta, stucco or steel with minimum thicknesses in accordance with Table 1405.2.
2. Walls in which the *water-resistive barrier* is the only combustible component and the *water-resistive barrier* has a peak heat release rate of less than 150 kW/m<sup>2</sup>, a total heat release of less than 20 MJ/m<sup>2</sup> and an effective heat of combustion of less than 18 MJ/kg as determined in accordance with ASTM E1354 and has a flame spread index of 25 or less and a smoke-developed index of 450 or less as determined in accordance with ASTM E84 or UL 723. The ASTM E1354 test shall be conducted on specimens at the thickness intended for use, in the horizontal orientation and at an incident radiant heat flux of 50 kW/m<sup>2</sup>.

**[BS] 1403.6 Flood resistance.** For buildings in flood hazard areas as established in Section 1612.3, *exterior walls* extending below the elevation required by Section 1612 shall be constructed with flood-damage-resistant materials.

**[BS] 1403.7 Flood resistance for coastal high-hazard areas and coastal A zones.** For buildings in coastal high-hazard areas and coastal A zones as established in Section 1612.3, electrical, mechanical and plumbing system components shall not be mounted on or penetrate through exterior walls that are designed to break away under flood loads.

**1403.8** In order to provide for inspection for termite infestation, clearance between exterior wall coverings and final

earth grade on the exterior of a building shall not be less than 6 inches (152 mm).

### Exceptions:

1. Paint or decorative cementitious finish less than  $\frac{5}{8}$  inch (17.1 mm) thick adhered directly to the masonry foundation sidewall.
2. Access or vehicle ramps which rise to the interior finish floor elevation for the width of such ramps only.
3. A 4-inch (102 mm) inspection space above patio and garage slabs and entry areas.
4. If the patio has been soil treated for termites, the finish elevation may match the building interior finish floor elevations on masonry construction only.
5. Masonry veneers constructed in accordance with Section 2114.2.

## SECTION 1404 MATERIALS

**1404.1 General.** Materials used for the construction of *exterior walls* shall comply with the provisions of this section. Materials not prescribed herein shall be permitted, provided that any such alternative has been *approved*.

**1404.2 Water-resistive barrier.** Not fewer than one layer of No.15 asphalt felt, complying with ASTM D226 for Type 1 felt or other *approved* materials, shall be attached to the studs or sheathing, with flashing as described in Section 1405.4, in such a manner as to provide a continuous *water-resistive barrier* behind the *exterior wall veneer*.

**[BS] 1404.3 Wood.** *Exterior walls* of wood construction shall be designed and constructed in accordance with Chapter 23.

**[BS] 1404.3.1 Basic hardboard.** Basic hardboard shall conform to the requirements of AHA A135.4.

**[BS] 1404.3.2 Hardboard siding.** Hardboard siding shall conform to the requirements of AHA A135.6 and, where used structurally, shall be so identified by the *label* of an *approved* agency.

**[BS] 1404.4 Masonry.** *Exterior walls* of masonry construction shall be designed and constructed in accordance with this section and Chapter 21. Masonry units, mortar and metal accessories used in anchored and adhered veneer shall meet the physical requirements of Chapter 21. The backing of anchored and adhered veneer shall be of concrete, masonry, steel framing or wood framing. Continuous insulation meet-

The following shall be deemed to meet the class specified:

- Class I: Sheet polyethylene, nonperforated aluminum foil with a perm rating of less than or equal to 0.1.
- Class II: Kraft-faced fiberglass batts or paint with a perm rating greater than 0.1 and less than or equal to 1.0.
- Class III: Latex or enamel paint with a perm rating of greater than 1.0 and less than or equal to 10.0.

**1405.3.4 Minimum clear airspaces and vented openings for vented cladding.** For the purposes of this section, vented cladding shall include the following minimum clear airspaces:

1. Vinyl lap or horizontal aluminum siding applied over a weather-resistive barrier as specified in this chapter.
2. Brick veneer with a clear airspace as specified in this code.
3. Other *approved* vented claddings.

✱ **1405.4 Flashing.** Flashing shall be installed in such a manner so as to prevent moisture from entering the wall or to redirect that moisture to the exterior. Flashing shall be installed at the perimeters of exterior door and window assemblies, penetrations and terminations of *exterior wall* assemblies, *exterior wall* intersections with roofs, chimneys, porches, decks, balconies and similar projections and at built-in gutters and similar locations where moisture could enter the wall. Flashing with projecting flanges shall be installed on both sides and the ends of copings, under sills and continuously above projecting *trim*. When self-adhered membranes are used as flashing in wall assemblies, those self-adhered flashings shall comply with AAMA-711. When fluid applied membranes are used as flashing for exterior wall openings, those fluid applied membrane flashings shall comply with AAMA 714. Approved corrosion-resistant flashing shall be applied at the following locations:

1. Exterior window and door openings. Flashing at exterior window and door openings shall extend to the surface of the exterior wall finish or to the water-resistive barrier for subsequent drainage. Flashing at exterior window and door openings shall be installed in accordance with one or more of the following:
  - 1.1. The fenestration manufacturer's installation and flashing instructions, or for applications not addressed in the fenestration manufacturer's instructions, in accordance with the flashing manufacturer's instructions. Where flashing instructions or details are not provided, pan flashing shall be installed at the sill of exterior window and door openings. Pan flashing shall be sealed or sloped in such a manner as to direct water to the surface of the exterior wall finish or to the water-resistive barrier for subsequent drainage. Openings using pan flashing shall also incorporate flashing or protection at the head and sides.

1.2. In accordance with the flashing design or method of a registered design professional.

1.3. In accordance with other approved methods.

1.4. In accordance with FMA/AAMA 100, FMA/AAMA 200, FMA/WDMA 250, FMA/AAMA/WDMA 300 or FMA/AAMA/WDMA 400.

2. At the intersection of chimneys or other masonry construction with frame or stucco walls, with projecting lips on both sides under stucco copings.
3. Under and at the ends of masonry, wood or metal copings and sills.
4. Continuously above all projecting wood trim.
5. Where exterior porches, decks or stairs attach to a wall or floor assembly of wood-frame construction.
6. At wall and roof intersections.
7. At built-in gutters.

**1405.4.1 Exterior wall pockets.** In exterior walls of buildings or structures, wall pockets or crevices in which moisture can accumulate shall be avoided or protected with caps or drips, or other *approved* means shall be provided to prevent water damage.

**1405.4.2 Masonry.** Flashing and weep holes in anchored veneer shall be located in the first course of masonry above finished ground level above the foundation wall or slab, and other points of support, including structural floors, shelf angles and lintels where anchored veneers are designed in accordance with Section 1405.6.

**1405.5 Wood veneers.** Wood veneers on exterior walls of buildings of Type I, II, III and IV construction shall be not less than 1 inch (25 mm) nominal thickness, 0.438-inch (11.1 mm) exterior hardboard siding or 0.375-inch (9.5 mm) exterior-type wood structural panels or particleboard and shall conform to the following:

1. The veneer shall not exceed 40 feet (12 190 mm) in height above grade. Where fire-retardant-treated wood is used, the height shall not exceed 60 feet (18 290 mm) in height above grade.
2. The veneer is attached to or furred from a noncombustible backing that is fire-resistance rated as required by other provisions of this code.
3. Where open or spaced wood veneers (without concealed spaces) are used, they shall not project more than 24 inches (610 mm) from the building wall.

**[BS] 1405.6 Anchored masonry veneer.** Anchored masonry veneer shall comply with the provisions of Sections 1405.6, 1405.7, 1405.8 and 1405.9 and Sections 12.1 and 12.2 of TMS 402/ACI 530/ASCE 5.

**[BS] 1405.6.1 Tolerances.** Anchored masonry veneers in accordance with Chapter 14 are not required to meet the tolerances in Article 3.3 F1 of TMS 602/ACI 530.1/ASCE 6.

**[BS] 1405.6.2 Seismic requirements.** Anchored masonry veneer located in Seismic Design Category C, D, E or F

## CHAPTER 17

# SPECIAL INSPECTIONS AND TESTS

### SECTION 1701 GENERAL

**1701.1 Scope.** The provisions of this chapter shall govern the quality, workmanship and requirements for materials covered. Materials of construction and tests shall conform to the applicable standards listed in this code.

**1701.2 New materials.** New building materials, equipment, appliances, systems or methods of construction not provided for in this code, and any material of questioned suitability proposed for use in the construction of a building or structure, shall be subjected to the tests prescribed in this chapter and in the *approved* rules to determine character, quality and limitations of use.

### SECTION 1702 DEFINITIONS

**1702.1 Definitions.** The following terms are defined in Chapter 2:

**APPROVED AGENCY.**

**APPROVED FABRICATOR.**

**CERTIFICATE OF COMPLIANCE.**

**DESIGNATED SEISMIC SYSTEM.**

**FABRICATED ITEM.**

**GARAGE DOOR MANUFACTURER.**

**INTUMESCENT FIRE-RESISTANT COATINGS.**

**MAIN WINDFORCE-RESISTING SYSTEM.**

**MASTIC FIRE-RESISTANT COATINGS.**

**SPECIAL INSPECTION.** Reserved.

**Continuous special inspection.** Reserved.

**Periodic special inspection.** Reserved.

**SPECIAL INSPECTOR.** Reserved.

**SPRAYED FIRE-RESISTANT MATERIALS.**

**STRUCTURAL OBSERVATION.** Reserved.

### SECTION 1703 APPROVALS

**1703.1 Approved agency.** An approved agency shall provide all information as necessary for the *building official* to determine that the agency meets the applicable requirements specified in Sections 1703.1.1 through 1703.1.3.

**1703.1.1 Independence.** An *approved agency* shall be objective, competent and independent from the contractor responsible for the work being inspected. The agency shall also disclose to the *building official* and the *registered design professional in responsible charge* possible conflicts of interest so that objectivity can be confirmed.

**1703.1.2 Equipment.** An *approved agency* shall have adequate equipment to perform required tests. The equipment shall be periodically calibrated.

**1703.1.3 Personnel.** An *approved agency* shall employ experienced personnel educated in conducting, supervising and evaluating tests and *special inspections*.

**1703.2 Written approval.** Any material, appliance, equipment, system or method of construction meeting the requirements of this code shall be *approved* in writing after satisfactory completion of the required tests and submission of required test reports.

**1703.3 Record of approval.** For any material, appliance, equipment, system or method of construction that has been *approved*, a record of such approval, including the conditions and limitations of the approval, shall be kept on file in the *building official's* office and shall be available for public review at appropriate times.

**1703.4 Performance.** Specific information consisting of test reports conducted by an *approved agency* in accordance with the appropriate referenced standards, or other such information as necessary, shall be provided for the *building official* to determine that the product, material or assembly meets the applicable code requirements.

**1703.4.1 Research and investigation.** Sufficient technical data shall be submitted to the *building official* to substantiate the proposed use of any product, material or assembly. If it is determined that the evidence submitted is satisfactory proof of performance for the use intended, the *building official* shall approve the use of the product, material or assembly subject to the requirements of this code. The costs, reports and investigations required under these provisions shall be paid by the owner or the owner's authorized agent.

**1703.4.2 Research reports.** Supporting data, where necessary to assist in the approval of products, materials or assemblies not specifically provided for in this code, shall consist of valid research reports from *approved* sources.

**1703.5 Labeling.** Products, materials or assemblies required to be *labeled* shall be *labeled* in accordance with the procedures set forth in Sections 1703.5.1 through 1703.5.4.

**1703.5.1 Testing.** An *approved agency* shall test a representative sample of the product, material or assembly being *labeled* to the relevant standard or standards. The *approved agency* shall maintain a record of the tests performed. The record shall provide sufficient detail to verify compliance with the test standard.

**1703.5.2 Inspection and identification.** The *approved agency* shall periodically perform an inspection, which shall be in-plant if necessary, of the product or material that is to be *labeled*. The inspection shall verify that the

simulates applicable loading and deformation conditions. For components that are not a part of the seismic force-resisting system, at a minimum the test load shall be equal to the specified factored design loads. For materials such as wood that have strengths that are dependent on load duration, the test load shall be adjusted to account for the difference in load duration of the test compared to the expected duration of the design loads being considered. For statically loaded components, the test load shall be left in place for a period of 24 hours. For components that carry dynamic loads (e.g., machine supports or fall arrest anchors), the load shall be left in place for a period consistent with the component's actual function. The structure shall be considered to have successfully met the test requirements where the following criteria are satisfied:

1. Under the design load, the deflection shall not exceed the limitations specified in Section 1604.3.
2. Within 24 hours after removal of the test load, the structure shall have recovered not less than 75 percent of the maximum deflection.
3. During and immediately after the test, the structure shall not show evidence of failure.

### SECTION 1709 PRECONSTRUCTION LOAD TESTS

**1709.1 General.** Where proposed construction is not capable of being designed by *approved* engineering analysis, or where proposed construction design method does not comply with the applicable material design standard, the system of construction or the structural unit and the connections shall be subjected to the tests prescribed in Section 1709. The *building official* shall accept certified reports of such tests conducted by an *approved* testing agency, provided that such tests meet the requirements of this code and *approved* procedures.

**1709.2 Load test procedures specified.** Where specific load test procedures, load factors and acceptance criteria are included in the applicable referenced standards, such test procedures, load factors and acceptance criteria shall apply. In the absence of specific test procedures, load factors or acceptance criteria, the corresponding provisions in Section 1709.3 shall apply.

**1709.3 Load test procedures not specified.** Where load test procedures are not specified in the applicable referenced standards, the load-bearing and deformation capacity of structural components and assemblies shall be determined on the basis of a test procedure developed by a *registered design professional* that simulates applicable loading and deformation conditions. For components and assemblies that are not a part of the seismic force-resisting system, the test shall be as specified in Section 1709.3.1. Load tests shall simulate the applicable loading conditions specified in Chapter 16.

**1709.3.1 Test procedure.** The test assembly shall be subjected to an increasing superimposed load equal to not less than two times the superimposed design load. The test load shall be left in place for a period of 24 hours. The tested assembly shall be considered to have successfully

met the test requirements if the assembly recovers not less than 75 percent of the maximum deflection within 24 hours after the removal of the test load. The test assembly shall then be reloaded and subjected to an increasing superimposed load until either structural failure occurs or the superimposed load is equal to two and one-half times the load at which the deflection limitations specified in Section 1709.3.2 were reached, or the load is equal to two and one-half times the superimposed design load. In the case of structural components and assemblies for which deflection limitations are not specified in Section 1709.3.2, the test specimen shall be subjected to an increasing superimposed load until structural failure occurs or the load is equal to two and one-half times the desired superimposed design load. The allowable superimposed design load shall be taken as the lesser of:

1. The load at the deflection limitation given in Section 1709.3.2.
2. The failure load divided by 2.5.
3. The maximum load applied divided by 2.5.

**1709.3.2 Deflection.** The deflection of structural members under the design load shall not exceed the limitations in Section 1604.3. The HVHZ shall comply with Section 1616.3.1.

**1709.4 Wall and partition assemblies.** *Load-bearing wall* and partition assemblies shall sustain the test load both with and without window framing. The test load shall include all design load components. Wall and partition assemblies shall be tested both with and without door and window framing.

**1709.5 Exterior window and door assemblies.** The design pressure rating of exterior windows and doors in buildings shall be determined in accordance with Section 1709.5.1 or 1709.5.2. For the purposes of this section, the required design pressure shall be determined using the allowable stress design load combinations of Section 1605.3.

**Exception:** Custom doors. Custom (one-of-a-kind) exterior door assemblies shall be tested by an approved testing laboratory or be designed and engineered in accordance with accepted engineering practices by a Florida registered design professional. Signed and sealed copies of the rational analysis and calculations shall be provided to the building official upon permit application.

**1709.5.1 Exterior windows and doors.** Exterior windows and sliding doors shall be tested and labeled as conforming to AAMA/WDMA/CSA101/I.S.2/A440 or TAS 202 (HVHZ shall comply with TAS 202 and ASTM E1300 or Section 2404). Exterior side-hinged doors shall be tested and labeled as conforming to AAMA/WDMA/CSA101/I.S.2/A440 or comply with Section 1709.5.2. Products tested and labeled as conforming to AAMA/WDMA/CSA 101/I.S.2/A440 shall not be subject to the requirements of Sections 2403.2 and 2403.3. Exterior windows and doors shall be labeled with a permanent label, marking, or etching providing traceability to the manufacturer and product. The following shall also be required either on a permanent label or on a temporary supplemental label applied by the manufacturer: information identifying the manufacturer, the product model/series number, positive and negative

design pressure rating, product maximum size tested, impact-resistant rating if applicable, Florida product approval number or Miami-Dade product approval number, applicable test standard(s), and approved product certification agency, testing laboratory, evaluation entity or Miami-Dade product approval.

The labels are limited to one design pressure rating per referenced standard. The temporary supplemental label shall remain on the window or door until final approval by the building official.

**Exceptions:**

1. Door assemblies installed in nonhabitable areas where the door assembly and area are designed to accept water infiltration need not be tested for water infiltration.
2. Door assemblies installed where the overhang (OH) ratio is equal to or more than 1 need not be tested for water infiltration. The overhang ratio shall be calculated by the following equation:

$$\text{OH ratio} = \text{OH Length} / \text{OH Height}$$

where:

OH length = The horizontal measure of how far an overhang over a door projects out from door surface.

OH height = The vertical measure of the distance from the door sill to the bottom of the overhang over a door.

3. Structural wind load design pressures for window and door assemblies other than the size tested in accordance with Section 1709.5.1 shall be permitted to be different than the design value of the tested assembly provided such different pressures are determined by accepted engineering analysis. All components of the alternate size assembly shall be the same as the tested or labeled assembly; however, lineal components shall be permitted to vary in length compared to the tested or labeled assembly.

- i. Operable windows and doors rated in this manner shall comply with the following:

1. For windows and doors (other than sliding or bi-fold), the frame area of the alternate size unit shall not exceed the frame area of the tested approved unit.
2. For sliding or bi-fold doors, the panel area of the alternate size unit shall not exceed the panel area of the tested approved unit.
3. Shall vary from the tested approved unit only in width, height or load requirements.
4. Shall not exceed 100 percent of the proportional deflection and fiber stress of the intermediate members of the approved unit.

5. Shall not exceed 100 percent of the concentrated load at the juncture of the intermediate members and the frame of the approved unit.
  6. Shall not exceed the air and water infiltration resistance of the tested approved unit.
  7. Shall not exceed the maximum cyclic pressure of the tested approved unit when tested in accordance with TAS 201 and TAS 203 or ASTM E1886 and ASTM E1996 where applicable.
- ii. Nonoperable windows and doors rated in this manner shall comply with the following:
    1. The frame area of the alternate size unit shall not exceed the frame area of the tested approved unit.
    2. Shall vary from the tested approved unit only in width, height or load requirements.
    3. The maximum uniform load distribution (ULD) of any side shall be equal to the uniform load carried by the side divided by the length of the side.
    4. The ULD of any member shall not exceed the ULD of the corresponding member of the tested approved unit.
    5. The ULD of each member shall be calculated in accordance with standard engineering analysis.
    6. Shall not exceed the air and water infiltration resistance of the tested approved unit.
    7. Shall not exceed the maximum cyclic pressure of the tested approved unit when tested in accordance with TAS 201 and TAS 203 or ASTM E1886 and ASTM E1996 where applicable.
  4. Pass-through windows for serving from a single-family kitchen, where protected by a roof overhang of 5 feet (1.5 m) or more shall be exempted from the requirements of the water infiltration test.

**1709.5.2 Exterior windows and door assemblies not provided for in Section 1709.5.1.** Exterior window and door assemblies shall be tested in accordance with ASTM E330 or TAS 202 (HVHZ shall comply with TAS 202). Exterior window and door assemblies containing glass shall comply with Section 2403. The design pressure for testing shall be calculated in accordance with Chapter 16. Each assembly shall be tested for 10 seconds at a load equal to 1.5 times the design pressure.

**Exceptions:**

1. Door assemblies installed in nonhabitable areas where the door assembly and area are designed to

accept water infiltration need not be tested for water infiltration.

2. Door assemblies installed where the overhang (OH) ratio is equal to or more than 1 need not be tested for water infiltration. The overhang ratio shall be calculated by the following equation:

OH ratio = OH Length/OH Height

where:

OH Length = The horizontal measure of how far an overhang over a door projects out from the door's surface.

OH Height = The vertical measure of the distance from the door's sill to the bottom of the overhang over a door.

3. For window and door assemblies tested in accordance with this section, structural wind load design pressures for window and door assemblies other than the size tested in accordance with this section shall be permitted to be different than the design value of the tested assembly provided such different pressures are determined by accepted engineering analysis. All components of the alternate size assembly shall be the same as the tested assembly except for length. Where engineering analysis is used, the glass shall comply with Section 2403.

#### 1709.5.2.1 Sectional garage doors and rolling doors.

Sectional garage doors and rolling doors shall be tested for determination of structural performance under uniform static air pressure difference in accordance with ANSI/DASMA 108, ASTM E330 Procedure A, or TAS 202. For sectional garage doors and rolling doors tested in accordance with ASTM E330, acceptance criteria shall be in accordance with ANSI/DASMA 108. (HVHZ shall comply with TAS 202.) Design pressures shall be determined from Table 1609.7(1) or ASCE 7. The design pressures, as determined from ASCE 7, are permitted to be multiplied by 0.6.

**1709.5.2.1.1 Garage door labeling.** Garage doors shall be labeled with a permanent label provided by the garage door manufacturer. The label shall identify the garage door manufacturer, the garage door model/series number, the positive and negative design pressure rating, indicate impact rated if applicable, the installation instruction drawing reference number, the Florida product approval or Miami-Dade product approval number if applicable, and the applicable test standards. The required garage door components for an approved garage door assembly may be indicated using a checklist form on the label. If a checklist format is used on the label, the door installer or the garage door manufacturer shall mark the selected components on the checklist that are required to assemble an approved garage door system. The installation instructions shall be provided and available on the job site.

**1709.5.3 Door components evaluated by an approved product evaluation entity, certification agency, testing laboratory or engineer** may be interchangeable in exterior door assemblies provided that the door components provide equal or greater structural performance as demonstrated by accepted engineering practices.

**1709.6 Skylights and sloped glazing.** Skylights and sloped glazing shall comply with the requirements of Chapter 24.

**1709.7 Test specimens.** Test specimens and construction shall be representative of the materials, workmanship and details normally used in practice. The properties of the materials used to construct the test assembly shall be determined on the basis of tests on samples taken from the load assembly or on representative samples of the materials used to construct the load test assembly. Required tests shall be conducted or witnessed by an *approved agency*.

**1709.8 Mullions.** Mullions or mullioned fenestration assemblies shall be tested by an approved testing laboratory in accordance with either ASTM E330, or TAS 202 (HVHZ shall comply with TAS 202), or shall be engineered using accepted engineering practice such as AAMA 450. Mullions tested as stand-alone units or qualified by engineering shall use performance criteria cited in Sections 1709.8.1, 1709.8.2 and 1709.8.3.

**1709.8.1 Load transfer.** Mullions shall be designed to transfer the design pressure loads applied by the window and door assemblies to the rough opening substrate.

**1709.8.2 Deflection.** Mullions shall be capable of resisting the design pressure loads applied by the window and door assemblies to be supported without deflecting more than  $L/175$ , for spans up to and including 13 feet 6 inches, and  $L/240 + \frac{1}{4}$  inch for spans over 13 feet 6 inches, where L is the span of the mullion in inches.

**1709.8.3 Structural safety factor.** Mullions that are tested by an approved testing laboratory shall be capable of resisting a load of 1.5 times the design pressure loads applied by the window and door assemblies to be supported. The design pressures, as determined from ASCE 7, are permitted to be multiplied by 0.6. Mullions that are qualified by engineering shall be capable of resisting the design pressure loads applied by the window and door assemblies to be supported without exceeding the allowable stress of the mullion elements.

**1709.8.4 Glazed curtain wall, window wall and storefront systems** shall be tested in accordance with the requirements of this section and the laboratory test requirements of the American Architectural Manufacturers Association (AAMA) Standard 501, HVHZ shall comply with Section 2411.3.2.1.1.

#### 1709.9 Impact-resistant coverings.

**1709.9.1 Labels.** A permanent label shall be provided by the product approval holder on all impact-resistant coverings.

**1709.9.2** The following information shall be included on the labels on impact-resistant coverings:

1. Product approval holder name and address.

2. All applicable methods of approval. Methods of approval include, but are not limited to Miami-Dade NOA; Florida Building Commission, TDI Product Evaluation; ICC-ES.
3. The test standard or standards specified in Section 1609.1.2, including standards referenced within the test standards specified in Section 1609.1.2 used to demonstrate code compliance.
4. For products with a Florida product approval number or a Miami-Dade County Building and Neighborhood Compliance Department Notice of Acceptance Number (NOA), such numbers shall be included on the label.

**1709.9.3 Location of label.** The location of the label on the impact-resistant covering shall be as follows:

1. Accordions: Bottom of the locking bar or center mate facing the exterior or outside.
2. Rollup: On the bottom of the hood facing the exterior or outside or on the bottom slat facing the exterior or outside.
3. Bahama Awning or Colonial Hinged: On the bottom, placed on the back of the shutter.
4. Panels: For metal and plastic panels, the label may be embossed or printed spaced not more than every 3 lineal feet on each panel. The label shall be applied by the holder of the product approval and shall face the exterior or outside.
5. Framed products: The label shall be on the side or bottom facing the exterior or outside.
6. Labels on all other products shall face the exterior or outside.

**1709.9.4 Installation.** All impact-resistant coverings shall be installed in accordance with the manufacturer's installation instructions and in accordance with the product approval. Installation instructions shall be provided and

shall be available to inspection personnel on the job site. Opening protection components, fasteners, and other parts evaluated by an approved product evaluation entity, certification agency, testing laboratory, architect, or engineer and approved by the holder of the product approval may be interchangeable in opening protection assemblies provided that the opening protection component(s) provide equal or greater structural performance and durability as demonstrated by testing in accordance with approved test standards.

#### **1709.10 Soffit.**

**1709.10.1 Product approval.** Manufactured soffit materials and systems shall be subject to statewide or local product approval as specified in *Florida Administrative Code* Rule 61G-20. The net free area of the manufactured soffit material or system shall be included in the product approval submittal documents.

**1709.10.2 Labels.** Individual manufactured soffit pieces shall be marked at not more than 4 feet (1.2 m) on center with a number or marking that ties the product back to the manufacturer.

**1709.10.3** The following information shall be included on the manufactured soffit material packaging or on the individual manufactured soffit material or system pieces:

1. Product approval holder and/or manufacturer name and city and state of manufacturing plant.
2. Product model number or name.
3. Method of approval and approval numbers as applicable. Methods of approval include, but are not limited to: Florida Building Commission FL #; Miami-Dade NOA; TDI Product Evaluation; and ICC-ES.
4. The test standard or standards specified in Chapter 14 used to demonstrate code compliance.
5. The net free area shall be included on the packaging or label.