## Florida Building Code 2010 Chapter 9 Fire Protection Systems Quiz

- 1. Provided a modification to a fire protection system is small, no approval is needed by the building or fire official
  - a. True
  - b. False
- 2. Every automatic sprinkler system must be monitored except
  - a. One and two family dwellings
  - b. Systems with fewer than 6 sprinkler heads
  - c. Jurisdictions that do not require Central Station Service as outlined in NFPA 72
  - d. Both A & B
  - e. All of the Above
  - f. None of the above, they always have to be monitored
- 3. A system designed to alert individuals of the potential threat from hazardous materials is referred to as a
  - a. Fire alarm system
  - b. Threat level assessment system
  - c. Emergency alarm system
  - d. Class D system
- 4. A Supervising Station is
  - a. A Central Station as defined in NFPA 72
  - b. A Remote Station as defined in NFPA 72
  - c. A facility that receives signals and at which personnel are in attendance at all times to respond to these signals
  - d. A constantly attended station with trained personnel available to respond immediately to the emergency
- 5. Which of the following is not a mandatory requirement to be included on shop drawings?
  - a. Battery Calculations
  - b. The name of the Authority Having Jurisdiction
  - c. Floor plans
  - d. Detailed information from manufacturer's data sheets identifying the equipment being installed
- 6. Because fire alarm designs are dictated by code, they do not have to comply with the guidelines for accessibility.
  - a. True
  - b. False
- 7. Because of new types of construction and the advent of zoning and zoned reporting, there is no longer a need for any of the fire alarm equipment to be red in color.
  - a. True
  - b. False

- 8. When a building is fully sprinklered with an approved supervised sprinkler system, there is no requirement for a smoke detector to be installed above the control equipment.
  - a. True
  - b. False
- 9. Protective Covers installed on alarm boxes must always be provided with a local annunciator to indicate when the cover has been tampered with or dislodged.
  - a. True
  - b. False
- 10. Fire alarm systems required by Chapter 9, or by the Florida Fire Prevention Code must be monitored by an approved Central Station in accordance with NFPA 72
  - a. True
  - b. False

## Answers

- 1. B
- 2. D
- 3. C
- 4. C
- 5. B
- 6. B
- 7. B
- 8. A
- 9. B
- 10. B