

DHW Test Results:

Software Name: EnergyGauge v.4.0

User input data fields indicated by pale yellow
Test result fields indicated by pale green

Raw Results:

Minnesota	Energy Use (therms)	Florida	Energy Use (therms)
DHW-MN-56-2	204	DHW-FL-56-2	124
DHW-MN-56-4	263	DHW-FL-56-4	154
DHW-MN-62-2	184	DHW-FL-62-2	107

Test Cases:	% Change	Average	Range Min	Range Max	Pass/Fail
MN,0.56,4 (delta)	28.9%	29.3%	26.5%	32.2%	pass
MN,0.62,2 (delta)	-9.8%	-9.3%	-11.8%	-6.8%	pass
FL,0.56,4 (delta)	24.2%	24.1%	19.1%	29.1%	pass
FL,0.62,2 (delta)	-13.7%	-13.6%	-19.5%	-7.7%	pass
% [(MN-FL)/(MN)]	39.2%	37.0%	28.9%	45.1%	pass

	MBtu	Average	Range Min	Range Max	Pass/Fail
MN,0.56,2 (MBtu)	20.4	20.1	18.2	22.0	pass
FL,0.56,2 (MBtu)	12.4	12.7	10.9	14.4	pass
MN-FL (MBtu)	8	7.4	5.5	9.4	pass



