



[illegible]

GENERAL	
EXIST	- EXISTING TO REMAIN
EXP	- EXPOSED
FD	- FLOOR DRAIN
FE	- FIRE EXTINGUISHER
MFR	- MANUFACTURER
TH	- THRESHOLD
FLOORING	
CAR1	- COMMERCIAL GRADE CARPET (24"x24" SQUARES)
VCT	- VINYL CHLORIDE TILE (12"x12")
TILE	- PORCELAIN FLOOR TILE (6"x6")
BASE	
RB	- 4" RUBBER BASE
WALLS	
CB	- CEMENT BACKER BOARD BEHIND WALL TILE
FE	- SEMI-RECESSED ALUMINUM FIRE EXTINGUISHER CABINET
MWP	- METAL WALL PANEL
GB	- 5/8" GYPSUM BOARD
PNT	- INTERIOR LATEX PAINT
TCL2	- CERAMIC WALL TILE @ 6'-0" A.F.F w/ BULLNOSE CAP (4"x4")
CEILINGS	
ACT1	- LAY-IN ACOUSTICAL CEILING TILE 2'x2'-WHITE
GYP	- 5/8" GYP BOARD; PRIMED & PAINTED
DOORS	
ALUM	- ALUMINUM STORE FRONT SYSTEM
HM	- HOLLOW METAL FRAME
METAL	- INSULATED METAL DOOR
FINISH SCHEDULE NOTES	
1.	SEE REFLECTED CEILING PLAN AND DETAILS FOR EXACT CEILING HEIGHT LOCATIONS.
2.	ANTI-FRACTURE MAT SHALL BE INSTALLED UNDER ALL FLOOR TILE SURFACES.
3.	CONCRETE BACKER BOARD SHALL BE INSTALLED BEHIND ALL WALL TILE.



A1.11

THIS DOCUMENT CONTAINS UNCLASSIFIED AND PROPRIETARY INFORMATION. ALL OF WHICH IS EXPRESSLY PROVIDED BY AVCON, INC. FOR USE BY THE INTENDED RECIPIENT. ANY OTHER USE OF THIS DOCUMENT IN WHOLE OR IN PART, WITHOUT THE EXPRESS WRITTEN CONSENT OF AVCON, INC., FOR ANY DISTRIBUTION, REDUPLICATION, OR OTHER USE OF THIS DOCUMENT, IS STRICTLY PROHIBITED.