

Schindler Elevator Corporation**Traction Elevator Specification Summary**

Earth Remedies
310 E Bradford Rd
Tallahassee, FL 32303

Project Information:
Opportunity ID: 0201685036-AA
Unit(s) in Estimate: 01
Units in Bank: 01
Product Code: 450
Sales Office: 9686
Installation Office: 9686

Sales Rep Information:
Chris Cornelius
9143 Philips Highway
Suite 260
Jacksonville, FL 32256
Phone: (904) 880-4922 Ext 223
Fax: (904) 880-4916
Chris.Cornelius@schindler.com

Product:	Schindler 3300	Opening Size:	3 Ft. 0.00 In. X 7 Ft. 0.00 In.
Application:	3300 MRL	Cab Height:	7 Ft. 9 In.
Capacity:	2100 lbs General Purpose	Cab Type:	3300
Speed:	100 FP	Pit Depth:	5 Ft. 0 In.
Travel:	12 Ft. 0.00 In.	Overhead:	12 Ft. 7 In.
Cwt Location:	Side	Inside Cab Width:	5' 9 15/16"
Stops:	2 (2 Front / 0 Rear)	Inside Cab Depth:	4' 4 13/16"
Power Supply:	208 Volts 60 Hz 3 Phase	Hoistway Width:	7 Ft. 6.00 In.
Sprinklers In Hoistway:	N	Hoistway Depth:	5 Ft. 9.00 In.
Doors:	Two Speed Side Opening 01 LH	Seismic Equipment:	N
		NFPA Code Year:	2013

Cab:

Cab Walls LH Side: Laminate - type to be defined
Cab Walls RH Side: Laminate - type to be defined
Cab Walls Rear: Laminate - type to be defined
Base, Frieze: Aluminum
Front Return, Transom: #4 Stainless Steel
Cab Doors: #4 Stainless Steel
Canopy: Schindler
Ceiling Type: LED Down Light
Ceiling Finish: Stainless Steel #4
Cab Threshold: Aluminum
Threshold Extensions:
Handrail Type: Straight Rectangular
Handrail Finish: Brushed Aluminum
Handrail Location: Rear
Handrail Row Qty: 1
Platform Recess: 0.375
Protective Pads: None
Protective Pads Source: None
Cab Finished Floor: Carpet By Others

Cab Fixtures:

Type: Standard
Finish: #4 Stainless Steel
(1) L.E.D. Car Position Indicator
1 Main COP
(1) Car Lantern(s)
Certificate Frame

Features:

Follow IBC - 2015
Audible Gong (Std)
Infrared Door Protection(Std)
Phase Monitor Relay(Std)
Independent Service/HES (Std)
Top Exit Lock
FER Door Operator
T127 Rails
Keyed Emergency Stop Switch
Top Exit Switch
ADA Compliant Phone
Sliding Guide Shoes
1 Speed Fan
2 Hoistway Access Switches
Firefighter's Service Phase 2
Class B Fire Rating For Cab
Top Exit Guard
Smoke Detector Provisions
1 Intermediate Support - by Customer
Intermediate Support(s): 1
Automatic Evacuation
Pit Ladder Source: GC
STM - With Fire Retardant

Entrances:

Emergency Escutcheons
Doors:
(2) #4 Stainless Steel
Frames:
(2) #4 Stainless Steel
Sills:
(2) Aluminum
Sill Mounting:
(2) Easy Match

Hall Fixtures:

Hall Fixtures Type
Jamb Mounted
Hall Fixtures Finish
(2) #4 SS Push Buttons
(1) Separate FER Switch

New Product Service:

12 Months, 8 Hours Callback

This bid is subject to change after forty-five (45) days.

Visit Our Website @ www.us.schindler.com

06/12/20

8:35AM

2020.2