

ENERGY PERFORMANCE LEVEL (EPL) DISPLAY CARD

ESTIMATED ENERGY PERFORMANCE INDEX* = 80

The lower the EnergyPerformance Index, the more efficient the home.

123 Main Street, Orlando, FL, 32922-

<p>1. New construction or existing 2. Single family or multiple family 3. Number of units, if multiple family 4. Number of Bedrooms 5. Is this a worst case? 6. Conditioned floor area (ft²)</p>	<p>New (From Plans) Single-family 1 6 No 2400</p>	<p>9. Wall Types a. Frame - Wood, Exterior b. Concrete Block - Int Insul, Exterior c. Frame - Wood, Adjacent d. N/A</p>	<p>Insulation R=13.0 R=5.0 R=13.0 R=</p>	<p>Area 1230.00 ft² 944.00 ft² 176.00 ft² ft²</p>																													
<p>7. Windows**</p> <table border="0" style="width: 100%;"> <tr> <td style="width: 15%;">a. U-Factor:</td> <td style="width: 45%;">Dbl, U=0.75</td> <td style="width: 40%;">276.00 ft²</td> </tr> <tr> <td>SHGC:</td> <td>SHGC=0.40</td> <td></td> </tr> <tr> <td>b. U-Factor:</td> <td>Dbl, U=0.60</td> <td>40.00 ft²</td> </tr> <tr> <td>SHGC:</td> <td>SHGC=0.30</td> <td></td> </tr> <tr> <td>c. U-Factor:</td> <td>Dbl, U=0.50</td> <td>40.00 ft²</td> </tr> <tr> <td>SHGC:</td> <td>SHGC=0.35</td> <td></td> </tr> <tr> <td>d. U-Factor:</td> <td>other (see details)</td> <td>60.00 ft²</td> </tr> <tr> <td>SHGC:</td> <td>other (see details)</td> <td></td> </tr> <tr> <td colspan="2">Area Weighted Average Overhang Depth:</td> <td>2.000 ft.</td> </tr> <tr> <td colspan="2">Area Weighted Average SHGC:</td> <td>0.406</td> </tr> </table>	a. U-Factor:	Dbl, U=0.75	276.00 ft ²	SHGC:	SHGC=0.40		b. U-Factor:	Dbl, U=0.60	40.00 ft ²	SHGC:	SHGC=0.30		c. U-Factor:	Dbl, U=0.50	40.00 ft ²	SHGC:	SHGC=0.35		d. U-Factor:	other (see details)	60.00 ft ²	SHGC:	other (see details)		Area Weighted Average Overhang Depth:		2.000 ft.	Area Weighted Average SHGC:		0.406	<p>10. Ceiling Types a. Under Attic (Vented) b. N/A c. N/A</p>	<p>Insulation R=30.0 R= R=</p>	<p>Area 1200.00 ft² ft² ft²</p>
a. U-Factor:	Dbl, U=0.75	276.00 ft ²																															
SHGC:	SHGC=0.40																																
b. U-Factor:	Dbl, U=0.60	40.00 ft ²																															
SHGC:	SHGC=0.30																																
c. U-Factor:	Dbl, U=0.50	40.00 ft ²																															
SHGC:	SHGC=0.35																																
d. U-Factor:	other (see details)	60.00 ft ²																															
SHGC:	other (see details)																																
Area Weighted Average Overhang Depth:		2.000 ft.																															
Area Weighted Average SHGC:		0.406																															
<p>8. Floor Types</p> <table border="0" style="width: 100%;"> <tr> <td style="width: 15%;">a. Slab-On-Grade Edge Insulation</td> <td style="width: 45%;">R=0.0</td> <td style="width: 40%;">1200.00 ft²</td> </tr> <tr> <td>b. Interior Floor</td> <td>R=0.0</td> <td>1200.00 ft²</td> </tr> <tr> <td>c. N/A</td> <td>R=</td> <td>ft²</td> </tr> </table>	a. Slab-On-Grade Edge Insulation	R=0.0	1200.00 ft ²	b. Interior Floor	R=0.0	1200.00 ft ²	c. N/A	R=	ft ²	<p>11. Ducts a. Sup: Main, Ret: Main, AH: Main b. Sup: Attic, Ret: Attic, AH: 2nd Floor</p>	<p>R 6 6</p>	<p>ft² 240 240</p>																					
a. Slab-On-Grade Edge Insulation	R=0.0	1200.00 ft ²																															
b. Interior Floor	R=0.0	1200.00 ft ²																															
c. N/A	R=	ft ²																															
<p>Area Weighted Average Overhang Depth: Area Weighted Average SHGC:</p>	<p>2.000 ft. 0.406</p>	<p>12. Cooling systems a. Central Unit b. Central Unit</p>	<p>kBtu/hr 20.0 18.0</p>	<p>Efficiency SEER:13.00 SEER:13.00</p>																													
<p>Area Weighted Average Overhang Depth: Area Weighted Average SHGC:</p>	<p>2.000 ft. 0.406</p>	<p>13. Heating systems a. Electric Heat Pump b. Natural Gas Furnace</p>	<p>kBtu/hr 20.0 18.0</p>	<p>Efficiency HSPF:7.70 AFUE:0.78</p>																													
<p>Area Weighted Average Overhang Depth: Area Weighted Average SHGC:</p>	<p>2.000 ft. 0.406</p>	<p>14. Hot water systems a. Electric b. Conservation features None</p>	<p>Cap: 50 gallons EF: 0.9</p>	<p>Pstat</p>																													
<p>Area Weighted Average Overhang Depth: Area Weighted Average SHGC:</p>	<p>2.000 ft. 0.406</p>	<p>15. Credits</p>	<p>Pstat</p>	<p>Pstat</p>																													

I certify that this home has complied with the Florida Energy Efficiency Code for Building Construction through the above energy saving features which will be installed (or exceeded) in this home before final inspection. Otherwise, a new EPL Display Card will be completed based on installed Code compliant features.

Builder Signature: _____ Date: _____
Address of New Home: _____ City/FL Zip: _____



*Note: This is not a Building Energy Rating. If your Index is below 70, your home may qualify for energy efficient mortgage (EEM) incentives if you obtain a Florida EnergyGauge Rating. Contact the EnergyGauge Hotline at (321) 638-1492 or see the EnergyGauge web site at energygauge.com for information and a list of certified Raters. For information about the Florida Building Code, Energy Conservation, contact the Florida Building Commission's support staff.

**Label required by Section 303.1.3 of the Florida Building Code, Energy Conservation, if not DEFAULT.

** Software Title and Version Here ** Section 405.4.1 Compliant Software