

## Evaluation Report "Wind & Water Seal+™" Roof Underlayment

**Manufacturer:**  
**MFM Building Products Corp.**

525 Orange Street  
Coshocton, Ohio 43812  
(740) 622-2645

*for*

**Florida Product Approval**

**# FL 11842.3 R3**

**Florida Building Code 5th Edition (2014)**

**Method: 1 - D**

**Category: Roofing**

**Sub - Category: Underlayment**


**Product:** "Wind & Water Seal+™"  
**Description:** Self-Adhered Underlayment

### Prepared by:

James L. Buckner, P.E., SECB  
Florida Professional Engineer # 31242  
Florida Evaluation ANE ID: 1916  
Project Manager: Diana Galloway  
Report No. 15-115-W&WS+-ER  
*(Revises 11-182- W&WS+-ER)*  
Date: 4 / 02 / 15

### Contents:

Evaluation Report                      Pages 1 – 5



A handwritten signature in black ink, appearing to read "James L. Buckner".

Digitally Signed by: James L. Buckner, P.E.

<b>Manufacturer:</b>	MFM Building Products Corp.
<b>Product Name:</b>	“Wind & Water Seal+™”
<b>Product Category:</b>	Roofing
<b>Product Sub-Category</b>	Underlayment
<b>Compliance Method:</b>	State Product Approval Rule 61G20-3.005 (1) (d)
<b>Product Description:</b>	45-mils thick (nominally), self-adhering, multi-layer, white polymer film with a raised pattern embedded into the rubberized asphalt adhesive, and a release liner. Roll size: 36” wide x various lengths
<b>Product Material / Standards:</b>	Material Type: Styrene Butadiene Styrene (SBS) Material shall comply with ASTM D 1970 per Florida Building Code FBC 5th Edition (2014), Chapter 15.
<b>Substrate(s):</b>	<b>Plywood Deck</b> (Design of support is outside the scope of this evaluation)
<b>Installation:</b>	<b>General Installation Instructions:</b> <ul style="list-style-type: none"><li>• Product to be applied directly to a clean dry surface.</li><li>• Dust, dirt, oil, grease, moisture, debris and other loose materials or contaminants must be removed prior to application.</li><li>• Check that all nails in deck are not protruding and re-fasten any loose decking panels.</li><li>• Prime Substrate with asphalt base primer.</li><li>• Cut the membrane to appropriate length.</li><li>• Peel back the release sheet, align the membrane and press into place onto roof deck.</li><li>• Apply with selvedge on upward slope.</li><li>• Overlap end laps a minimum of 6”. Side laps must be a minimum of 3”.</li><li>• Store product in the carton in a dry place until ready to use. Keep product out of direct sunlight. Do not expose to direct sunlight for more than 60 days.</li><li>• Protect membrane from damage during construction.</li><li>• Apply membrane only in fair weather when the air, surface and membrane are at a minimum temperature of: 50° F</li></ul>

Installation shall comply with this report, applicable code sections of FBC 5th Edition (2014) (subject to the Limitations and Conditions of Use listed in this Evaluation Report) and manufacturer’s installation instructions as a supplemental guide for attachment.

- Performance Standards:** The product described herein has demonstrated compliance with:
- **ASTM D 1970-09** – *Specification Self-adhering Polymer Modified Bituminous Sheet Materials Used as Steep Roof Underlayment for Ice Dam Protection*
- Standards Equivalency:** The ASTM D 1970-01 standard version used to test the product meets the prescribed standards in ASTM D 1970-09 standard version adopted by the Florida Building Code 5th Edition (2014) for use as evaluated in this report.
- Code Compliance:** The products described herein have demonstrated compliance with ASTM D 1970-09 of Florida Building Code 2010.
- Evaluation Report Scope:** This product has been evaluated in compliance with the building envelope requirements of the Florida Building Code, as related to the scope section to Florida Product Approval Rule 61G20-3.001.
- Product Limitations and Conditions of Use:**
- Deck shall be in compliance with applicable building code.
  - Minimum slope shall be 3:12 or greater.
  - Installation is limited to use with approved roof coverings that are mechanically fastened through the underlayment and is attached to the sheathing or rafters.
  - Not to be applied over EPDM rubber or urethane or urethane composite insulations.
- General Limitations and Conditions of Use:**
- Scope of “Limitations and Conditions of Use” for this evaluation:  
This evaluation report for “Optional Statewide Approval” contains technical documentation, specifications and installation method(s) which include “Limitations and Conditions of Use” throughout the report in accordance with Rule 61G20-3.005. Per Rule 61G20-3.004, the Florida Building Commission is the authority to approve products under “Optional Statewide Approval”.
  - Option for application outside “Limitations and Conditions of Use”  
Rule 61G20-3.005(1)(e) allows engineering analysis for “project specific approval by the local authorities having jurisdiction in accordance with the alternate methods and materials authorized in the Code”. Any modification of the product as evaluated in this report and approved by the Florida Building Commission is outside the scope of this evaluation and will be the responsibility of others.
  - Fire Classification is outside the scope of Rule 61G20-3, and is therefore not included in this evaluation.
  - This evaluation report does not evaluate the use of this product for use in the High Velocity Hurricane Zone code section. (Dade & Broward Counties)
- Quality Assurance:** The manufacturer has demonstrated compliance of roof panel products in accordance with the Florida Building Code and Rule 61G20-3.0005 (3) for manufacturing under a quality assurance program audited by an approved quality assurance entity through Keystone Certifications, Inc.

**Referenced Data:**

1. ASTM D 1970-01 Test  
By PRI Construction Materials Technologies, Inc.  
(FBC Organization ID# TST 1556)  
Report No. MFM-036-02-01, Date: 8/21/11
2. Equivalency of Test Standard Certification  
By James L. Buckner, P.E. @ CBUGK Engineering  
(FBC Organization # ANE 1916)
3. Quality Assurance  
Keystone Certifications, Inc. (FBC Organization ID# QUA 1824)  
MFM Building Products Corp. Licensee #335
4. Certification of Independence  
By James L. Buckner, P.E. @ CBUGK Engineering  
(FBC Organization # ANE 1916)

**MFM Building Products Corp.  
Product Illustrations**



**“Wind & Water Seal+™”**