

398 E DANIA BEACH BLVD. SUITE 338, DANIA BEACH, FL 33004

Product Evaluation Report

of

Croft, LLC Series 30 Single Hung Window (Non-HVHZ) (Non-Impact)

for

Florida Product Approval

FL# FL28797

Report No. 7708

Current Florida Building Code

Method: Category: Sub – Category: 1 – A (Certificate) Windows Single Hung

Product: Materials: Product Dimensions: Series 30 Single Hung Window PVC See Installation Instructions, CRF019


Prepared for:

Croft, LLC P.O. Box 826 McComb, MS. 39649

Prepared by:

Hermes F. Norero, P.E. Florida Professional Engineer # 73778 Date: 9/3/2021

Contents: Evaluation Report Pages 1 – 3



Hermes F. Norero, P.E. Florida P.E. No. 73778



FL#:FL28797Date:9/3/2021Report No:7708

398 E DANIA BEACH BLVD. SUITE 338, DANIA BEACH, FL 33004

Manufacturer:		Croft, LLC	
Product Category:		Windows	
Product Sub-Category:		Single Hung	
Compliance Method:		State Product Approval Method (1)(a)	
Product Name:		Series 30 Single Hung Window (Non-HVHZ) (Non-Impact)	
Scope:	This is a Product Evaluation Report issued by Hermes F. Norero, P.E. (FL # 73778) Croft, LLC based on <u>Method 1a</u> of the State of Florida Product Approval, Department of Business and Professional Regulation - Florida Building Commission.		
	Hermes F. Norero, P.E. does not have nor will acquire financial interest in the company manufacturing or distributing the product or in any other entity involved in the approval process of the product named herein.		
	This product has been evaluated for use in locations adhering to the current Florida Building Code.		
	See Installation Instructions CRF019 , signed and sealed by Hermes F. Norero, P.E. (FL # 73778) for specific use parameters.		
Limits of Use:	4 T L:	and a band a state of the state	
	•	product has been evaluated and is in compliance with the current Florida ng Code, <u>excluding</u> the "High Velocity Hurricane Zone" (HVHZ).	
	2. Produ	act anchors shall be as listed and spaced as shown on details. Anchor adment into substrate material shall be beyond wall dressing or stucco.	
	3. When	n used in areas requiring wind borne debris protection this product complies Chapter 16 of the current Florida Building Code and <u>does require</u> an impact	

- with Chapter 16 of the current Florida Building Code and <u>does require</u> an impact resistant covering.
 4. Site conditions that deviate from the details of installation instructions CRF019
- require further engineering analysis by a licensed engineer or registered architect.
- 5. See Installation Instructions **CRF019** for size and design pressure limitations.

Page 2 of 3

BUILDINGDROPS.COM

954.399.8478

CONTACT@BUILDINGDROPS.COM

954.744.4738



398 E DANIA BEACH BLVD. SUITE 338, DANIA BEACH, FL 33004

Certification Agency:	in acco approv	The manufacturer has demonstrated compliance of manufacture of production in accordance with the Florida Building Code for manufacturing under an approved certification agency through Fenestration and Glazing Industry Alliance (formerly AAMA) (FBC Organization # CER1498).		
Performance Standards:	The product described herein has been evaluated per:AAMA/WDMA/CSA 101/I.S.2/A440-11			
Referenced Data:				
	1.	Product Testing performed by (FBC Organization # TST1910)	Architectural Testing, Inc.	
		Report #: B9751.01-801-47,	Report Date: 06/07/2012	
	2.	 Certification Agency Fenestration and Glazing Industry Alliance (formerly AAMA) (FBC Organization #: CER1498) 		

Installation:

Refer to Installation Instructions (CRF019) for anchor spacing and more details of the installation requirements.

Design Pressure:

Refer to Installation Instructions (CRF019) for design pressures based on size, configuration, and glass types.

