



LISTING INFORMATION OF
Air Louvers 1500A-HR Louver
SPEC ID: 32786

Air Louvers, Inc.
6285 Randolph St.
Commerce, CA 90040
United States

This report is for the exclusive use of Intertek's Client and is provided pursuant to the agreement between Intertek and its Client. Intertek's responsibility and liability are limited to the terms and conditions of the agreement. Intertek assumes no liability to any party, other than to the Client in accordance with the agreement, for any loss, expense or damage occasioned by the use of this report. Only the Client is authorized to permit copying or distribution of this report and then only in its entirety. Any use of the Intertek name or one of its marks for the sale or advertisement of the tested material, product or service must first be approved in writing by Intertek. The observations and test results in this report are relevant only to the sample tested. This report by itself does not imply that the material, product, or service is or has ever been under an Intertek certification program.

LISTING INFORMATION

WINDSTORM RESISTANT PRODUCTS & COMPONENTS

Model 1500A-HR air louver system with Security Grill on interior and exterior sides.

* Louver must be installed in a listed windstorm resistant door. Door Thickness: 1-3/4".

Model#	Configuration	Door Stiffness	Max. Overall Size		Ratings (D.L.)	
			Width (in)	Height (in)	Structural (PSF)	Impact (ft-lb)
1500A-HR	In & Out-Swing	Class I	24	64	+/-60	350

D. L. = Maximum design load. NR = Not Rated

This specification confirms the Air Louver 1500A-HR IS manufactured under a program of follow-up inspections conducted by Intertek. The inspections verify the products are manufactured in a manner consistent with the submitted quality system documentation.

Product	Product Approval No.
Air Louver 1500A-HR	FL # 13341

Attribute	Value
Criteria	ASTM E330 (2002)
Criteria	ASTM E1996 (2003)
Criteria	ANSI A250.13 (2003)
Criteria	TAS 203
Criteria	TAS 201
Criteria	TAS 202
Criteria	ASTM E1886 (2005)
CSI Code	08 11 00 Metal Doors and Frames
DP Rating (psf)	60
Hurricane Impact Load Rating ft-lb	350
Intertek Services	Certification
Intertek Services	Quality Assurance
Listed or Inspected	LISTED
Listing Section	WINDSTORM - SWINGING DOOR COMPONENTS
Report Number	3116736-004, 101254435MID-003
Spec ID	32786
Verification Testing	No