



ZHDL.R8931 Door Frames

[Page Bottom](#)

Door Frames

[See General Information for Door Frames](#)

FLEMING-BARON DOOR PRODUCTS

R8931

101 ASHBRIDGE CIR
WOODBRIIDGE, ON L4L 3R5 CANADA

Model	Configuration	Wall Type	Max Opening Size	Design Load (psf)	Impact (ft-lbs)
3-Sided Frames	Single - In-Swing	Drywall and Wood or Metal Stud (new or existing), Masonry (new or existing) and Structural Steel	3-0, 7-0	+/- 70	350
	Single - Out-Swing	Drywall and Wood or Metal Stud (new or existing), Masonry (new or existing) and Structural Steel	4-0, 8-0	+/- 70	350
	Pairs without mullion - In-Swing	Drywall and Wood or Metal Stud (new or existing), Masonry (new or existing) and Structural Steel	6-0, 7-0	+/- 70	350
	Pairs with or without removable hollow metal mullion - Out-Swing	Drywall and Wood or Metal Stud (new or existing), Masonry (new or existing) and Structural Steel	8-0, 7-0	+/- 65	350
	Pairs with or without hardware mullion - Out-Swing	Drywall and Wood or Metal Stud (new or existing), Masonry (new or existing) and Structural Steel	8-0, 8-0	+/- 70	350
Transom Frames*	Single - In-Swing or Out-Swing	Drywall and Wood or Metal Stud (new or existing), Masonry (new or existing) and Structural Steel	3-0, 7-0 (Door)10-2 (Max Door + Transom Ht)	+/- 60	350
	Single - Out-Swing	Drywall and Wood or Metal Stud (new or existing), Masonry (new or existing) and Structural Steel	3-0, 8-0 (Door)10-0 (Max Door + Transom Ht)	+/- 60	350
	Pair -without mullion Out-Swing	Drywall and Wood or Metal Stud (new or existing), Masonry (new or existing) and Structural Steel	6-0, 7-0 (Doors)10-2 (Max Door + Transom Ht)	+/- 60	350
	Pairs with or without hardware mullion - Out-Swing	Drywall and Wood or Metal Stud (new or existing), Masonry (new or existing) and Structural Steel	6-0, 8-0 (Doors)10-0 (Max Door + Transom Ht)	+/- 60	350
Sidelight Frames*	Single - In-Swing or Out-Swing	Drywall and Wood or Metal Stud (new or existing), Masonry (new or existing) and Structural Steel	3-0, 7-0 (Door)4-6 (Max O/A Unit Width)	+/- 60	350
	Single - Out-Swing	Drywall and Wood or Metal Stud (new or existing), Masonry (new or existing) and Structural Steel	3-0, 8-0 (Door)12-8, 10-0 (Max O/A Unit Size)	+/- 60	350
	Pairs without mullion - Out-Swing	Drywall and Wood or Metal Stud (new or existing), Masonry (new or existing) and Structural Steel	6-0, 7-0 (Doors) 12-8, 10-0 (Max O/A Unit Size)	+/- 60	350
	Pairs with or without hardware mullion - Out-Swing	Drywall and Wood or Metal Stud (new or existing), Masonry (new or existing) and Structural Steel	6-0, 8-0 (Doors)12-8, 10-0 (Max O/A Unit Size)	+/- 60	350
Hollow Metal Window	Fixed	Drywall and Wood or Metal Stud (new or existing), Masonry (new or existing) and Structural Steel	12-8, 10-0 (Max O/A Unit Size)6-0, 8-10 (Max	+/- 60	350

Frames*		or existing) and Structural Steel	Individual Light Opening)	
---------	--	-----------------------------------	---------------------------	--

* Frame to be glazed with a windstorm resistant glazing material with a design load and impact rating the same or greater than the ratings presented for the frame.

Products also tested to TAS 201, TAS 202, TAS 203, PA 201, PA 202, PA 203, ASTM E330, ASTM E1886 and ASTM E1996

Last Updated on 2012-01-05

[Questions?](#)

[Print this page](#)

[Notice of Disclaimer](#)

[Page Top](#)

© 2012 UL LLC

The appearance of a company's name or product in this database does not in itself assure that products so identified have been manufactured under UL's Follow-Up Service. Only those products bearing the UL Mark should be considered to be Listed and covered under UL's Follow-Up Service. Always look for the Mark on the product.

UL permits the reproduction of the material contained in the Online Certification Directory subject to the following conditions: 1. The Guide Information, Designs and/or Listings (files) must be presented in their entirety and in a non-misleading manner, without any manipulation of the data (or drawings). 2. The statement "Reprinted from the Online Certifications Directory with permission from UL" must appear adjacent to the extracted material. In addition, the reprinted material must include a copyright notice in the following format: "© 2012 UL LLC".