



## ZHCK.R25219 Accessories for Windstorm-rated Swinging Doors

[Page Bottom](#)

### Accessories for Windstorm-rated Swinging Doors

[See General Information for Accessories for Windstorm-rated Swinging Doors](#)

**SECURITRON MAGNALOCK CORP**

R25219

10027 S 51ST ST

PHOENIX, AZ 85044-5219 USA

| Model                      | For Use with Component Type | Wall Type                   | Max Door Opening Size (ft-in.) | Max Design Pressure (psf) | Max Impact Energy Resistance (ft-lbs) | Test Method(s)*                                                                |
|----------------------------|-----------------------------|-----------------------------|--------------------------------|---------------------------|---------------------------------------|--------------------------------------------------------------------------------|
| <b>Power transfer unit</b> |                             |                             |                                |                           |                                       |                                                                                |
| CEPT                       | Latching hardware           | Drywall, wood stud, Masonry | 4 ft - 0 in. by 8 ft - 0 in.   | +150, -150                | 350                                   | SDI-BHMA A250.13, ASTM E330, ASTM E1886, ASTM E1996, TAS 201, TAS 202, TAS 203 |
| ICPT, ICPT-R               | Latching hardware           | Drywall, wood stud, Masonry | 4 ft - 0 in. by 8 ft - 0 in.   | +/-150                    | 350                                   | SDI-BHMA A250.13, ASTM E330, ASTM E1886, ASTM E1996, TAS 201, TAS 202, TAS 203 |
| SEPT                       | Latching hardware           | Drywall, wood stud, Masonry | 4 ft - 0 in. by 8 ft - 0 in.   | +/-150                    | 350                                   | SDI-BHMA A250.13, ASTM E330, ASTM E1886, ASTM E1996, TAS 201, TAS 202, TAS 203 |
| EPT                        | Latching hardware           | Drywall, wood stud          | 3 ft - 0 in. by 7 ft - 0 in.   | +/-60                     | 350                                   | SDI-BHMA A250.13, ASTM E330, ASTM E1886, ASTM E1996, TAS 201, TAS 202, TAS 203 |
| EPTL                       | Latching hardware           | Drywall, wood stud          | 3 ft - 0 in. by 7 ft - 0 in.   | +/-60                     | 350                                   | SDI-BHMA A250.13, ASTM E330, ASTM E1886, ASTM E1996, TAS 201, TAS 202, TAS 203 |

(+) Positive load applied to outdoor (exterior) side of assembly; (-) negative load applied to indoor (interior) side of assembly

\* See [ZHCH](#) for ratings and construction details

\*\* Product tested only for out-swing installation

\*\*\* Product tested for out-swing and in-swing installation

[Last Updated](#) on 2015-06-12

[Questions?](#)
[Print this page](#)
[Terms of Use](#)
[Page Top](#)

© 2015 UL LLC

The appearance of a company's name or product in this database does not in itself assure that products so identified have been manufactured under UL's Follow-Up Service. Only those products bearing the UL Mark should be considered to be Certified and covered under UL's Follow-Up Service. Always look for the Mark on the product.

UL permits the reproduction of the material contained in the Online Certification Directory subject to the following conditions: 1. The Guide Information, Assemblies, Constructions, Designs, Systems, and/or Certifications (files) must be presented in their entirety and in a non-misleading manner, without any manipulation of the data (or drawings). 2. The statement "Reprinted from the Online Certifications Directory with permission from UL" must appear adjacent to the extracted material. In addition, the reprinted material must include a copyright notice in the following format: "© 2015 UL LLC".