

Latching Hardware

See General Information for Latching Hardware

ROCKWOOD MFG CO
300 MAIN ST
PO BOX 79
ROCKWOOD, PA 15557-0079 USA

R27275

Model	Type	Config- uration	Max Size (ft-in.)	Stiffness Class (min)	Max Design Pressure (psf)	Max Impact Energy Resistance (ft-lbs)	Latch Throw Min (in.)	Max Latch Design Pressure (lbf)	Test Method(s)*
556WS Flush Bolt	—	Inswing/ Outswing Pair	8 ft - 0 in. by 8 ft - 0 in.	I	+/-70	350	—	560	SDI/BHMA ANSI A250.13, ASTM E330, ASTM E1886, ASTM E1996, TAS 201, TAS 202, TAS 203

* See [ZHCH](#) for ratings and construction details.

[Last Updated](#) on 2020-10-12

The appearance of a company's name or product in this database does not in itself assure that products so identified have been manufactured under UL Solutions' Follow - Up Service. Only those products bearing the UL Mark should be considered to be Certified and covered under UL Solutions' Follow - Up Service. Always look for the Mark on the product.

UL Solutions permits the reproduction of the material contained in Product iQ subject to the following conditions: 1. The Guide Information, Assemblies, Constructions, Designs, Systems, and/or Certifications (files) must be presented in their entirety and in a non-misleading manner, without any manipulation of the data (or drawings). 2. The statement "Reprinted from Product iQ with permission from UL Solutions" must appear adjacent to the extracted material. In addition, the reprinted material must include a copyright notice in the following format: "©2023 UL LLC."