



LISTING INFORMATION OF

Habersham Metal Windstorm Pair Door and Frame Assembly

SPEC ID: 23696

Habersham Metal Products Company, Inc.
264 Stapleton Road
Cornelia, GA 30531
United States

This report is for the exclusive use of Intertek's Client and is provided pursuant to the agreement between Intertek and its Client. Intertek's responsibility and liability are limited to the terms and conditions of the agreement. Intertek assumes no liability to any party, other than to the Client in accordance with the agreement, for any loss, expense or damage occasioned by the use of this report. Only the Client is authorized to permit copying or distribution of this report and then only in its entirety. Any use of the Intertek name or one of its marks for the sale or advertisement of the tested material, product or service must first be approved in writing by Intertek. The observations and test results in this report are relevant only to the sample tested. This report by itself does not imply that the material, product, or service is or has ever been under an Intertek certification program.

LISTING INFORMATION

PRODUCT DESCRIPTION

Windstorm resistant steel stiffened hollow metal door and steel frame out-swinging pair door assembly with nominal maximum size 6'-0" wide x 7'-0" tall.

WINDSTORM RATING

Test Standard	Maximum Pair Size	Rating	Latching Hardware
ASTM E330-14 ASTM E1886-13a ASTM E1886-19 ASTM E1996-17 ASTM E1996-20 TAS 201 TAS 203 TAS 202	Frame: 6' 4" wide x 7'- 4" tall Frame Depth 7.5 in. Doors 3'0" x 7' 0" 1-3/4" thick doors	Design Pressure +104 PSF / -104PSF Large Missile Impact	Sargent HC8700/FM8700 2-point (top and bottom) Surface Vertical Rod Exit Device on each door.

AIR INFILTRATION RATING*

Test Standard	Test Type	Air Infiltration Rating
ASTM E283-04(R2012)	Air Infiltration	0.16 cfm / Sq. Ft.

*When installed assemblies include the required perimeter and meeting edge sealing gaskets.

WATER RESISTANCE RATING*

Test Standard	Test Type	Water
ASTM E331-00(R2009)	Water Resistance	10.5 PSF - pass

*When installed assemblies include the required perimeter and meeting edge sealing gaskets.

FLORIDA PRODUCT APPROVAL

Product	Florida Product Approval No.
Habersham Metal Windstorm Pair Door and Frame Assembly	FL15843

Attribute	Value
Criteria	ANSI A250.13 (2003)
Criteria	TAS 203
Criteria	TAS 201
Criteria	TAS 202
Criteria	ASTM E331 (2009)

Criteria	ASTM E330 (2014)
Criteria	ASTM E331 (2016)
Criteria	ASTM E283 (2004) R2012
Criteria	ASTM E1996 (2017)
Criteria	ASTM E1996 (2020)
Criteria	ASTM E1886 (2019)
Criteria	ASTM E1886 (2013a)
CSI Code	08 11 00 Metal Doors and Frames
CSI Code	08 11 13 Hollow Metal Doors and Frames
DP Rating (psf)	104
Intertek Services	Certification
Listed or Inspected	LISTED
Listing Section	WINDSTORM - SWING DOOR ASSEMBLIES
Report Number	3076273a, G104598306
Spec ID	23696
Swing	Out swing
Test Original Issue Date	2/2/2006
Verification Testing	No