

Hallmark® Certificate of Conformance and License (CCL)



Hurd Windows & Doors
575 S. Whelen Ave.
Medford, WI 54451

Mfr ID: 436

For more information visit www.amscert.com

Website:

TEL: (715) 748-1716

Product No.	Product Name	Standard	Rating	Wide	High	Test Report #	CertDate	ExpDate
436-H-105.38	Energy Saver Clad Casement 28x84	CSA A440 S1-09	Class CW-PG35; Size Tested 718 x 2140 Type-C; DP +35/-35 psf; Water Test Press 360Pa (7.52psf); Can. Air Infil/Exfil. Level=A3	718mm	2140mm	TCT004982P-0200 Rev. B	9/30/2014	8/21/2018
436-H-105.39	Energy Saver Clad Casement Mulled 36x72	101/I.S.2/A440-11	Class LC-PG50; Size Tested 921mm x 1835mm Type-C; DP +50/-50 psf; Water Test Press 360Pa (7.52psf); Can. Air Infil/Exfil. Level=A3	921mm	1835mm	E0618.01-602-44	9/19/2014	8/21/2018
436-H-105.40	Energy Saver Clad Arch Top Casement 36x72	101/I.S.2/A440-11	Class CW-PG50; Size Tested 919mm x 1834mm(36x72in) Type-C; DP +50/-65 psf; Water Test Press 360Pa (7.52psf); Can. Air Infil/Exfil. Level=A3	919mm	1834mm	ESP016461P-1553	10/31/2014	4/28/2018
436-H-105.41	Energy Saver Clad 2-Wide Casement Operator (57"x96")- -Individual Unit Sizes of 28.25"x96"	101/I.S.2/A440-11	Class LC-PG25; Size Tested 718mm Trib width/2445mm span(28 trib width/96in span) * Type-MA; DP +25/-25 psf; Water Test Press 360Pa (7.52psf); Can. Air Infil/Exfil. Level=A3	718mm (Trib width)	2445mm (span)	ESP017804P-1612	2/11/2015	9/15/2024
436-H-105.42	Energy Saver Clad Springline Casement Operator (36"x72")	101/I.S.2/A440-11	Class LC-PG45; Size Tested 919mm x 1834mm (36x72in) Type-C; DP +45/-45 psf; Water Test Press 360Pa (7.52psf); Can. Air Infil/Exfil. Level=A3	919mm	1834mm	ESP018511P-1656	2/11/2015	12/15/2024
436-H-109.13	ES Clad Csmt Pict 67x79	101/I.S.2/A440-08	Class CW-PG50; Size Tested 1834x2138mm (72x84in)-FW; Negative Design Pressure = 2880Pa (60psf)	1834mm	2138mm	TCT007166P-1097	9/2/2011	7/21/2015
436-H-109.14	ES Clad Csmt Pict 67x79	101/I.S.2/A440-05	FW-C50; Negative Design Pressure = 2880Pa (60psf)	1834mm	2138mm	TCT007166P-1097	9/2/2011	7/21/2015
436-H-523.23	Clad Energy Saver Direct Set Fixed (O)	101/I.S.2/A440-05	FW-C50	2489mm	2135mm	TCT006336P-1046	8/10/2011	4/28/2015
436-H-523.24	Clad Energy Saver Direct Set 98x84	101/I.S.2/A440-08	Class CW-PG50;Size tested 2483x2130mm(98x84in)-FW; Negative Design Pressure = 2640pa (55psf)	2483mm	2130mm	TCT008274P-1149RevA	1/16/2012	10/13/2015
436-H-523.25	Clad Energy Saver Direct Set 98x84	101/I.S.2/A440-05	FW-C50; Negative Design Pressure = 2640pa (55psf)	2483mm	2130mm	TCT008274P-1149RevA	1/16/2012	10/13/2015