

Document Title:

Structural Performance Certification Authorization Report

Doc No:	FRM B1-02						
Rev No:	7	Page:	1	Of:	1		

Required By:

PRO B1-03

CAR & Product ID Number: 622 - 107.0

Issue Date: 12/29/2016
Revision Date: 1/12/2017
Expiration Date: 6/6/2020

Company Code: 622

This Certification Authorization Report (CAR) is issued by Keystone Certifications, Inc. (KCI) after full validation review, and is based on a standardized evaluation of the product conducted by an independent accredited laboratory in accordance with the specified referenced standard. Actual fenestration product performance may vary based on many factors, including installation, condition of the wall/roof substrate and the age of the product and installation components.

This report indicates the product is eligible for the application of Keystone Certification Program certification labels. Licensee stipulates in affixing certification labels to products, that those products are representative of the specimen evaluated and documented for certification authorization. Only products bearing such a certification label shall be considered certified. The information in this report can be verified at www.keystonecerts.com.

Licensee Information:	Product Information:				
Eastern Architectural Systems	Model: 176 HVHZ Vertical/Horizontal Mullion				
16341 Domestic Avenue	Operator Type: Mull				
Fort Myers FL 33912	Config: No Reinforcement				
	Max Width: See Table				
	Max Height: See Table				

Referenced Standard:	Product Rating:				
AAMA 450-10 & PA/TAS 201/202/203	See Appendix 1 Load Tables and Impact Ratings				

Qualifying Test Information:				
Test Report No:	NCTL-210-4032-1			
Test Report Expiration:	6/6/2020			

Authorized Signature:

Keystone Certifications, Inc.

564 Old York Road, Suite 5 Etters, Pennsylvania 17319 Phone: 717-932-8500

Fax: 717-932-8501



Appendix 1

CAR No: 622-107.0 Expiration Date: 06/06/2020

Eastern Architectural Systems

10030 Bavaria Road Fort Myers, FL 33913

Load Tables for the:

176 HVHZ Vertical/Horizontal Mullion

DESIGN PRESSURE RATING (psf)

(Design pressures are positive and negative)

Mullion	Tributary width (in)								
span (in)	24.00	30.00	36.00	42.00	48.00	54.00	60.00	66.00	72.00
36.00	150.0	150.0	150.0	150.0	150.0	150.0	150.0	150.0	150.0
42.00	150.0	150.0	150.0	150.0	150.0	150.0	150.0	150.0	150.0
48.00	150.0	150.0	150.0	150.0	150.0	150.0	150.0	150.0	150.0
54.00	150.0	150.0	150.0	150.0	150.0	150.0	150.0	150.0	150.0
60.00	150.0	150.0	150.0	137.7	128.1	122.7	120.9	120.9	120.9
66.00	150.0	143.1	123.3	110.0	101.1	95.3	92.0	90.9	90.9
72.00	145.4	118.9	101.8	90.2	82.2	76.6	72.9	70.7	70.0
78.00	123.2	100.4	85.6	75.4	68.2	63.1	59.4	57.0	55.5
84.00	105.7	85.9	73.0	64.1	57.7	53.0	49.6	47.1	45.4
90.00	91.8	74.4	63.1	55.2	49.5	45.2	42.1	39.7	38.0
96.00	80.4	65.1	55.1	48.1	42.9	39.1	36.2	34.0	32.3
102.00	71.1	57.5	48.5	42.2	37.7	34.2	31.5	29.5	27.9
108.00	63.3	51.1	43.1	37.4	33.3	30.2	27.7	25.8	24.3
114.00	54.2	43.8	36.9	32.1	28.6	25.9	23.9	22.2	21.0
120.00	46.4	37.4	31.5	27.4	24.3	22.0	20.2	18.8	17.7

Impact Ratings

PA/TAS 201/203 – Large and Small Missile Impact Rated Up to Wind Zone 4 and HVHZ