

NOTICE OF PRODUCT CERTIFICATION



Company: Masonite International Corporation
1955 Powis Road
West Chicago, IL 60185

Certification No.: NI013717.11-R3
Certification Date: 05/12/2017
Expiration Date: 05/31/2027
Revision Date: 12/06/2023

Product: Fiberglass Glazed Inswing or Outswing Door w/ and w/o Non-Impact Rated Sidelites w/Endura Trilennium or Panolock Multipoint Hardware (w/Wood Frame or Worldwide Composite Frame⁴ unless noted)

Specification: TAS 202-94/ASTM E330-02/14/M-14

Glazing: Insulating Glass (Tempered)

This certification represents product conformity to the applicable specification and that certification criteria has been satisfied. A NAMI approved certification label must be applied to the product to claim certification status. To affirm the certification status, please visit www.namincertification.com. NAMI is accredited to the ISO/IEC 17065 by the ANSI National Accreditation Board (ANAB) and the Standards Council of Canada (SCC).

Configuration	Inswing or Outswing	Glazed or Opaque	Maximum Size	Structural Design Pressure	Water Test Pressure	Missile Impact Rated	Test Report Number Drawing Number & Comments
X Single	I/S	Glazed	3'0" x 6'8"	+40/-40	0.0 psf	No	ATLNC 0829.01-16/ATLNC 1013.01-16/W-1814/W-2106/W-2107 Maximum Panel Size: 3'0" x 6'8" Anchor Details-DWG-MA-FL0199-17
X Single	O/S	Glazed	3'0" x 6'8"	+40/-40	3.75 psf ¹ 6.0 psf ² 8.25 psf ³	No	ATLNC 0829.01-16/ATLNC 1013.01-16/W-1813/W-1814 /W-1843/W-2106/W-2107 Maximum Panel Size: 3'0" x 6'8" Anchor Details-DWG-MA-FL0199-17
XX Double	I/S	Glazed	6'0" x 6'8"	+40/-40	0 psf	No	ATLNC 0829.01-16/ATLNC 1013.01-16/W-1814/W-2106/W-2107 Maximum Panel Size: 3'0" x 6'8" Anchor Details-DWG-MA-FL0199-17
XX Double	O/S	Glazed	6'0" x 6'8"	+40/-40	3.75 psf ¹ 6.0 psf ² 8.25 psf ³	No	ATLNC 0829.01-16/ATLNC 1013.01-16/W-1813/W-1814 /W-1843/W-2106/W-2107 Maximum Panel Size: 3'0" x 6'8" Anchor Details-DWG-MA-FL0199-17
XO/OX Single w/Sidelite	I/S	Glazed	6'0" x 6'8"	+40/-40	0 psf	Door-No Sidelite-No	ATLNC 0829.01-16/ATLNC 1013.01-16/W-1814/W-2106/W-2107 Maximum Panel Size: 3'0" x 6'8" Anchor Details-DWG-MA-FL0199-17
XO/OX Single w/Sidelite	O/S	Glazed	6'0" x 6'8"	+40/-40	3.75 psf ¹ 6.0 psf ² 8.25 psf ³	Door-No Sidelite-No	ATLNC 0829.01-16/ATLNC 1013.01-16/W-1813/W-1814 /W-1843/W-2106/W-2107 Maximum Panel Size: 3'0" x 6'8" Anchor Details-DWG-MA-FL0199-17
OXO Single w/Sidelites	I/S	Glazed	9'0" x 6'8"	+40/-40	0 psf	Door-No Sidelites-No	ATLNC 0829.01-16/ATLNC 1013.01-16/W-1814/W-2106/W-2107 Maximum Panel Size: 3'0" x 6'8" Anchor Details-DWG-MA-FL0199-17
OXO Single w/Sidelites	O/S	Glazed	9'0" x 6'8"	+40/-40	3.75 psf ¹ 6.0 psf ² 8.25 psf ³	Door-No Sidelites-No	ATLNC 0829.01-16/ATLNC 1013.01-16/W-1813/W-1814 /W-1843/W-2106/W-2107 Maximum Panel Size: 3'0" x 6'8" Anchor Details-DWG-MA-FL0199-17
OXXO Double w/Sidelites	I/S	Glazed	12'4" x 6'8"	+40/-40	0 psf	Door-No Sidelites-No	ATLNC 0829.01-16/ATLNC 1013.01-16/W-1814/W-2106/W-2107 Maximum Panel Size: 3'0" x 6'8" Anchor Details-DWG-MA-FL0199-17
OXXO Double w/Sidelites	O/S	Glazed	12'4" x 6'8"	+40/-40	3.75 psf ¹ 6.0 psf ² 8.25 psf ³	Door-No Sidelite-No	ATLNC 0829.01-16/ATLNC 1013.01-16/W-1813/W-1814 /W-1843/W-2106/W-2107 Maximum Panel Size: 3'0" x 6'8" Anchor Details-DWG-MA-FL0199-17

1 -Denotes Bumper Outswing Threshold 2 -Denotes Z-Series Outswing Threshold 3 -Hi-Dam Outswing Threshold 4 -W-1815 5 -Worldwide Pro T4 Threshold

National Accreditation & Management Institute, Inc./4794 George Washington Memorial Highway/Hayes, VA 23072

Tel: (804) 684-5124/nami@namiinc.com

NAMI AUTHORIZED SIGNATURE: _____