

Latching Hardware

COMPANY

HANCHETT ENTRY SYSTEMS INC

10027 S 51ST ST STE 102
PHOENIX, AZ 85044 United States

R27043

View model for additional information

Model(s): 1006, 1500 and 1500E, 1600 and 1600E, 9600, ES100-15, ES100-16

Model(s): 9700 (with ASSA ABLOY Accentra7150(E)WS or Corbin Russwin ED5200S(A)xM170, pairs to be supplied with accompanying mullion)

Electric Strike, Model(s): 5000, 5300, 5900, 8000, 8300

Last Updated on 2025-05-15

The appearance of a company's name or product in this database does not in itself assure that products so identified have been manufactured under UL Solutions' Follow - Up Service. Only those products bearing the UL Mark should be considered to be Certified and covered under UL Solutions' Follow - Up Service. Always look for the Mark on the product.

UL Solutions permits the reproduction of the material contained in Product iQ subject to the following conditions: 1. The Guide Information, Assemblies, Constructions, Designs, Systems, and/or Certifications (files) must be presented in their entirety and in a non-misleading manner, without any manipulation of the data (or drawings). 2. The statement "Reprinted from Product iQ with permission from UL Solutions" must appear adjacent to the extracted material. In addition, the reprinted material must include a copyright notice in the following format: "©2025 UL LLC."

Cookies on UL Solutions

We use cookies to personalize content and ads, to provide social media features and to analyze our traffic. We also share information about your use of our site with our social media, advertising and analytics partners. [Learn more](#)

Cookies Settings

Reject All

Accept All Cookies

Model 1500 and 1500E

File Number: R27043

COMPANY

HANCHETT ENTRY SYSTEMS INC

10027 S 51ST ST STE 102

PHOENIX, AZ 85044 United States

MODEL INFO

1500 and 1500E

GENERAL								
Configuration	Max. Size	Stiffness Class (min)	Positive Design Load (psf)	Negative Design Load (psf)	Impact (ft-lb)	Min. Latch Throw (in)	Min. Latch Strength (lbf)	Test Methods
Single Out-Swing	4-0 x 8-0	I	60	-60	350	3/4	960	SDI A250.13, ASTM E330, ASTM E1886, ASTM E1996, TAS 201, TAS 202, TAS 203

The appearance of a company's name or product in this database does not in itself assure that products so identified have been manufactured under UL Solutions' Follow - Up Service. Only those products bearing the UL Mark should be considered to be Certified and covered under UL Solutions' Follow - Up Service. Always look for the Mark on the product.

UL Solutions permits the reproduction of the material contained in Product iQ subject to the following conditions: 1. The Guide Information, Assemblies, Constructions, Designs, Systems, and/or Certifications (files) must be presented in their entirety and in a non-misleading manner, without any manipulation of the data (or drawings). 2. The statement "Reprinted from Product iQ with permission from UL Solutions" must appear adjacent to the extracted material. In addition, the reprinted material must include a copyright notice in the following format: "©2025 UL LLC."

Cookies on UL Solutions

We use cookies to personalize content and ads, to provide social media features and to analyze our traffic. We also share information about your use of our site with our social media, advertising and analytics partners. [Learn more](#)

Cookies Settings

Reject All

Accept All Cookies

Model 1600 and 1600E

File Number: R27043

COMPANY

HANCHETT ENTRY SYSTEMS INC

10027 S 51ST ST STE 102

PHOENIX, AZ 85044 United States

MODEL INFO

1600 and 1600E

GENERAL								
Configuration	Max. Size	Stiffness Class (min)	Positive Design Load (psf)	Negative Design Load (psf)	Impact (ft·lb)	Min. Latch Throw (in)	Min. Latch Strength (lbf)	Test Methods
Single Out-Swing	4-0 x 8-0	I	70	-70	350	3/4	1120	SDI A250.13, ASTM E330, ASTM E1886, ASTM E1996, TAS 201, TAS 202, TAS 203



The appearance of a company's name or product in this database does not in itself assure that products so identified have been manufactured under UL Solutions' Follow - Up Service. Only those products bearing the UL Mark should be considered to be Certified and covered under UL Solutions' Follow - Up Service. Always look for the Mark on the product.

UL Solutions permits the reproduction of the material contained in Product iQ subject to the following conditions: 1. The Guide Information, Assemblies, Constructions, Designs, Systems, and/or Certifications (files) must be presented in their entirety and in a non-misleading manner, without any manipulation of the data (or drawings). 2. The statement "Reprinted from Product iQ with permission from UL Solutions" must appear adjacent to the extracted material. In addition, the reprinted material must include a copyright notice in the following format: "©2025 UL LLC."

Cookies on UL Solutions

We use cookies to personalize content and ads, to provide social media features and to analyze our traffic. We also share information about your use of our site with our social media, advertising and analytics partners. [Learn more](#)

Cookies Settings

Reject All

Accept All Cookies