

NOTICE OF PRODUCT CERTIFICATION



Company: Masonite International Corporation
1955 Powis Road
West Chicago, IL 60185

Certification No.: NI012729.06-R2
Certification Date: 11/06/2018
Expiration Date: 12/31/2026
Revision Date: 12/06/2023

Product: Fiberglass Integral Glazed Inswing or Outswing Door w/ and w/o Non-Impact Rated Sidelites (w/Wood Frame or Worldwide Composite Frame & Trilennium or Panolock Multipoint unless noted)

Specification: TAS 202/ASTM E330

Glazing: IG-3mm Tempered Glass

This certification represents product conformity to the applicable specification and that certification criteria has been satisfied. A NAMI approved certification label must be applied to the product to claim certification status. To affirm the certification status, please visit www.namicertification.com. NAMI is accredited to the ISO/IEC 17065 by the ANSI National Accreditation Board (ANAB) and the Standards Council of Canada (SCC).

Configuration	Inswing or Outswing	Glazed or Opaque	Maximum Size	Structural Design Pressure(psf)	Water Test Pressure	Missile Impact Rated	Test Report Number Drawing Number & Comments
X Single	I/S	Glazed	3'0" x 8'0"	+40/-45	0.0 psf	No	ATLNC0427.01/W-1842/W-1878/W-2107 Maximum Panel Size: 3'0" x 8'0" Anchor Detail-MA-FL0183-1
X Single	O/S	Glazed	3'0" x 8'0"	+45/-45	5.25 psf ¹ 6.00 psf ² 7.05 psf ³	No	ATLNC0427.01/W-1842/W-1878/W-2107 Maximum Panel Size: 3'0" x 8'0" Anchor Detail-MA-FL0183-1
XX Double	I/S	Glazed	6'0" x 8'0"	+40/-45	0.0 psf	No	ATLNC0427.01/W-1842/W-1878/W-2107 Maximum Panel Size: 3'0" x 8'0" Anchor Detail-MA-FL0183-1
XX Double	O/S	Glazed	6'0" x 8'0"	+45/-45	5.25 psf ¹ 6.00 psf ² 7.05 psf ³	No	ATLNC0427.01/W-1842/W-1878/W-2107 Maximum Panel Size: 3'0" x 8'0" Anchor Detail-MA-FL0183-1
XO/OX Single w/Sidelite	I/S	Glazed Door Glazed Sidelite	6'0" x 8'0"	+40/-45	0.0 psf	Door-No Sidelite-No	ATLNC0427.01/W-1842/W-1878/W-2107 Maximum Panel Size: 3'0" x 8'0" Anchor Detail-MA-FL0183-1
XO/OX Single w/Sidelites	O/S	Glazed Door Glazed Sidelite	6'0" x 8'0"	+45/-45	5.25 psf ¹ 6.00 psf ² 7.05 psf ³	Door-No Sidelite-No	ATLNC0427.01/W-1842/W-1878/W-2107 Maximum Panel Size: 3'0" x 8'0" Anchor Detail-MA-FL0183-1
OXO Single w/Sidelites	I/S	Glazed Door Glazed Sidelites	9'0" x 8'0"	+40/-45	0.0 psf	Door-No Sidelites-No	ATLNC0427.01/W-1842/W-1878/W-2107 Maximum Panel Size: 3'0" x 8'0" Anchor Detail-MA-FL0183-1
OXO Single w/Sidelites	O/S	Glazed Door Glazed Sidelites	9'0" x 8'0"	+45/-45	5.25 psf ¹ 6.00 psf ² 7.05 psf ³	Door-No Sidelites-No	ATLNC0427.01/W-1842/W-1878/W-2107 Maximum Panel Size: 3'0" x 8'0" Anchor Detail-MA-FL0183-1
OXXO Double w/Sidelites	I/S	Glazed Doors Glazed Sidelites	12'6" x 8'0"	+40/-45	0.0 psf	Doors-No Sidelites-No	ATLNC0427.01/W-1842/W-1878/W-2107 Maximum Panel Size: 3'0" x 8'0" Anchor Detail-MA-FL0183-1
OXXO Double w/Sidelites	O/S	Glazed Doors Glazed Sidelites	12'6" x 8'0"	+45/-45	5.25 psf ¹ 6.00 psf ² 7.05 psf ³	Doors-No Sidelites-No	ATLNC0427.01/W-1842/W-1878/W-2107 Maximum Panel Size: 3'0" x 8'0" Anchor Detail-MA-FL0183-1

*Requires Surface Bolts ¹Bumper Threshold ²Z-Series Threshold ³Denotes High Dam Threshold Design

National Accreditation & Management Institute, Inc./4794 George Washington Memorial Highway/Hayes, VA 23072

Tel: (804) 684-5124/nami@namiinc.com

NAMI AUTHORIZED SIGNATURE: _____