Model HC-MD-8600 Series Concealed Vertical Rod Devices

File Number: R21744

COMPANY

SARGENT MFG CO
100 SARGENT DR
NEW HAVEN, CT 06511-5918 United States

MODEL INFO

HC-MD-8600 Series Concealed Vertical Rod Devices *May be provided with the following options: 12- (Fire-Rated), AL- (Alarm), 53- (Latchbolt Monitoring), 55- (Touchbar Monitoring), 54- (Trim Monitoring), 56- (Electric Latch Retraction), 59- (Delayed Egress), IN100 (Access Control), IN120 (Access Control), IN220 (Access Control), SN200 (Access Control), SN210 (Access Control)*

GENERAL

Configuration	Max. Size	Stiffness Class (min)	Positve Design Load (psf)	Negative Design Load (psf)	Impact (ft·lb)	Min. Latch Throw (in)	Min. Latch Strength (lbf)	Test Methods
Pair Out-Swing	8-0 x 8-0	I	86	-86	350	1/2	688	TAS 201, TAS 202, TAS 203

GENERAL

Additional Information

Two-point latching Model numbers for these devices may also be prefixed by the following designations: 53, 55, 56, 57, 58, 59, ET, H1, H2 and TL. Tested to 70 PSF per ASTM E330, ASTM E1886, ASTM E1996 and TAS 201, TAS 202 (Structural only), TAS 203. Devices have been tested to 86 PSF per ANSI/SDI A250.13.

Report Date: 2004-04-12
Revision Date: 2026-08-31

UL Solutions permits the reproduction of the material contained in Product iQ subject to the following conditions: 1. The Guide Information, Assemblies, Constructions, Designs, Systems, and/or Certifications (files) must be presented in their entirety and in a non-misleading manner, without any manipulation of the data (or drawings). 2. The statement "Reprinted from Product iQ with permission from UL Solutions" must appear adjacent to the extracted material. In addition, the reprinted material must include a copyright notice in the following format: "©2026 UL LLC."