Model HC-PE8700 Surface Vertical Rod Device

File Number: R21744

COMPANY

SARGENT MFG CO

100 SARGENT DR

NEW HAVEN, CT 06511-5918 United States

MODEL INFO

HC-PE8700 Surface Vertical Rod Device *May be provided with the following options: 12- (Fire-Rated), AL- (Alarm), 53- (Latchbolt Monitoring), 55- (Touchbar Monitoring), 54- (Trim Monitoring), 56- (Electric Latch Retraction), 59- (Delayed Egress), IN100 (Access Control), IN120 (Access Control), IN220 (Access Control), SN200 (Access Control), SN210 (Access Control), DELR (Delayed Egress and Electric Latch Retraction)*

GENERAL

Configuration	Max. Size	Stiffness Class (min)	Positve Design Load (psf)	Negative Design Load (psf)	Impact (ft·lb)	Min. Latch Throw (in)	Min. Latch Strength (lbf)	Test Methods
Pair Out-Swing	8-0 x 8-0	I	65	-65	350	3/4	520	TAS 201, TAS 202, TAS 203
Single Out-Swing	4-0 x 8-0	I	65	-65	350	3/4	520	--

GENERAL

Additional Information

Paired with (2) 988 surface bolts engaged (inactive leaf), Model options and designations are provided in the Model Info section.

Report Date: 2005-04-21
Revision Date: 2026-08-31

UL Solutions permits the reproduction of the material contained in Product iQ subject to the following conditions: 1. The Guide Information, Assemblies, Constructions, Designs, Systems, and/or Certifications (files) must be presented in their entirety and in a non-misleading manner, without any manipulation of the data (or drawings). 2. The statement "Reprinted from Product iQ with permission from UL Solutions" must appear adjacent to the extracted material. In addition, the reprinted material must include a copyright notice in the following format: "©2026 UL LLC."