

Model HC8800 Rim Exit Device

File Number: R21744

COMPANY
SARGENT MFG CO
100 SARGENT DR
NEW HAVEN, CT 06511-5918 United States

MODEL INFO
HC8800 Rim Exit Device *May be provided with the following options: 12- (Fire-Rated), AL- (Alarm), 53- (Latchbolt Monitoring), 55- (Touchbar Monitoring), 54- (Trim Monitoring), 56- (Electric Latch Retraction), 59- (Delayed Egress), IN100 (Access Control), IN120 (Access Control), IN220 (Access Control), SN200 (Access Control), SN210 (Access Control)*

GENERAL

Configuration	Max. Size	Stiffness Class (min)	Positive Design Load (psf)	Negative Design Load (psf)	Impact (ft-lb)	Min. Latch Throw (in)	Min. Latch Strength (lbf)	Test Methods
Pair Out-Swing	8-0 x 8-0	I	70	-70	350	3/4	1120	TAS 201, TAS 202, TAS 203
Single Out-Swing	4-0 x 8-0	I	70	-70	350	3/4	1120	--

GENERAL

Additional Information

The model numbers may also be prefixed by the following designations: 53, 55, 55-56, 56, 57, 58, AWE, B, ET, H1, H2, KP, LK, LU, M1, N1, N2, PA, PK, PG, P1, P2, IPSKM, CPKM, IPSM, CPM, IM, IKM, PRX, S1, S2, S3, IA, IK, IN, TK, TL, TP and TU. May be prefixed by "59-" designates an delayed egress option.

Report Date: 2004-04-13
Revision Date: 2026-08-31

UL Solutions permits the reproduction of the material contained in Product iQ subject to the following conditions: 1. The Guide Information, Assemblies, Constructions, Designs, Systems, and/or Certifications (files) must be presented in their entirety and in a non-misleading manner, without any manipulation of the data (or drawings). 2. The statement "Reprinted from Product iQ with permission from UL Solutions" must appear adjacent to the extracted material. In addition, the reprinted material must include a copyright notice in the following format: "©2026 UL LLC."