

Model 6150EDWS

File Number: R21801

COMPANY
ASSA ABLOY ACCENTRA
225 Episcopal Road
Berlin, CT 06037 United States

MODEL INFO
6150EDWS
Rim Type Exit Device, "6000 Series"

GENERAL

Configuration	Max. Size	Stiffness Class (min)	Positive Design Load (psf)	Negative Design Load (psf)	Impact (ft-lb)	Min. Latch Throw (in)	Min. Latch Strength (lbf)	Test Methods
Single Out-Swing	4-0 x 1 8-0		70	-70	350	3/4	1120	SDI A250.13, ASTM E330, ASTM E1886, ASTM E1996, TAS 201, TAS 202, TAS 203
Pair Out-Swing	8-0 x 1 8-0		70	-70	350	3/4	1120	SDI A250.13, ASTM E330, ASTM E1886, ASTM E1996, TAS 201, TAS 202, TAS 203

GENERAL

Additional Information

Models may or may not employ the following suffixes: -MELR. TAS 202 (Structural, FER)

Report Date: 2026-02-27
Revision Date: 2026-03-10

UL Solutions permits the reproduction of the material contained in Product iQ subject to the following conditions: 1. The Guide Information, Assemblies, Constructions, Designs, Systems, and/or Certifications (files) must be presented in their entirety and in a non-misleading manner, without any manipulation of the data (or drawings). 2. The statement "Reprinted from Product iQ with permission from UL Solutions" must appear adjacent to the extracted material. In addition, the reprinted material must include a copyright notice in the following format: "©2026 UL LLC."