

Latching Hardware

COMPANY

ASSA ABLOY ACCENTRA

225 EPISCOPAL RD.

BERLIN, CT 06037-1524 United States

R21801

Model	Configuration	Max Size	Stiffness Class (min)	Design Load (psf)	Impact (ft-lbs)	Latch Throw Min (in.)	Latch Strength Min (lbf)
7150(F)WS/7250M(F)WS Squarebolt Exit Device* with or without 500F, 600F Series Trims or prefixed "Sym" (Symphony Trim)	Single	4-0 x 8-0	I	+/-70	350	3/4	1120
7150/7250M(F)WS*	out-swing						
W/M100F, M200FWS, KRM200FWS Mullions	Paired	8-0 x 8-0					
	out-swing						
7170(F)WS SVR Exit Device* with or without 500F, 600F Series Trims or prefixed "Syms" (Symphony Trim)	Single	4-0 x 8-0	I	+/-70	350	3/4	1120
	out-swing						
	Paired	8-0 x 8-0					
	out-swing						
	Door Pair	8-0, 8-0	I	+/-70	350	N/A	N/A
KRM-100F Series, Keyed Removable Mullion	Door Pair	8-0, 7-0					
988Y, 988Y-1, and 988Y-2 Surface Bolts	Paired	6-0 x 8-0	I	+/-60	350	—	720
NTC600 Series Interconnect Lockset	Single	3-0 x 7-0	I	+/- 70	350	1/2	735

4800 Series Interconnect Lockset	Single In Swing Deadbolt & Latchbolt engaged	3-0 x 7-0	I	+/- 70	350	1/2	735
82 Series Interconnect Lockset	Single In Swing Deadbolt & Latchbolt engaged	3-0 x 7-0	I	+/- 70	350	1/2	735
D Series Interconnect Lockset	Single In Swing Deadbolt & Latchbolt engaged	3-0 x 7-0	I	+/- 70	350	1/2	735
5300/5300LN Series Cylindrical Lockset	Single	3-0 x 7-0	I	+/- 60	350	1/2	630
5300/5300LN Series Cylindrical Lockset with or without, Securitron UNL unlatch electromechanical strike	Single	3-0 x 7-0	I	+/- 60	350	1/2	630
5400/5400LN Series Cylindrical Lockset with or without, Securitron UNL unlatch electromechanical strike	Single	3-0 x 7-0	I	+/- 60	350	1/2	630
5400/5400LN Series Cylindrical Lockset S5400LN x Sym Series Cylindrical Lockset	Single In Swing	3-0 x 7-0	I	+/- 60	350	1/2	630
5400/5400LN Series Cylindrical Lockset & 3600 Series Deadbolt or D100 Series Deadbolt	Single In Swing Deadbolt & Latchbolt engaged	3-0 x 7-0	I	+/- 70	350	1/2	735
7150 (F)WS, Squarebolt Exit Device* Squarebolt Exit Device* with or without 500F, 600F Series Trims or prefixed "Sym"(Symphony Trim)	Single	3-0 x 7-0	I	+/- 60	350	3/4	630
8800 Series Mortise Lockset***, S8800 x Sym Series Mortise Lockset	Single Inswing or Outswing	3-0 x 7-0	I	+/- 60	350	3/4	630
8800 Series Mortise Lockset, S8800 x Sym Series Mortise Lockset	Single In Swing or Outswing Latchbolt and Deadbolt engaged	3-0 x 7-0	I	+/- 70	350	3/4	735
8800 Series Mortise Lockset, S8800 x Sym Series Mortise Lockset (Latchbolt x Deadbolt)	Paired Latchbolt and deadbolt engaged with (2) 988Y, 988Y-1, or 988Y-2 surface bolts engaged. (inactive leaf)	8-0 x 8-0	I	+/-70	350	3/4	1120
8800 Series Mortise Lockset, S8800 x Sym Series Mortise Lockset (Latchbolt x Deadbolt)	Single Latchbolt and deadbolt engaged	4-0 x 8-0	I	+/-70	350	3/4	1120

988Y, 988Y-1, and 988Y-2 Surface Bolts	Paired	8-0 x 8-0	I	+/-150	350	—	1200
8800 Series Mortise Lockset with or without Securitron EPTL Power Transfer***	Single	3-0 x 7-0	I	+/- 60	350	3/4	630
8800 Series Mortise Lockset with or without Securitron MUNL unlatch electromechanical strike***	Single	3-0 x 7-0	I	+/- 60	350	3/4	630
eBOSS E5400LN Series Cylindrical Lockset	Single	3-0 x 7-0	I	+/- 60	350	1/2	630
eBOSS E8800 Series Mortise Lockset	Single	3-0 x 7-0	I	+/- 60	350	3/4	630
4700LN Series Cylindrical Lockset	Single	3-0 x 7-0	I	+/- 50	350	1/2	525
inTouch E4760LN Series Electrically Controlled Cylindrical Lockset	Single	3-0 x 7-0	I	+/- 60	350	1/2	630
nexTouch NTB600 Series Electrically Controlled Cylindrical Lockset	Single	3-0 x 7-0	I	+/- 60	350	1/2	630
4600LN Series Cylindrical Lockset	Single	3-0 x 7-0	I	+/- 50	350	1/2	525
4600CL Series Cylindrical Lockset	Single, Outswing	3-0 x 7-0	I	+/- 60	350	1/2	630
8800 Series Mortise Lockset***. S8800FL x Sym Series Mortise Locks	Single	3-0 x 7-0	I	+/- 50	350	3/4	525
8800 Series Mortise Lockset (Latchbolt x Deadbolt)	Pair with (2) Rockwood 556 WS Flushbolts engaged (inactive leaf) Inswing or Outswing	6-0 x 7-0	I	+/- 70	350	3/4	735
7380F Series Multi-Point Lock	Single	4-0 x 8-0	I	+/- 150	350	3/4	800
7380F Series Multi-Point Lock	Pair with (2) 988Y, 988Y-1, or 988Y-2 surface bolts engaged (inactive leaf)	8-0 x 8-0	I	+/- 150	350	3/4	800

8800 Series Mortise Lockset, S8800 x Sym Series Mortise Lockset (Latchbolt x Deadbolt)	Single Door, Inswing or Outswing	3-0 x 7-0	I	+/-115	350	3/4	1208
NTM600 Series Sectional Mortise Lockset (Latchbolt x Deadbolt)	Single Door, Inswing or Outswing	4-0 x 8-0	I	+/- 70	350	3/4	1120
NTM600 Series Sectional Mortise Lockset (Latchbolt x Deadbolt)	Single Door, Inswing or Outswing	3-0 x 7-0	I	+/-115	350	3/4	1208
7150(F)WS/7250M(F)WS Squarebolt Exit Device* with or without 500F, 600F Series Trims or prefixed "Sym" (Symphony Trim)	Single door, Outswing	3-0 x 7-0	I	+/-115	350	3/4	1208
2100(F)WS Exit Device	Single door outswing	3-0 x 7-0	I	+/-50	350	3/4	525
inTouch E5360LN Series Electrically Controlled Cylindrical Lockset	Single	3-0 x 7-0	I	+/- 60	350	1/2	630
8800 Series Mortise Lockset, S8800 x Sym Series Mortise Lockset (Latchbolt x Deadbolt)	Paired Latchbolt and deadbolt engaged with (2) Rockwood 556 WS Flushbolts engaged (inactive leaf), Inswing or Outswing	8-0 x 8-0	I	+/-70	350	3/4	1120
8800 Series Mortise Lockset, S8800 x Sym Series Mortise Lockset (Latchbolt x Deadbolt)	Single Latchbolt and deadbolt engaged, Inswing or Outswing	4-0 x 8-0	I	+/-70	350	3/4	1120
YRD200 Series Deadbolt (Models YRD216, YRD226, YRD256) x HCG2 Series Tubular Lockset (Model HCG211) w/Knob or Lever	Single In Swing Deadbolt & Latchbolt engaged	3-0 x 7-0	I	+/- 70	350	1/2	735
NTD600 Series Deadbolt (Models NTD621, NTD623) x HCG2 Series Tubular Lockset (Model HCG211) w/Knob or Lever	Single In Swing Deadbolt & Latchbolt engaged	3-0 x 7-0	I	+/- 70	350	1/2	735
YRD400 Series Deadbolt (Models YRD410, F-YRD410, YRD420, F-YRD420, YRD430, F-YRD430, YRD450, F-YRD450) x HCG2 Series Tubular Lockset (Model HCG211) w/Knob or Lever	Single In Swing Deadbolt & Latchbolt engaged	3-0 x 7-0	I	+/- 70	350	1/2	735
HCG2 Series Deadbolt (Model HCG282) x HCG2 Series Tubular Lock (Model HCG211) w/Knob or Lever	Single In Swing Deadbolt & Latchbolt engaged	3-0 x 7-0	I	+/- 70	350	1/2	735
HCG2 Series Deadbolt (Model HCG282) x HCG2 Series Tubular Lock (Model HCG271) w/Knob or Lever	Single In Swing Deadbolt & Latchbolt engaged	3-0 x 7-0	I	+/- 70	350	1/2	735

Series SBM100 Mortise Lockset	Single	3-0 x 7-0	I	+/- 60	350	3/4	630
SSB100 Series Cylindrical Lockset	Single Door, Inswing or Outswing	3-0 x 7-0	I	+/-60	350	1/2	630
NTC600 Series Interconnect Lockset	Single In Swing Deadbolt & Latchbolt engaged	3-0 x 7-0	I	+/- 70	350	1/2	735
*NTD600 Series Deadbolt (Models NTD621, NTD623) x HCG2 Series Tubular Lockset (Model HCG211) w/Knob or Lever	Single In Swing Deadbolt & Latchbolt engaged	3-0 x 7-0	I	+/- 70	350	1/2	735

* 7150(F)WS, 7250M(F)WS & 7170(F)WS series may be suffixed by "MELR" or "P" (Latch retraction), with any combination of "A" (Alarm Option), "B" (Touchbar Monitor), "O" (Trim Monitor), or "S" (Bolt Monitor). These devices may be prefixed by "Sym" for Symphony Trim or exit devices can include 500F or 600F Series Trims.

*7150(F)WS, 7250M(F)WS can include NTT600 Series Trim.

S8800 or 8800 series may be suffixed by "FL" designating lever trim option.

Vxx - Sectional Escutcheon Trim and Vxx-VN Integrated Escutcheon Trim for use with Mortise-Type Locks Series 8800.

Products also tested to TAS 201, TAS 202, TAS 203, PA 201, PA 202 and PA 203.

*** - May be followed by suffix "MELR"

Trademark and/or tradename: "ASSA ABLOY", "ASSA ABLOY INC", "ACCENTRA", "ASSA ABLOY ACCENTRA", 



Last Updated on 2024-05-08

The appearance of a company's name or product in this database does not in itself assure that products so identified have been manufactured under UL Solutions' Follow - Up Service. Only those products bearing the UL Mark should be considered to be Certified and covered under UL Solutions' Follow - Up Service. Always look for the Mark on the product.

UL Solutions permits the reproduction of the material contained in Product iQ subject to the following conditions: 1. The Guide Information, Assemblies, Constructions, Designs, Systems, and/or Certifications (files) must be presented in their entirety and in a non-misleading manner, without any manipulation of the data (or drawings). 2. The statement "Reprinted from Product iQ with permission from UL Solutions" must appear adjacent to the extracted material. In addition, the reprinted material must include a copyright notice in the following format: "©2024 UL LLC."