

# NOTICE OF PRODUCT CERTIFICATION



CERTIFICATION NO: NI014627.01-R1  
DATE: 02/17/2022  
CERTIFICATION PROGRAM: Structural  
COMPANY: Sunset Windows  
CODE: 2348-1  
REVISION DATE: 05/27/2025

This certification represents product conformity to the applicable specification and that certification criteria has been satisfied. A NAMI approved certification label must be applied to the product to claim certification status. To affirm the certification status, please visit [www.namicertification.com](http://www.namicertification.com). NAMI is accredited to the ISO/IEC 17065 by the Standards Council of Canada (SCC).

| COMPANY NAME AND ADDRESS                                                                                   | PRODUCT DESCRIPTION                                                                                                                                                                                                                                                                                                                                                                                                                                        |
|------------------------------------------------------------------------------------------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>Sunset Windows and Doors, LLC</b><br><b>910 Warehouse Road, Unit 110104</b><br><b>Orlando, FL 32803</b> | <b>Series "V-750"</b><br><b>Vinyl Casement Window</b><br><br>Configuration: XX<br>Glazing: Mono-3/16" Heat Strengthened Glass/0.090 Trosifol PVB<br>by Kuraray/3/16" Heat Strengthened Glass<br>IG-3/16" Tempered Glass/ 3/16" Heat Strengthened Glass/0.090<br>Trosifol PVB by Kuraray/3/16" Heat Strengthened Glass<br><br>Frame: W-1829mm(72") H-1981mm(78")<br><br>Vent: W-868mm(34.18") H-1912mm(75.29")<br><br>DLO: W-712mm(28.03") H-1755mm(69.10") |

| SPECIFICATION                                                                                                                                                          | PRODUCT RATING                                                                                                                                                                                                                        |
|------------------------------------------------------------------------------------------------------------------------------------------------------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>AAMA/WDMA/CSA 101/I.S.2/A440-17</b><br><b>AAMA/WDMA/CSA 101/I.S.2/A440-11</b><br><b>ASTM E1886-12/13a</b><br><b>ASTM E1996-12a/14a</b><br><b>TAS-201/202/203-94</b> | <b>Class CW-PG50 1829 x 1981 (72 x 78)-C</b><br><b>Design Pressure: ±2400 Pa (±50 psf)</b><br><b>Water Penetration Resistance Level: 504 Pa (10.5 psf)</b><br><b>Wind Zone 4-Missile Level D</b><br><b>Large Missile Impact Rated</b> |

Product Tested By: National Certified Testing Laboratories  
Report No: NCTL-210-4227-02/NCTL-210-4227-02A  
Expiration Date: August 31, 2035

Administrator's Signature:  \_\_\_\_\_

## NATIONAL ACCREDITATION AND MANAGEMENT INSTITUTE, INC.

4794 George Washington Memorial Highway  
Hayes, VA 23072  
Tel: (804) 684-5124  
[nami@namiinc.com](mailto:nami@namiinc.com)

NOPC-03/30/2023