NOTICE OF PRODUCT CERTIFICATION



CERTIFICATION NO: NI015604.04-R2

DATE: 06/20/2022

CERTIFICATION PROGRAM: <u>Structural</u>

COMPANY: Ply Gem

CODE: <u>1408-1</u>

REVISION DATE: 12/12/2022

This certification represents product conformity to the applicable specification and that certification criteria has been satisfied. A NAMI approved certification label must be applied to the product to claim certification status. To affirm the certification status, please visit www.namicertification.com. NAMI is accredited to the ISO/IEC 17065 by the ANSI National Accreditation Board (ANAB) and the Standards Council of Canada (SCC).

COMPANY NAME AND ADDRESS	PRODUCT DESCRIPTION
Ply Gem Window Group	Series "Perspective & MaxView"
Simonton Windows	Vinyl Sliding Glass Door
5020 Weston Parkway, Suite 300	(2-Track w/Exterior Pocket)
Cary, NC 27513	Configuration: XX-XXP Glazing: Insulating Glass-1/8" Tempered Glass/1/8" Heat Strengthened Glass/0.105" Eastman Saflex PVB Interlayer/1/8" Heat Strengthened Glass or 3/16" Tempered Glass/5/32" Heat Strengthened Glass/0.105" Eastman Saflex PVB Interlayer/5/32" Heat Strengthened Glass
	Frame: W-5944mm(234") H-2438mm(96")
	Panel: W-1524mm(60") H-2365mm(93.13")
	DLO: W-1295mm(51") H-2137mm(84.13")

SPECIFICATION	PRODUCT RATING
AAMA/WDMA/CSA 101/I.S.2/A440-17 ASTM E1886-05/12/13a ASTM E1996-12/12a/14	Class LC-PG50 5944 x 2438 (234 x 96)-SD Design Pressure: ±2400 Pa (±50 psf) Water Penetration Resistance Test Pressure: 360 Pa (7.52 psf) Missile Level D

Product Tested By: Molimo Architectural Product Testing

Report No: 3137.07-106-11/W-2035 Expiration Date: **December 31, 2025**

Administrator's Signature:

NATIONAL ACCREDITATION AND MANAGEMENT INSTITUTE, INC.

4794 George Washington Memorial Highway Hayes, VA 23072 Tel: (804) 684-5124

nami@namiinc.com