NOTICE OF PRODUCT CERTIFICATION



This certification represents product conformity to the applicable specification and that certification criteria has been satisfied. A NAMI approved certification label must be applied to the product to claim certification status. To affirm the certification status, please visit <u>www.namicertification.com</u>. NAMI is accredited to the ISO/IEC 17065 by the ANSI National Accreditation Board (ANAB) and the Standards Council of Canada (SCC).

COMPANY NAME AND ADDRESS	PRODUCT DESCRIPTION
Ply Gem Window Group	Series "Perspective & MaxView"
Simonton Windows	Vinyl Sliding Glass Door
5020 Weston Parkway, Suite 300	(2-Track w/Interior Pocket)
Cary, NC 27513	Configuration: XX-XXP Glazing: Insulating Glass-1/8" Tempered Glass/1/8" Heat Strengthened Glass/0.105" Eastman Saflex PVB Interlayer/1/8" Heat Strengthened Glass or 3/16" Tempered Glass/5/32" Heat Strengthened Glass/0.105" Eastman Saflex PVB Interlayer/5/32" Heat Strengthened Glass
	Frame: W-5944mm(234") H-2438mm(96")
	Panel: W-1524mm(60") H-2365mm(93.13")
	DLO: W-1295mm(51") H-2137mm(84.13")

SPECIFICATION	PRODUCT RATING
AAMA/WDMA/CSA 101/I.S.2/A440-17 ASTM E1886-05/12/13a ASTM E1996-12/12a/14	Class LC-PG50 5944 x 2438 (234 x 96)-SD Design Pressure: ±2400 Pa (±50 psf) Water Penetration Resistance Test Pressure: 360 Pa (7.52 psf) Missile Level D

Product Tested By: Report No: Expiration Date: Molimo Architectural Product Testing 3137.18-106-11/W-2035 March 31, 2026

Administrator's Signature:

NATIONAL ACCREDITATION AND MANAGEMENT INSTITUTE, INC.

4794 George Washington Memorial Highway Hayes, VA 23072 Tel: (804) 684-5124 nami@namiinc.com