## **NOTICE OF PRODUCT CERTIFICATION**



CERTIFICATION NO: DATE: CERTIFICATION PROGRAM: COMPANY: CODE:

NI015832.13	
07/25/2023	
Structural	
Ply Gem	
1408-1	

This certification represents product conformity to the applicable specification and that certification criteria has been satisfied. A NAMI approved certification label must be applied to the product to claim certification status. To affirm the certification status, please visit <u>www.namicertification.com</u>. NAMI is accredited to the ISO/IEC 17065 by the ANSI National Accreditation Board (ANAB) and the Standards Council of Canada (SCC).

COMPANY NAME AND ADDRESS	PRODUCT DESCRIPTION
Ply Gem Window Group	Series "Ply Gem Perspective/
Simonton Windows	Simonton MaxView"
520 Weston Parkway, Suite 300	Vinyl Sliding Glass Door
Cary, NC 27513	(3-Track w/Exterior Pocket)
	Configuration: XXX-XXXP Glazing: IG-3/16" Tempered Glass/1/8" Heat Strengthened Glass/0.105" Eastman Saflex PVB Interlayer/1/8" Heat Strengthened Glass or 3/16" Tempered Glass/5/32" Heat Strengthened Glass/0.105" Eastman Saflex PVB Interlayer/5/32" Heat Strengthened Glass
	Frame: W-7126mm(280.56") H-3035mm(119.5")
	Panel: W-1248mm(49.13") H-2974mm(117.06")
	DLO: W-1019mm(40.13") H-2745mm(108.06")

SPEC	IFICATION	PRODUCT RATING	
TAS 20	01/202/203-94	Design Pressure: ±2880 Pa (±60 psf) Positive Design Pressure: 2880 Pa (60 psf) Negative Design Pressure: 3120 Pa (65 psf) Water Penetration Resistance Test Pressure: 440 Pa (9.2 psf) Large Missile Impact Rated	
Product Tested By:	Molimo Architectural Pr	oduct Testing	
Report No:	11835.19-106-11		
Expiration Date:	<u>March 31, 2027</u>	Sho.	
Administrator's Sign	ature:		
NATIONAL ACCREDITATION AND			
MANAGEMENT INSTITUTE, INC.			
4794 George Washington Memorial Highway			
Hayes, VA 23072			
	Tel: (804	4) 684-5124	

nami@namiinc.com