

Model HT-AB

File Number: R41784

COMPANY
ONITY INC
4001 FAIRVIEW INDUSTRIAL DR SE
SALEM, OR 97302-1142 United States

MODEL INFO
HT-AB *Trillium*

GENERAL

Configuration	Max. Size	Stiffness Class (min)	Positive Design Load (psf)	Negative Design Load (psf)	Impact (ft·lb)	Min. Latch Throw (in)	Min. Latch Strength (lbf)	Test Methods
Single Out-Swing, Single In-Swing	4-0 x 18-0		60	-60	350	3/4	960	SDI A250.13, ASTM E330, ASTM E1886, ASTM E1996, TAS 201, TAS 202, TAS 203

GENERAL

Additional Information

TAS 202 evaluation for structural load and forced entry only. No air or water infiltration. Missile Level D, 9.0 lb 2 x 4 at 50 ft/s. With or without deadbolt.

Report Date: 2025-12-03

The appearance of a company's name or product in this database does not in itself assure that products so identified have been manufactured under UL Solutions' Follow - Up Service. Only those products bearing the UL Mark should be considered to be Certified and covered under UL Solutions' Follow - Up Service. Always look for the Mark on the product.

UL Solutions permits the reproduction of the material contained in Product iQ subject to the following conditions: 1. The Guide Information, Assemblies, Constructions, Designs, Systems, and/or Certifications (files) must be presented in their entirety and in a non-misleading manner, without any manipulation of the data (or drawings). 2. The statement "Reprinted from Product iQ with permission from UL Solutions" must appear adjacent to the extracted material. In addition, the reprinted material must include a copyright notice in the following format: "©2026 UL LLC."