



ZHDX.R22241 Hinges

[Page Bottom](#)

Hinges

[See General Information for Hinges](#)
MCKINNEY PRODUCTS CO

225 EPISCOPAL RD

BERLIN, CT 06037 USA

R22241

Model	Type	Shear Load (lbs) (leaf hinges only)	Max Opening Size (continuous or pivot hinges only)	Design Pressure (psf) (continuous or pivot hinges only)	Impact (ft- lbs)
4-1/2 x 4-1/2 TA2714	Leaf	3165	X	X	350
4-1/2 x 4-1/2 TA2714 x QC12					
4-1/2 x 4-1/2 TA/B2714 *					
4-1/2 x 4 TA/B2714 *					
4-1/2 x 4-1/2 T4A/B3786 *					
4-1/2 x 4-1/2 TA714 *					
4-1/2 x 4 TA714 *					
4-1/2 x 4 TA786*					
4-1/2 x 4-1/2 TA786 *					
4-1/2 x 4-1/2 SP3786 *					
4-1/2 x 4-1/2 TA/B2314 *					
4-1/2 x 4 TA/B2314 *					
4-1/2 x 4-1/2 TA4/B3386 *					
4-1/2 x 4-1/2 TA314 *					
4-1/2 x 4 TA314 *					
4-1/2 x 4 TA386 *					
4-1/2 x 4 T4A/B3386 *					
4-1/2 x 4 T4A/B3786 *					
4-1/2 x 4-1/2 TA386 *					
4-1/2 x 4-1/2 SP3386 *					
5 x 5 TA/B2714 *					
5 x 4-1/2 TA/B2714 *					
5 x 5 T4A/B3786 *					
5 x 4-1/2 T4A/B3786 *					
5 x 5 TA714 *					
5 x 4-1/2 TA714 *					
5 x 5 TA786 *					
5 x 4-1/2 TA786 *					

5 x 4-1/2 SP3786 *					
5 x 5 TA/B2314 *					
5 x 4-1/2 TA/B2314 *					
5 x 5 T4A/B3386 *					
5 x 4-1/2 T4A/B3386 *					
5 x 5 TA314 *					
5 x 4-1/2 TA314 *					
5 x 5 TA386 *					
5 x 4-1/2 TA386 *					
5 x 4-1/2 SP3386 *					
6 x 6 TA/B2714					
6 x 5 TA/B2714					
6 x 6 T4A/B3786					
6 x 5 T4A/B3786					
6 x 6 TA714					
6 x 5 TA714					
6 x 6 TA786					
6 x 5 TA786					
6 x 6 TA/B2314					
6 x 5 TA/B2314					
6 x 6 T4A/B3386					
6 x 5 T4A/B3386					
6 x 6 TA314					
6 x 5 TA314					
6 x 6 TA386					
6 x 5 TA386					
8 x 8 T6A/B3786					
8 x 6 T6A/B3786					
8 x 8 TB786					
8 x 6 TB786					
MCK-12-HD **	Continuous	—	4 ft x 8 ft single swing, 8 ft x 8 ft pair of doors	+150, -150	350
MCK-14-HD **	Continuous	—	4 ft x 8 ft single swing, 8 ft x 8 ft pair of doors	+150, -150	350
MCK-25-HD **	Continuous	—	4 ft x 8 ft single swing, 8 ft x 8 ft pair of doors	+150, -150	350
MCK HG 305 +	Continuous	—	4 ft x 8 ft single swing, 8 ft x 8 ft pair of doors	+150, -150	350
MCK-FM300, MCK-FM3500, MCK-FM3700 **	Continuous	—	4 ft x 8 ft single swing, 8 ft x 8 ft pair of doors	+150, -150	350

* Also with options QC, CC, QC x CS, QC x MM, CC x CS, or CC x MM, the shear load of these options is 2720 lbs.

** Products evaluated in accordance with TAS 201-94, TAS 202-94, TAS 203-94, ASTM E330, ASTM E1886, ASTM E1996-02 and ANSI/SDI A250.13.

Last Updated on 2017-09-08

[Questions?](#)

[Print this page](#)

[Terms of Use](#)

[Page Top](#)

© 2017 UL LLC

The appearance of a company's name or product in this database does not in itself assure that products so identified have been manufactured under UL's Follow-Up Service. Only those products bearing the UL Mark should be considered to be Certified and covered under UL's Follow-Up Service. Always look for the Mark on the product.

UL permits the reproduction of the material contained in the Online Certification Directory subject to the following conditions: 1. The Guide Information, Assemblies, Constructions, Designs, Systems, and/or Certifications (files) must be presented in their entirety and in a non-misleading manner, without any manipulation of the data (or drawings). 2. The statement "Reprinted from the Online Certifications Directory with permission from UL" must appear adjacent to the extracted material. In addition, the reprinted material must include a copyright notice in the following format: "© 2017 UL LLC".