



NOTES

- DESIGNED AND TESTED IN ACCORDANCE WITH THE WIND LOAD PROVISIONS OF THE FLORIDA BUILDING CODE, INTERNATIONAL BUILDING CODE, AND INTERNATIONAL RESIDENTIAL CODE. NOT TESTED FOR IMPACT RESISTANCE. PROFESSIONAL ENGINEER'S SEAL PROVIDED ONLY FOR VERIFICATION OF WIND LOAD CONSTRUCTION DETAILS.
- FOUR SECTION, 7' TALL DOOR SHOWN, TALLER DOORS WILL HAVE ADDITIONAL SECTIONS.
- SECTION HEIGHTS OF 20.81, 19.00, AND 16.75 ARE AVAILABLE, AND MAY BE USED IN COMBINATION TO ACHIEVE VARIOUS DOOR HEIGHTS. MAXIMUM DOOR HEIGHT IS 16'. FOR ADDITIONAL SECTIONS, THE STRUTTING SHALL BE CONSISTANT WITH THE TOP INTERMEDIATE SECTION.
- EMBOSSMENT PATTERNS OF 14.50 X 20.375, 15.5 X 43.375, 12.5 X 20.375, AND 12.5 X 43.375 MAY BE USED. DOOR WITHOUT EMBOSSMENTS ALSO AVAILABLE. EXTERIOR PAN THICKNESS IS 25 GA (.018") FOR THE 470, EMBOSSMENT TO BE HORIZONTAL PINSTRIPE.
- TORSION SPRINGS SHOWN. EXTENSION SPRINGS COUNTERBALANCE ALSO AVAILABLE.
- USE THIS BRACKET, REF. P/N 405964-0002 ON 8' HIGH DOORS ONLY.
- WINDOWS OR VENTS MAY ONLY BE PUT IN 21" SECTIONS. WINDOW SIZE MAY BE STANDARD EMBOSSMENT SIZE WITH THICKNESS OF 1/2" INSULATED, 1/8", 1/4".
- ATTACH STRUTS WITH TWO SCREWS AT THE END STILES AND IN PAIRS ALONG THE STRUT AT 12" CENTERS. STRUT LOCATION MAY VARY +/-2 IN. AT THE FOLLOWING LOCATIONS:
TOP SECTION: DIRECTLY ABOVE TOP FIXTURES
INTERMEDIATE SECTION: NONE FOR FIRST INTERMEDIATE
BOTTOM OF ALL OTHER INTERMEDIATES
BOTTOM SECTION: CENTER OF SECTION
- USE 5/16 X 1-5/8" LAG SCREW TO ATTACH JAMB BRACKET TO JAMB. JAMB DETAIL TO BE IN ACCORDANCE WITH DRAWING 409783. JAMB BRACKETS MAY NOT BE INSTALLED DIRECTLY ON TOP OF DRYWALL.
- ROLLER ASSY P/N 319138 AND 108135 (STEEL) MAY BE SUBSTITUTED FOR ROLLER ASSY P/N 608682 (NYLON).
- LOW HEADROOM TRACK MAY BE SUBSTITUTED FOR STANDARD TRACK.
- LOCK OR DRAWBAR OPERATOR REQUIRED TO HOLD THE DOOR CLOSED DURING HIGH WIND EVENT.
- EXTERIOR JAMB WEATHERSTRIP TO BE ATTACHED WITH EITHER 2" #8 SCREWS OR 2-1/2" 8D BRIGHT COMMON NAILS AT 12" O.C., STARTING 2" FROM THE GROUND.
- DOORS OVER 8' TALL WILL BE SUPPLIED WITH COMMERCIAL TRACK AND HARDWARE. COMMERCIAL TRACK JAMB FASTENING WILL BE 12" MAX CENTERS.
- 2" 20GA HEMMED STRUT 14B (412619-XXXX2) MAY BE SUBSTITUTED FOR HS-1 ROLLED STRUT 3A (400650-0001).




STANDARD TRACK DETAIL

SCALE: 1/16" = 1"




VIEW A-A
(TRACK ASSY REMOVED FOR CLARITY)

APPROVED PRESSURE RATING CHART			
DOOR WIDTH	9'	8'	6'
POS. DESIGN PRESSURE	26.7	30	40
NEG. DESIGN PRESSURE	-30.2	-34	-45.3
MAX. JAMB LOAD LBS/FT	136	136	136



INTERIOR ELEVATION

SCALE: 1/16"=1"





DETAIL "B"

SCALE: 1/4

Digitally signed by John E Scates
Date: 2025.11.20 15:24:13 -06'00'

FL # 11494

JOHN E. SCATES, PE
8811 TEEL PKWY #100-5175
FRISCO, TX 75036-4428
FL PE 51737 TX PE 56308/F2203




PROFESSIONAL ENGINEER'S SEAL PROVIDED ONLY FOR VERIFICATION OF WINDLOAD CONSTRUCTION DETAILS.

CENTER HINGE/SECTION	END STILE	RLR SHAFT BRACKET	STRUTS/SECT	ROLLER	VERT TRK
1	SINGLE	NO	HS-1	2"x7/16"	2"x .046" THK


THE DRAWING AND/OR TECHNICAL INFORMATION ON THIS SHEET IS THE PROPERTY OF OVERHEAD DOOR CORPORATION OR ITS SUBSIDIARY AND IS LOANED IN CONFIDENCE FOR ENGINEERING AND MUTUAL ASSISTANCE PURPOSES ONLY. AND MAY NOT BE REPRODUCED OR USED TO MANUFACTURE ANYTHING DISCLOSED HEREON WITHOUT THE EXPRESS PERMISSION OF OVERHEAD DOOR CORPORATION WHICH MAY RECALL THIS SHEET AT ANY TIME.

UNLESS OTHERWISE SPECIFIED			OVERHEAD DOOR		DALLAS, TEXAS		NAME		DATE		DRAWING TITLE:	
DIMENSIONS ARE IN INCHES/TOLERANCES ON	DECIMAL DIMENSIONS	HOLE DIMETERS	ANGLES ± ° 30'	MATERIAL:	N/A	APPLIED FINISH:	NONE	UNIT OF MEASURE:	EACH	CHECKED BY:	G FINERAN	WINDLOAD, 390, 470, 1600 26.7/-30.2 PSF (DESIGN) 9'0" MAX WIDE
200+ ± .03	UNDER .251+ .004-.003	UNDER .251 TO .000+ .008-.003	FRACTIONS ± 1/16"	APPROVED BY:	M SAWICKI	DATE:	10/15/08	DRAWING NUMBER	D-410723	SCALE:	3/8	SHEET 1 OF 2

NOTES




1 409808-0001, TOP FIXTURE
ATTACH TO DOOR WITH 4 SCREWS
P/N 605911-0001




2 405771-XXXX BOT. FIXTURE
ATTACH TO DOOR WITH 3 SCREWS
P/N 605911-0001

SUB	PART NUMBER	HAND	VIEW
A	405771-0001	LH	SHOWN
B	405771-0002	RH	OPP.




3 400650-XXX1, ROLLED HS STRUT

SUB	PART NUMBER	THK.	DIM H	STRUT
A	400650-0001	.030	2.25	HS-1
B	400650-0002	.052	2.25	HS-2
C	400650-0003	.055	3.50	HS-3
D	400650-0004	.020	2.25	HS-0




4 409334-0001 SLIDE LOCK ASSY
ATTACH TO DOOR WITH 4 SCREWS
P/N 605911-0001




5 407605-000X END HINGE
ATTACH TO DOOR WITH 4 SCREWS
P/N 605911-0001

SUB	PART NUMBER	"H"
A	407605-0002	.85
B	407605-0003	1.10
C	407605-0004	1.35
D	407605-0005	1.60





6 405964-000X BRACKET, JAMB JOINT
ATTACH TO TRACK WITH 1/4\"/>

SUB	PART. NUMBER	"L"
A	405964-0002	4.37
B	405964-0003	5.12
C	405964-0004	3.75




7 407603-0001 CENTER HINGE
ATTACH TO DOOR WITH 4 SCREWS
P/N 605911-0001




8 405964 & 046450, BRACKET, JAMB
ATTACH TO TRACK WITH 1/4\"/>

SUB	PART. NUMBER	"L"
A	405964-0000	2.75
B	405964-0001	3.25
C	046450-0003	4.00




- 9 108135, ROLLER ASSY, TR3
10 319138, ROLLER ASSY, TR3
11 608682-0001, ROLLER ASSY, TR3
12 608682-0002, ROLLER ASSY, TR3


PART NUMBER	"L"
108135	5.13
319138	7.00
608682-0001	4.70
608682-0002	7.56



THE DRAWING AND/OR TECHNICAL INFORMATION ON THIS SHEET IS THE PROPERTY OF OVERHEAD DOOR CORPORATION OR ITS SUBSIDIARY AND IS LOANED IN CONFIDENCE FOR ENGINEERING AND MUTUAL ASSISTANCE PURPOSES ONLY, AND MAY NOT BE REPRODUCED OR USED TO MANUFACTURE ANYTHING DISCLOSED HEREON WITHOUT THE EXPRESS PERMISSION OF OVERHEAD DOOR CORPORATION WHICH MAY RECALL THIS SHEET AT ANY TIME.



13 405742-0001, BRACKET, ROLLER SHAFT
ATTACH TO DOOR WITH 2 SCREWS
P/N 605911-0001
0.085\"/>



14 411186 & 412619, HEMMED STRUT

SUB	PART NUMBER	THK.	DIM H	STRUT
A	412619-XXXX1	.018	2.00	2\"/>
B	412619-XXXX2	.034	2.00	2\"/>
C	411186-XXX2	.034	3.00	3\"/>

UNLESS OTHERWISE SPECIFIED

DIMENSIONS ARE IN INCHES	TOLERANCES ON DIMENSIONS
DECIMAL DIMENSIONS	HOLE DIMENSIONS
XX+ ± .03	UNDER .251+.004-.003
.000+ ± .005	.251 TO .500+.006-.003
	OVER .500+.008-.003

APPLIED FINISH:	UNIT OF MEASURE:
NONE	EACH

NAME	DATE
J. BARTON	9/23/08
CHECKED BY:	APPROVED BY:
G. FINERAN	M. SAWICKI

DRAWING TITLE:	DRAWING NUMBER
WINDLOAD, 390, 470, 1600 26.7/-30.2 PSF (DESIGN) 9'0\"/>	D-410723
SCALE:	SHEET
1/2	2 OF 2

FL # 11494

JOHN E. SCATES, PE
8811 TEEL PKWY #100-5175
FRISCO, TX 75036-4428
FL PE 51737 TX PE 56308/F2203

