



NOTES

- DESIGNED AND TESTED IN ACCORDANCE WITH THE WIND LOAD PROVISIONS OF THE FLORIDA BUILDING CODE, INTERNATIONAL BUILDING CODE, AND INTERNATIONAL RESIDENTIAL CODE. NOT TESTED FOR IMPACT RESISTANCE. PROFESSIONAL ENGINEER'S SEAL PROVIDED ONLY FOR VERIFICATION OF WIND LOAD CONSTRUCTION DETAILS.
- FIVE SECTION, 8' TALL DOOR SHOWN.
- SECTION HEIGHTS OF 20.81, 19.00, AND 16.75 ARE AVAILABLE, AND MAY BE USED IN COMBINATION TO ACHIEVE VARIOUS DOOR HEIGHTS. MAXIMUM DOOR HEIGHT IS 8'.
- EMBOSSMENT PATTERNS OF 14.50 X 20.375, 15.5 X 43.375, 12.5 X 20.375, AND 12.5 X 43.375 MAY BE USED. DOOR WITHOUT EMBOSSMENTS ALSO AVAILABLE. EXTERIOR PAN THICKNESS IS 25 GA (.018") FOR THE 470, EMBOSSMENT TO BE HORIZONTAL PINSTRIPE.
- TORSION SPRINGS SHOWN. EXTENSION SPRINGS COUNTERBALANCE ALSO AVAILABLE.
- USE THIS BRACKET, REF. P/N 405964-0002 ON 8' HIGH DOORS ONLY.
- WINDOWS OR VENTS MAY ONLY BE PUT IN 21" SECTIONS. WINDOW SIZE MAY BE STANDARD EMBOSSMENT SIZE WITH THICKNESS OF 1/2" INSULATED, 1/8", OR 1/4".
- ATTACH STRUTS WITH TWO SCREWS AT THE END STILES AND IN PAIRS ALONG THE STRUT AT 12" CENTERS. STRUT LOCATION MAY VARY +/-2 IN. AT THE FOLLOWING LOCATIONS:
TOP SECTION: DIRECTLY ABOVE TOP FIXTURES
INTERMEDIATE SECTION: FIRST INTERMEDIATE 6" FROM TOP OF SECTION
ALL OTHER INTERMEDIATES BELOW END HINGE
BOTTOM SECTION: 9" FROM TOP OF SECTION
- USE 5/16 X 1-5/8" LAG SCREW TO ATTACH JAMB BRACKET TO JAMB. JAMB DETAIL TO BE IN ACCORDANCE WITH DRAWING 409783. JAMB BRACKETS MAY NOT BE INSTALLED DIRECTLY ON TOP OF DRYWALL.
- ROLLER ASSY P/N 319138 AND 108135 (STEEL) MAY BE SUBSTITUTED FOR ROLLER ASSY P/N 608682 (NYLON).
- LOW HEADROOM TRACK MAY BE SUBSTITUTED FOR STANDARD TRACK.
- LOCK OR DRAWBAR OPERATOR REQUIRED TO HOLD THE DOOR CLOSED DURING HIGH WIND EVENT.
- EXTERIOR JAMB WEATHERSTRIP TO BE ATTACHED WITH EITHER 2" #8 SCREWS OR 2-1/2" 8D BRIGHT COMMON NAILS AT 12" O.C., STARTING 2" FROM THE GROUND.
- DOORS OVER 8' TALL WILL BE SUPPLIED WITH COMMERCIAL TRACK AND HARDWARE. COMMERCIAL TRACK JAMB FASTENING WILL BE 12" MAX CENTERS.
- 2" 25GA HEMMED STRUT 14A (412619-XXXX1) MAY BE SUBSTITUTED FOR HS-0 ROLLED STRUT 3D (400650-0004).




STANDARD TRACK DETAIL
SCALE: 1/16" = 1"

CENTER HINGE/SECTION	END STILE	ROLLER SHAFT BRACKET	STRUTS/SECT.	ROLLER	VERTICAL TRACK
1	SINGLE	NO	HS-0	2" X 7/16"	2"X 0.068" THK



VIEW A-A
(TRACK ASSY REMOVED FOR CLARITY)

APPROVED PRESSURE RATING CHART				
WIDTH	10'	9'	8'	6'
POS. DESIGN PRESSURE	22.8	25.3	28.5	38
NEG. DESIGN PRESSURE	-25.8	-28.7	-32.3	-43
MAX. JAMB LOAD (LBS/FT-HT)	129	129	129	129




INTERIOR ELEVATION
SCALE: 1/16"=1"

Digitally signed by John E Scates
Date: 2025.11.20 15:21:15 -06'00'



FL # 11494

JOHN E. SCATES, PE
8811 TEEL PKWY #100-5175
FRISCO, TX 75036-4428
FL PE 51737 TX PE 56308/F2203



DETAIL "B"
SCALE: 1/4

PROFESSIONAL ENGINEER'S SEAL PROVIDED ONLY FOR VERIFICATION OF WINDLOAD CONSTRUCTION DETAILS.



THE DRAWING AND/OR TECHNICAL INFORMATION ON THIS SHEET IS THE PROPERTY OF OVERHEAD DOOR CORPORATION OR ITS SUBSIDIARY AND IS LOANED IN CONFIDENCE FOR ENGINEERING AND MUTUAL ASSISTANCE PURPOSES ONLY, AND MAY NOT BE REPRODUCED OR USED TO MANUFACTURE ANYTHING DISCLOSED HEREON WITHOUT THE EXPRESS PERMISSION OF OVERHEAD DOOR CORPORATION WHICH MAY RECALL THIS SHEET AT ANY TIME.


UNLESS OTHERWISE SPECIFIED		
DIMENSIONS ARE IN INCHES-TOLERANCES ON DECIMAL DIMENSIONS	HOLE DIAMETERS	ANGLES ± 0° 30'
.300" ± .03	UNDER .251" ± .004-.003	FRACTIONS ± 1/16"
.000" ± .005	.251 TO .500" ± .006-.003	OVER .500" ± .008-.003

APPLIED FINISH:	UNIT OF MEASURE:
NONE	EACH


NAME	DATE
J. BARTON	9/23/08
CHECKED BY:	DATE
G FINERAN	10/15/08
APPROVED BY:	DATE
M SAWICKI	10/15/08

DRAWING TITLE:	DRAWING NUMBER	SCALE:	SHEET	OF
WINDLOAD, 390, 470, 1600 +22.8/-25.8 PSF (DESIGN), 10'-0" MAX WIDE	D-410726	3/8	1	2

NOTES




1 409808-0001, TOP FIXTURE
ATTACH TO DOOR WITH 4 SCREWS
P/N 605911-0001




2 405771-XXXX BOT. FIXTURE
ATTACH TO DOOR WITH 3 SCREWS
P/N 605911-0001

SUB	PART NUMBER	HAND	VIEW
A	405771-0001	LH	SHOWN
B	405771-0002	RH	OPP.




3 400650-XXX1, ROLLED HS STRUT

SUB	PART NUMBER	THK.	DIM H	STRUT
A	400650-0001	.030	2.25	HS-1
B	400650-0002	.052	2.25	HS-2
C	400650-0003	.055	3.50	HS-3
D	400650-0004	.020	2.25	HS-0




4 409334-0001 SLIDE LOCK ASSY
ATTACH TO DOOR WITH 4 SCREWS
P/N 605911-0001




5 407605-000X END HINGE
ATTACH TO DOOR WITH 4 SCREWS
P/N 605911-0001

SUB	PART NUMBER	"H"
A	407605-0002	.85
B	407605-0003	1.10
C	407605-0004	1.35
D	407605-0005	1.60





6 405964-000X BRACKET, JAMB JOINT
ATTACH TO TRACK WITH 1/4" TRACK
BOLT AND NUT

SUB	PART. NUMBER	"L"
A	405964-0002	4.37
B	405964-0003	5.12
C	405964-0004	3.75




7 407603-0001 CENTER HINGE
ATTACH TO DOOR WITH 4 SCREWS
P/N 605911-0001





8 405964 & 046450, BRACKET, JAMB
ATTACH TO TRACK WITH 1/4" TRACK
BOLT AND NUT

SUB	PART. NUMBER	"L"
A	405964-0000	2.75
B	405964-0001	3.25
	046450-0003	4.00




9 108135, ROLLER ASSY, TR3
10 319138, ROLLER ASSY, TR3
11 608682-0001, ROLLER ASSY, TR3
12 608682-0002, ROLLER ASSY, TR3

PART NUMBER	"L"
108135	5.13
319138	7.00
608682-0001	4.70
608682-0002	7.56



13 405742-0001, BRACKET, ROLLER SHAFT
ATTACH TO DOOR WITH 2 SCREWS
P/N 605911-0001
0.085" THK



14 411186 & 412619, HEMMED STRUT

SUB	PART NUMBER	THK.	DIM H	STRUT
A	412619-XXXX1	.018	2.00	2" 25GA
B	412619-XXXX2	.034	2.00	2" 20GA
C	411186-XXX2	.034	3.00	3" 20GA

THE DRAWING AND/OR TECHNICAL INFORMATION ON THIS SHEET IS THE PROPERTY OF OVERHEAD DOOR CORPORATION OR ITS SUBSIDIARY AND IS LOANED IN CONFIDENCE FOR ENGINEERING AND MUTUAL ASSISTANCE PURPOSES ONLY, AND MAY NOT BE REPRODUCED OR USED TO MANUFACTURE ANYTHING DISCLOSED HEREON WITHOUT THE EXPRESS PERMISSION OF OVERHEAD DOOR CORPORATION WHICH MAY RECALL THIS SHEET AT ANY TIME.

UNLESS OTHERWISE SPECIFIED				OVERHEAD DOOR		NAME		DATE		DRAWING TITLE:	
DIMENSIONS ARE IN INCHES-TOLERANCES ON DECIMAL DIMENSIONS				DALLAS, TEXAS		DRAWN BY:		9/23/08		WINDLOAD, 390, 470, 1600 22.8/-25.8 PSF (DESIGN), 10'-0" MAX	
HOLE DIAMETERS				ANGLES ± 0° 30'		CHECKED BY:		10/15/08		DRAWING NUMBER	
.250 ± .03				UNDER .251 ± .004-.003		MATERIAL:		APPROVED BY:		SCALE: 1/2	
.351 TO .500 ± .006-.003				OVER .500 ± .008-.003		N/A		M SAWICKI		SHEET 2 OF 2	
.000 ± .005				FRACTIONS ± 1/16"		APPLIED FINISH:		10/15/08			
						NONE					
						UNIT OF MEASURE:					
						EACH					

FL # 11494

JOHN E. SCATES, PE
8811 TEEL PKWY #100-5175
FRISCO, TX 75036-4428
FL PE 51737 TX PE 56308/F2203

