



8TH EDITION (2023) FLORIDA WIND ZONE COMPLIANCE WORKSHEET, Height (h) ≤ 30 ft

CERTAINTTEED					Ultimate Design Wind Speed - Vult (mph) – FBC Figures 1609.3(1) through 1609.3(4)										Exposure	Zone
Product	Profile	Max. Fastener Spacing	Fastener Engage	Design Pressure (psf)	110	120	130	140	150	160	170	180	190	200		
Board & Batten	S8	Nails: 12" o.c.	OSB or plywood sheathing	71	OK	OK	OK	OK	OK	OK	OK	OK	OK	OK	B	Interior Zone 4
					OK	OK	OK	OK	OK	OK	OK	OK	OK	OK	C	
					OK	OK	OK	OK	OK	OK	OK	OK	OK	NO	D	
					OK	OK	OK	OK	OK	OK	OK	OK	OK	OK	B	End Zone 5
					OK	OK	OK	OK	OK	OK	OK	OK	NO	NO	C	
					OK	OK	OK	OK	OK	OK	OK	NO	NO	NO	D	
Board & Batten Single 7 Vertical Siding	S7	Nails: 12" o.c.	OSB, plywood and/or studs	80	OK	OK	OK	OK	OK	OK	OK	OK	OK	OK	B	Interior Zone 4
					OK	OK	OK	OK	OK	OK	OK	OK	OK	OK	C	
					OK	OK	OK	OK	OK	OK	OK	OK	OK	OK	D	
					OK	OK	OK	OK	OK	OK	OK	OK	OK	OK	B	End Zone 5
					OK	OK	OK	OK	OK	OK	OK	OK	NO	NO	C	
					OK	OK	OK	OK	OK	OK	OK	OK	NO	NO	D	
Carolina Beaded	S6.5	Nails: 16" o.c.	Studs	41	OK	OK	OK	OK	OK	OK	OK	NO	NO	NO	B	Interior Zone 4
					OK	OK	OK	OK	NO	NO	NO	NO	NO	NO	C	
					OK	OK	OK	NO	NO	NO	NO	NO	NO	NO	D	
					OK	OK	OK	OK	OK	NO	NO	NO	NO	NO	B	End Zone 5
					OK	OK	OK	NO	NO	NO	NO	NO	NO	NO	C	
					OK	OK	NO	NO	NO	NO	NO	NO	NO	NO	D	
	S6.5	Staples: 16" o.c.	Studs	56	OK	OK	OK	OK	OK	OK	OK	OK	OK	OK	B	Interior Zone 4
					OK	OK	OK	OK	OK	OK	OK	NO	NO	NO	C	
					OK	OK	OK	OK	OK	NO	NO	NO	NO	NO	D	
					OK	OK	OK	OK	OK	OK	OK	OK	NO	NO	B	End Zone 5
					OK	OK	OK	OK	OK	NO	NO	NO	NO	NO	C	
					OK	OK	OK	OK	NO	NO	NO	NO	NO	NO	D	
	S6.5	Nails: 24" o.c.	Studs	35	OK	OK	OK	OK	OK	NO	NO	NO	NO	NO	B	Interior Zone 4
					OK	OK	OK	NO	NO	NO	NO	NO	NO	NO	C	
					OK	OK	NO	NO	NO	NO	NO	NO	NO	NO	D	
					OK	OK	OK	OK	NO	NO	NO	NO	NO	NO	B	End Zone 5
					OK	OK	NO	NO	NO	NO	NO	NO	NO	NO	C	
					OK	NO	NO	NO	NO	NO	NO	NO	NO	NO	D	
Carolina Beaded	S6.5	Staples: 24" o.c.	Studs	37	OK	OK	OK	OK	OK	OK	NO	NO	NO	NO	B	Interior Zone 4
					OK	OK	OK	NO	NO	NO	NO	NO	NO	NO	C	
					OK	OK	NO	NO	NO	NO	NO	NO	NO	NO	D	
					OK	OK	OK	OK	NO	NO	NO	NO	NO	NO	B	End Zone 5
					OK	OK	NO	NO	NO	NO	NO	NO	NO	NO	C	
					OK	NO	NO	NO	NO	NO	NO	NO	NO	NO	D	
Chamfer Board	D5	Nails: 16" o.c.	Through sheathing to studs	37	OK	OK	OK	OK	OK	OK	NO	NO	NO	NO	B	Interior Zone 4
					OK	OK	OK	NO	NO	NO	NO	NO	NO	NO	C	
					OK	OK	NO	NO	NO	NO	NO	NO	NO	NO	D	
					OK	OK	OK	OK	NO	NO	NO	NO	NO	NO	B	End Zone 5
					OK	OK	NO	NO	NO	NO	NO	NO	NO	NO	C	
					OK	NO	NO	NO	NO	NO	NO	NO	NO	NO	D	



8TH EDITION (2023) FLORIDA WIND ZONE COMPLIANCE WORKSHEET, Height (h) ≤ 30 ft

CERTAINTTEED					Ultimate Design Wind Speed - Vult (mph) – FBC Figures 1609.3(1) through 1609.3(4)										Exposure	Zone
Product	Profile	Max. Fastener Spacing	Fastener Engage	Design Pressure (psf)	110	120	130	140	150	160	170	180	190	200		
Encore	D4	Nails: 16" o.c.	Studs	77	OK	OK	OK	OK	OK	OK	OK	OK	OK	OK	B	Interior Zone 4
					OK	OK	OK	OK	OK	OK	OK	OK	OK	OK	C	
					OK	OK	OK	OK	OK	OK	OK	OK	NO	NO	D	
					OK	OK	OK	OK	OK	OK	OK	OK	OK	OK	B	End Zone 5
					OK	OK	OK	OK	OK	OK	OK	OK	NO	NO	C	
	D4	Staples: 16" o.c.	Studs	53	OK	OK	OK	OK	OK	OK	OK	OK	OK	NO	B	Interior Zone 4
					OK	OK	OK	OK	OK	OK	NO	NO	NO	NO	C	
					OK	OK	OK	OK	OK	NO	NO	NO	NO	NO	D	
					OK	OK	OK	OK	OK	OK	OK	NO	NO	NO	B	End Zone 5
					OK	OK	OK	NO	NO	NO	NO	NO	NO	NO	C	
	D4	Nails: 24" o.c.	Studs	40	OK	OK	OK	OK	OK	OK	OK	NO	NO	NO	B	Interior Zone 4
					OK	OK	OK	NO	NO	NO	NO	NO	NO	NO	C	
					OK	OK	OK	NO	NO	NO	NO	NO	NO	NO	D	
					OK	OK	OK	OK	OK	NO	NO	NO	NO	NO	B	End Zone 5
					OK	OK	NO	NO	NO	NO	NO	NO	NO	NO	C	
	D4.5DL	Nails: 16" o.c.	Studs	47	OK	OK	OK	OK	OK	OK	OK	OK	NO	NO	B	Interior Zone 4
					OK	OK	OK	OK	OK	NO	NO	NO	NO	NO	C	
					OK	OK	OK	OK	NO	NO	NO	NO	NO	NO	D	
					OK	OK	OK	OK	OK	OK	NO	NO	NO	NO	B	End Zone 5
					OK	OK	NO	NO	NO	NO	NO	NO	NO	NO	C	
	D5	Nails: 16" o.c.	Studs	57	OK	OK	OK	OK	OK	OK	OK	OK	OK	OK	B	Interior Zone 4
					OK	OK	OK	OK	OK	OK	OK	NO	NO	NO	C	
					OK	OK	OK	OK	OK	NO	NO	NO	NO	NO	D	
					OK	OK	OK	OK	OK	OK	OK	OK	NO	NO	B	End Zone 5
					OK	OK	OK	OK	NO	NO	NO	NO	NO	NO	C	
	D5	Nails: 24" o.c.	Studs	33	OK	OK	OK	OK	OK	NO	NO	NO	NO	NO	B	Interior Zone 4
					OK	OK	OK	NO	NO	NO	NO	NO	NO	NO	C	
					OK	OK	NO	NO	NO	NO	NO	NO	NO	NO	D	
					OK	OK	OK	OK	NO	NO	NO	NO	NO	NO	B	End Zone 5
					OK	NO	NO	NO	NO	NO	NO	NO	NO	NO	C	
					NO	NO	NO	NO	NO	NO	NO	NO	NO	NO	D	



8TH EDITION (2023) FLORIDA WIND ZONE COMPLIANCE WORKSHEET, Height (h) ≤ 30 ft

CERTAINTTEED					Ultimate Design Wind Speed - Vult (mph) – FBC Figures 1609.3(1) through 1609.3(4)										Exposure	Zone
Product	Profile	Max. Fastener Spacing	Fastener Engage	Design Pressure (psf)	110	120	130	140	150	160	170	180	190	200		
MainStreet	D4	Nails: 16" o.c.	Studs	76	OK	OK	OK	OK	OK	OK	OK	OK	OK	OK	B	Interior Zone 4
					OK	OK	OK	OK	OK	OK	OK	OK	OK	NO	C	
					OK	OK	OK	OK	OK	OK	OK	OK	NO	NO	D	
					OK	OK	OK	OK	OK	OK	OK	OK	OK	OK	B	End Zone 5
					OK	OK	OK	OK	OK	OK	OK	NO	NO	NO	C	
					OK	OK	OK	OK	OK	OK	NO	NO	NO	NO	D	
	D4	Staples: 16" o.c.	Studs	83	OK	OK	OK	OK	OK	OK	OK	OK	OK	OK	B	Interior Zone 4
					OK	OK	OK	OK	OK	OK	OK	OK	OK	OK	C	
					OK	OK	OK	OK	OK	OK	OK	OK	OK	NO	D	
					OK	OK	OK	OK	OK	OK	OK	OK	OK	OK	B	End Zone 5
					OK	OK	OK	OK	OK	OK	OK	NO	NO	NO	C	
					OK	OK	OK	OK	OK	OK	OK	NO	NO	NO	D	
	D4	Nails: 24" o.c.	Studs	43	OK	OK	OK	OK	OK	OK	OK	NO	NO	NO	B	Interior Zone 4
					OK	OK	OK	NO	NO	NO	NO	NO	NO	NO	D	
					OK	OK	OK	OK	OK	NO	NO	NO	NO	NO	B	
					OK	OK	OK	NO	NO	NO	NO	NO	NO	NO	C	End Zone 5
					OK	OK	NO	NO	NO	NO	NO	NO	NO	NO	D	
	D4DL	Nails: 16" o.c.	Studs	64	OK	OK	OK	OK	OK	OK	OK	OK	OK	OK	B	Interior Zone 4
					OK	OK	OK	OK	OK	OK	OK	OK	NO	NO	C	
					OK	OK	OK	OK	OK	OK	NO	NO	NO	NO	D	
					OK	OK	OK	OK	OK	OK	OK	OK	OK	NO	B	End Zone 5
					OK	OK	OK	OK	OK	OK	NO	NO	NO	NO	C	
					OK	OK	OK	OK	OK	NO	NO	NO	NO	NO	D	
	D5	Nails: 16" o.c.	Studs	64	OK	OK	OK	OK	OK	OK	OK	OK	OK	OK	B	Interior Zone 4
					OK	OK	OK	OK	OK	OK	OK	OK	NO	NO	C	
					OK	OK	OK	OK	OK	OK	NO	NO	NO	NO	D	
					OK	OK	OK	OK	OK	OK	OK	OK	OK	NO	B	End Zone 5
					OK	OK	OK	OK	OK	OK	NO	NO	NO	NO	C	
					OK	OK	OK	OK	OK	NO	NO	NO	NO	NO	D	
	D5	Staples: 16" o.c.	Studs	37	OK	OK	OK	OK	OK	OK	NO	NO	NO	NO	B	Interior Zone 4
					OK	OK	OK	NO	NO	NO	NO	NO	NO	NO	C	
					OK	OK	NO	NO	NO	NO	NO	NO	NO	NO	D	
					OK	OK	NO	NO	NO	NO	NO	NO	NO	NO	B	End Zone 5
					OK	NO	NO	NO	NO	NO	NO	NO	NO	NO	C	
					OK	NO	NO	NO	NO	NO	NO	NO	NO	NO	D	
	D5	Nails: 24" o.c.	Studs	47	OK	OK	OK	OK	OK	OK	OK	OK	NO	NO	B	Interior Zone 4
					OK	OK	OK	OK	OK	NO	NO	NO	NO	NO	C	
					OK	OK	OK	OK	OK	OK	NO	NO	NO	NO	D	
					OK	OK	OK	OK	OK	OK	NO	NO	NO	NO	B	End Zone 5
					OK	OK	OK	OK	OK	NO	NO	NO	NO	NO	C	
					OK	OK	NO	NO	NO	NO	NO	NO	NO	NO	D	
	D5DL	Nails: 16" o.c.	Studs	60	OK	OK	OK	OK	OK	OK	OK	OK	OK	OK	B	Interior Zone 4
					OK	OK	OK	OK	OK	OK	OK	NO	NO	NO	C	
					OK	OK	OK	OK	OK	OK	NO	NO	NO	NO	D	
					OK	OK	OK	OK	OK	OK	OK	OK	NO	NO	B	End Zone 5
					OK	OK	OK	OK	OK	NO	NO	NO	NO	NO	C	
					OK	OK	OK	OK	NO	NO	NO	NO	NO	NO	D	



8TH EDITION (2023) FLORIDA WIND ZONE COMPLIANCE WORKSHEET, Height (h) ≤ 30 ft

CERTAINTTEED					Ultimate Design Wind Speed - Vult (mph) – FBC Figures 1609.3(1) through 1609.3(4)										Exposure	Zone
Product	Profile	Max. Fastener Spacing	Fastener Engage	Design Pressure (psf)	110	120	130	140	150	160	170	180	190	200		
MainStreet	D5DL	Staples: 16" o.c.	Studs	58	OK	OK	OK	OK	OK	OK	OK	OK	OK	OK	B	Interior Zone 4
					OK	OK	OK	OK	OK	OK	OK	NO	NO	NO	C	
					OK	OK	OK	OK	OK	NO	NO	NO	NO	NO	D	
					OK	OK	OK	OK	OK	OK	OK	OK	NO	NO	B	End Zone 5
					OK	OK	OK	OK	NO	NO	NO	NO	NO	NO	C	
	D5DL	Nails: 24" o.c.	Studs	42	OK	OK	OK	OK	OK	OK	OK	NO	NO	NO	B	Interior Zone 4
					OK	OK	OK	NO	NO	NO	NO	NO	NO	NO	C	
					OK	OK	OK	NO	NO	NO	NO	NO	NO	NO	D	
					OK	OK	OK	OK	OK	NO	NO	NO	NO	NO	B	End Zone 5
					OK	OK	OK	NO	NO	NO	NO	NO	NO	NO	C	
	D5DL	Staples: 24" o.c.	Studs	36	OK	OK	OK	OK	OK	OK	NO	NO	NO	NO	B	Interior Zone 4
					OK	OK	OK	NO	NO	NO	NO	NO	NO	NO	C	
					OK	OK	NO	NO	NO	NO	NO	NO	NO	NO	D	
					OK	OK	OK	OK	NO	NO	NO	NO	NO	NO	B	End Zone 5
					OK	OK	NO	NO	NO	NO	NO	NO	NO	NO	C	
Monogram	D4	Nails: 16" o.c.	Studs	116	OK	OK	OK	OK	OK	OK	OK	OK	OK	OK	B	Interior Zone 4
					OK	OK	OK	OK	OK	OK	OK	OK	OK	OK	C	
					OK	OK	OK	OK	OK	OK	OK	OK	OK	OK	D	
					OK	OK	OK	OK	OK	OK	OK	OK	OK	OK	B	End Zone 5
					OK	OK	OK	OK	OK	OK	OK	OK	OK	OK	C	
	D4	Staples: 16" o.c.	Studs	57	OK	OK	OK	OK	OK	OK	OK	OK	OK	OK	B	Interior Zone 4
					OK	OK	OK	OK	OK	OK	OK	NO	NO	NO	C	
					OK	OK	OK	OK	OK	NO	NO	NO	NO	NO	D	
					OK	OK	OK	OK	OK	OK	OK	OK	NO	NO	B	End Zone 5
					OK	OK	OK	OK	OK	NO	NO	NO	NO	NO	C	
	D4	Nails: 24" o.c.	Studs	51	OK	OK	OK	OK	OK	OK	OK	OK	OK	NO	B	Interior Zone 4
					OK	OK	OK	OK	OK	OK	NO	NO	NO	NO	C	
					OK	OK	OK	OK	NO	NO	NO	NO	NO	NO	D	
					OK	OK	OK	OK	OK	OK	OK	NO	NO	NO	B	End Zone 5
					OK	OK	OK	NO	NO	NO	NO	NO	NO	NO	C	
	D5	Nails: 16" o.c.	Studs	67	OK	OK	OK	OK	OK	OK	OK	OK	OK	OK	B	Interior Zone 4
					OK	OK	OK	OK	OK	OK	OK	OK	NO	NO	C	
					OK	OK	OK	OK	OK	OK	OK	NO	NO	NO	D	
					OK	OK	OK	OK	OK	OK	OK	OK	OK	NO	B	End Zone 5
					OK	OK	OK	OK	OK	NO	NO	NO	NO	NO	C	
	D5	Staples: 16" o.c.	Studs	47	OK	OK	OK	OK	OK	OK	OK	OK	NO	NO	B	Interior Zone 4
					OK	OK	OK	OK	OK	NO	NO	NO	NO	NO	C	
					OK	OK	OK	OK	NO	NO	NO	NO	NO	NO	D	
					OK	OK	OK	OK	OK	OK	NO	NO	NO	NO	B	End Zone 5
					OK	OK	NO	NO	NO	NO	NO	NO	NO	NO	C	



8TH EDITION (2023) FLORIDA WIND ZONE COMPLIANCE WORKSHEET, Height (h) ≤ 30 ft

CERTAINTTEED					Ultimate Design Wind Speed - Vult (mph) – FBC Figures 1609.3(1) through 1609.3(4)										Exposure	Zone
Product	Profile	Max. Fastener Spacing	Fastener Engage	Design Pressure (psf)	110	120	130	140	150	160	170	180	190	200		
Monogram	D5	Nails: 24" o.c.	Studs	47	OK	OK	OK	OK	OK	OK	OK	OK	NO	NO	B	Interior Zone 4
					OK	OK	OK	OK	OK	NO	NO	NO	NO	NO	C	
					OK	OK	OK	OK	OK	NO	NO	NO	NO	NO	D	
					OK	OK	OK	OK	OK	OK	NO	NO	NO	NO	B	End Zone 5
					OK	OK	OK	OK	NO	NO	NO	NO	NO	NO	C	
					OK	OK	NO	NO	NO	NO	NO	NO	NO	NO	D	
	D5DL	Nails: 16" o.c.	Studs	73	OK	OK	OK	OK	OK	OK	OK	OK	OK	OK	B	Interior Zone 4
					OK	OK	OK	OK	OK	OK	OK	OK	OK	NO	C	
					OK	OK	OK	OK	OK	OK	OK	NO	NO	NO	D	
					OK	OK	OK	OK	OK	OK	OK	OK	OK	OK	B	End Zone 5
					OK	OK	OK	OK	OK	OK	NO	NO	NO	NO	C	
					OK	OK	OK	OK	OK	OK	NO	NO	NO	NO	D	
	D5DL	Staples: 16" o.c.	Studs	51	OK	OK	OK	OK	OK	OK	OK	OK	OK	NO	B	Interior Zone 4
					OK	OK	OK	OK	OK	OK	NO	NO	NO	NO	C	
					OK	OK	OK	OK	NO	NO	NO	NO	NO	NO	D	
					OK	OK	OK	OK	OK	OK	OK	NO	NO	NO	B	End Zone 5
					OK	OK	OK	OK	NO	NO	NO	NO	NO	NO	C	
					OK	OK	OK	NO	NO	NO	NO	NO	NO	NO	D	
	D5DL	Nails: 24" o.c.	Studs	44	OK	OK	OK	OK	OK	OK	OK	NO	NO	NO	B	Interior Zone 4
					OK	OK	OK	OK	OK	NO	NO	NO	NO	NO	C	
					OK	OK	OK	NO	NO	NO	NO	NO	NO	NO	D	
					OK	OK	OK	OK	OK	OK	NO	NO	NO	NO	B	End Zone 5
					OK	OK	OK	NO	NO	NO	NO	NO	NO	NO	C	
					OK	OK	NO	NO	NO	NO	NO	NO	NO	NO	D	
Monogram XL	D4	Nails: 16" o.c.	Studs	91	OK	OK	OK	OK	OK	OK	OK	OK	OK	OK	B	Interior Zone 4
					OK	OK	OK	OK	OK	OK	OK	OK	OK	OK	C	
					OK	OK	OK	OK	OK	OK	OK	OK	OK	NO	D	
					OK	OK	OK	OK	OK	OK	OK	OK	OK	OK	B	End Zone 5
					OK	OK	OK	OK	OK	OK	OK	OK	OK	NO	C	
	D4	Nails: 24" o.c.	Studs	64	OK	OK	OK	OK	OK	OK	OK	OK	OK	OK	B	Interior Zone 4
					OK	OK	OK	OK	OK	OK	OK	NO	NO	NO	C	
					OK	OK	OK	OK	OK	OK	NO	NO	NO	NO	D	
					OK	OK	OK	OK	OK	OK	OK	OK	OK	NO	B	End Zone 5
					OK	OK	OK	OK	OK	NO	NO	NO	NO	NO	C	
					OK	OK	OK	OK	OK	NO	NO	NO	NO	NO	D	
	D5DL	Nails: 16" o.c.	Studs	64	OK	OK	OK	OK	OK	OK	OK	OK	OK	OK	B	Interior Zone 4
					OK	OK	OK	OK	OK	OK	OK	OK	NO	NO	C	
					OK	OK	OK	OK	OK	OK	NO	NO	NO	NO	D	
					OK	OK	OK	OK	OK	OK	OK	OK	OK	NO	B	End Zone 5
					OK	OK	OK	OK	OK	NO	NO	NO	NO	NO	C	
					OK	OK	OK	OK	OK	NO	NO	NO	NO	NO	D	
	D5DL	Nails: 24" o.c.	Studs	40	OK	OK	OK	OK	OK	OK	OK	NO	NO	NO	B	Interior Zone 4
					OK	OK	OK	OK	NO	NO	NO	NO	NO	NO	C	
					OK	OK	OK	NO	NO	NO	NO	NO	NO	NO	D	
					OK	OK	OK	OK	OK	NO	NO	NO	NO	NO	B	End Zone 5
					OK	OK	NO	NO	NO	NO	NO	NO	NO	NO	C	
					OK	NO	NO	NO	NO	NO	NO	NO	NO	NO	D	



8TH EDITION (2023) FLORIDA WIND ZONE COMPLIANCE WORKSHEET, Height (h) ≤ 30 ft

CERTAINTEED					Ultimate Design Wind Speed - Vult (mph) – FBC Figures 1609.3(1) through 1609.3(4)										Exposure	Zone
Product	Profile	Max. Fastener Spacing	Fastener Engage	Design Pressure (psf)	110	120	130	140	150	160	170	180	190	200		
Northwoods	S7 Strait Edge Rough-Split Shakes	Nails: 16" o.c.	Studs	76	OK	OK	OK	OK	OK	OK	OK	OK	OK	OK	B	Interior Zone 4
					OK	OK	OK	OK	OK	OK	OK	OK	OK	NO	C	
					OK	OK	OK	OK	OK	OK	OK	OK	NO	NO	D	
					OK	OK	OK	OK	OK	OK	OK	OK	OK	OK	B	End Zone 5
					OK	OK	OK	OK	OK	OK	NO	NO	NO	NO	C	
	S7 Perfection Shingle	Nails: 16" o.c.	Studs	87	OK	OK	OK	OK	OK	OK	OK	OK	OK	OK	B	Interior Zone 4
					OK	OK	OK	OK	OK	OK	OK	OK	OK	OK	C	
					OK	OK	OK	OK	OK	OK	OK	OK	NO	NO	D	
					OK	OK	OK	OK	OK	OK	OK	OK	OK	OK	B	End Zone 5
					OK	OK	OK	OK	OK	OK	OK	NO	NO	NO	C	
	S9 Staggered Rough-Split Shakes	Nails: 16" o.c.	Studs	71	OK	OK	OK	OK	OK	OK	OK	OK	OK	OK	B	Interior Zone 4
					OK	OK	OK	OK	OK	OK	OK	OK	OK	NO	C	
					OK	OK	OK	OK	OK	OK	NO	NO	NO	NO	D	
					OK	OK	OK	OK	OK	OK	OK	OK	OK	OK	B	End Zone 5
					OK	OK	OK	OK	OK	OK	NO	NO	NO	NO	C	
Restoration Classic	D4	Nails: 16" o.c.	Studs	87	OK	OK	OK	OK	OK	OK	OK	OK	OK	OK	B	Interior Zone 4
					OK	OK	OK	OK	OK	OK	OK	OK	OK	OK	C	
					OK	OK	OK	OK	OK	OK	OK	OK	NO	NO	D	
					OK	OK	OK	OK	OK	OK	OK	OK	OK	OK	B	End Zone 5
					OK	OK	OK	OK	OK	OK	OK	NO	NO	NO	C	
	D4	Nails: 24" o.c.	Studs	69	OK	OK	OK	OK	OK	OK	OK	OK	OK	OK	B	Interior Zone 4
					OK	OK	OK	OK	OK	OK	OK	NO	NO	NO	C	
					OK	OK	OK	OK	OK	OK	OK	NO	NO	NO	D	
					OK	OK	OK	OK	OK	OK	OK	OK	OK	OK	B	End Zone 5
					OK	OK	OK	OK	OK	OK	NO	NO	NO	NO	C	
	D4.5	Nails: 16" o.c.	Studs	104	OK	OK	OK	OK	OK	OK	OK	OK	OK	OK	B	Interior Zone 4
					OK	OK	OK	OK	OK	OK	OK	OK	OK	OK	C	
					OK	OK	OK	OK	OK	OK	OK	OK	OK	OK	D	
					OK	OK	OK	OK	OK	OK	OK	OK	OK	OK	B	End Zone 5
					OK	OK	OK	OK	OK	OK	OK	OK	OK	NO	C	
	D4.5DL	Nails: 16" o.c.	Studs	76	OK	OK	OK	OK	OK	OK	OK	OK	OK	OK	B	Interior Zone 4
					OK	OK	OK	OK	OK	OK	OK	OK	NO	NO	C	
					OK	OK	OK	OK	OK	OK	OK	NO	NO	NO	D	
					OK	OK	OK	OK	OK	OK	OK	OK	OK	OK	B	End Zone 5
					OK	OK	OK	OK	OK	OK	NO	NO	NO	NO	C	
	D5	Nails: 16" o.c.	Studs	71	OK	OK	OK	OK	OK	OK	OK	OK	OK	OK	B	Interior Zone 4
					OK	OK	OK	OK	OK	OK	OK	OK	NO	NO	C	
					OK	OK	OK	OK	OK	OK	NO	NO	NO	NO	D	
					OK	OK	OK	OK	OK	OK	OK	NO	NO	NO	C	End Zone 5
					OK	OK	OK	OK	OK	NO	NO	NO	NO	NO	D	



8TH EDITION (2023) FLORIDA WIND ZONE COMPLIANCE WORKSHEET, Height (h) ≤ 30 ft

CERTAINTEED					Ultimate Design Wind Speed - Vult (mph) – FBC Figures 1609.3(1) through 1609.3(4)										Exposure	Zone
Product	Profile	Max. Fastener Spacing	Fastener Engage	Design Pressure (psf)	110	120	130	140	150	160	170	180	190	200		
Restoration Classic	D5	Staples: 16" o.c.	Studs	35	OK	OK	NO	NO	NO	NO	NO	NO	NO	NO	D	Interior
					OK	OK	OK	OK	NO	NO	NO	NO	NO	NO	B	End Zone 5
					OK	OK	NO	NO	NO	NO	NO	NO	NO	NO	C	
					OK	NO	NO	NO	NO	NO	NO	NO	NO	NO	D	
	D5	Nails: 24" o.c.	Studs	48	OK	OK	OK	OK	OK	OK	OK	OK	NO	NO	B	Interior Zone 4
					OK	OK	OK	OK	OK	NO	NO	NO	NO	NO	C	
					OK	OK	OK	OK	NO	NO	NO	NO	NO	NO	D	
					OK	OK	OK	OK	OK	OK	NO	NO	NO	NO	B	
	T3	Nails: 16" o.c.	Studs	78	OK	OK	OK	OK	NO	NO	NO	NO	NO	NO	C	End Zone 5
					OK	OK	OK	OK	NO	NO	NO	NO	NO	NO	D	
					OK	OK	OK	OK	OK	OK	OK	OK	NO	NO	B	
					OK	OK	OK	OK	OK	OK	OK	OK	NO	NO	C	
Vinyl Carpentry Beaded Vertical	T2	Nails: 12" o.c.	Sheathing	58	OK	OK	OK	OK	OK	OK	OK	OK	OK	NO	B	Interior Zone 4
					OK	OK	OK	OK	OK	OK	NO	NO	NO	NO	C	
					OK	OK	OK	OK	OK	NO	NO	NO	NO	NO	D	
					OK	OK	OK	OK	OK	OK	OK	NO	NO	NO	B	
					OK	OK	OK	OK	NO	NO	NO	NO	NO	NO	C	
					OK	OK	OK	NO	NO	NO	NO	NO	NO	NO	D	
Vinyl Carpentry IronMax Vertical	D5	Nails: 12" o.c.	Sheathing	40	OK	OK	OK	OK	OK	OK	OK	OK	OK	OK	B	Interior Zone 4
					OK	OK	OK	OK	OK	OK	OK	NO	NO	NO	C	
					OK	OK	OK	OK	OK	NO	NO	NO	NO	NO	D	
					OK	OK	OK	OK	OK	OK	OK	OK	NO	NO	B	
					OK	OK	OK	OK	NO	NO	NO	NO	NO	NO	C	
					OK	OK	OK	OK	NO	NO	NO	NO	NO	NO	D	
Vinyl Carpentry Triple 3-1/3" Vertical	T3-1/3	Nails: 12" o.c.	Sheathing	42	OK	OK	OK	OK	OK	OK	NO	NO	NO	NO	B	Interior Zone 4
					OK	OK	OK	OK	NO	NO	NO	NO	NO	NO	C	
					OK	OK	OK	NO	NO	NO	NO	NO	NO	NO	D	
					OK	OK	OK	OK	OK	NO	NO	NO	NO	NO	B	
					OK	OK	NO	NO	NO	NO	NO	NO	NO	NO	C	
					OK	NO	NO	NO	NO	NO	NO	NO	NO	NO	D	
Vinyl Carpentry Universal Vertical	T4	Nails: 12" o.c.	Sheathing	40	OK	OK	OK	OK	OK	NO	NO	NO	NO	NO	B	Interior Zone 4
					OK	OK	OK	NO	NO	NO	NO	NO	NO	NO	C	
					OK	OK	NO	NO	NO	NO	NO	NO	NO	NO	D	
					OK	OK	OK	OK	NO	NO	NO	NO	NO	NO	B	
					OK	NO	NO	NO	NO	NO	NO	NO	NO	NO	C	
					NO	NO	NO	NO	NO	NO	NO	NO	NO	NO	D	



8TH EDITION (2023) FLORIDA WIND ZONE COMPLIANCE WORKSHEET, Height (h) ≤ 30 ft

VYTEC					Ultimate Design Wind Speed - Vult (mph) – FBC Figures 1609.3(1) through 1609.3(4)										Exposure	Zone
Product	Profile	Max. Fastener Spacing	Fastener Engage	Design Pressure (psf)	110	120	130	140	150	160	170	180	190	200		
Board & Batten Single 7 Vertical Siding	S7	Nails: 12" o.c.	OSB, plywood and/or studs	80	OK	OK	OK	OK	OK	OK	OK	OK	OK	OK	B	Interior Zone 4
					OK	OK	OK	OK	OK	OK	OK	OK	OK	OK	C	
					OK	OK	OK	OK	OK	OK	OK	OK	OK	OK	D	End Zone 5
					OK	OK	OK	OK	OK	OK	OK	OK	OK	OK	B	
					OK	OK	OK	OK	OK	OK	OK	OK	OK	NO	C	
Nantucket	D4	Nails: 16" o.c.	Studs	51	OK	OK	OK	OK	OK	OK	OK	OK	OK	NO	B	Interior Zone 4
					OK	OK	OK	OK	OK	OK	NO	NO	NO	NO	C	
					OK	OK	OK	OK	NO	NO	NO	NO	NO	NO	D	End Zone 5
					OK	OK	OK	OK	OK	OK	NO	NO	NO	NO	B	
					OK	OK	OK	OK	NO	NO	NO	NO	NO	NO	C	
	D4.5DL	Nails: 16" o.c.	Studs	40	OK	OK	OK	OK	OK	OK	OK	NO	NO	NO	B	Interior Zone 4
					OK	OK	OK	OK	NO	NO	NO	NO	NO	NO	C	
					OK	OK	OK	OK	OK	NO	NO	NO	NO	NO	D	End Zone 5
					OK	OK	OK	OK	NO	NO	NO	NO	NO	NO	B	
					OK	OK	OK	NO	NO	NO	NO	NO	NO	NO	C	
Prestige	D4.5	Nails: 16" o.c.	Studs	82	OK	OK	OK	OK	OK	OK	OK	OK	OK	OK	B	Interior Zone 4
					OK	OK	OK	OK	OK	OK	OK	OK	OK	OK	C	
					OK	OK	OK	OK	OK	OK	OK	OK	NO	NO	D	End Zone 5
					OK	OK	OK	OK	OK	OK	OK	OK	OK	OK	B	
					OK	OK	OK	OK	OK	OK	OK	OK	NO	NO	C	
	D4.5DL	Nails: 16" o.c.	Studs	91	OK	OK	OK	OK	OK	OK	OK	OK	OK	OK	B	Interior Zone 4
					OK	OK	OK	OK	OK	OK	OK	OK	OK	OK	C	
					OK	OK	OK	OK	OK	OK	OK	OK	OK	NO	D	End Zone 5
					OK	OK	OK	OK	OK	OK	OK	OK	OK	OK	B	
					OK	OK	OK	OK	OK	OK	OK	OK	NO	NO	C	
	D5DL	Nails: 16" o.c.	Studs	78	OK	OK	OK	OK	OK	OK	OK	OK	OK	OK	B	Interior Zone 4
					OK	OK	OK	OK	OK	OK	OK	OK	OK	OK	C	
					OK	OK	OK	OK	OK	OK	OK	OK	NO	NO	D	End Zone 5
					OK	OK	OK	OK	OK	OK	OK	OK	OK	OK	B	
					OK	OK	OK	OK	OK	OK	OK	OK	NO	NO	C	
Prosidge LG	D4	Nails: 16" o.c.	Studs	35	OK	OK	OK	OK	OK	OK	NO	NO	NO	NO	B	Interior Zone 4
					OK	OK	OK	NO	NO	NO	NO	NO	NO	NO	C	
					OK	OK	NO	NO	NO	NO	NO	NO	NO	NO	D	End Zone 5
					OK	OK	OK	OK	NO	NO	NO	NO	NO	NO	B	
					OK	OK	NO	NO	NO	NO	NO	NO	NO	NO	C	
	D4.5	Nails: 16" o.c.	Studs	51	OK	OK	OK	OK	OK	OK	OK	OK	OK	NO	B	Interior Zone 4
					OK	OK	OK	OK	OK	OK	NO	NO	NO	NO	C	
					OK	OK	OK	OK	NO	NO	NO	NO	NO	NO	D	End Zone 5
					OK	OK	OK	OK	OK	OK	NO	NO	NO	NO	B	
					OK	OK	OK	OK	NO	NO	NO	NO	NO	NO	C	



8TH EDITION (2023) FLORIDA WIND ZONE COMPLIANCE WORKSHEET, Height (h) ≤ 30 ft

WOLVERINE					Ultimate Design Wind Speed - Vult (mph) – FBC Figures 1609.3(1) through 1609.3(4)										Exposure	Zone
Product	Profile	Max. Fastener Spacing	Fastener Engage	Design Pressure (psf)	110	120	130	140	150	160	170	180	190	200		
Wolverine American Legend	D4	Nails: 16" o.c.	Studs	52	OK	OK	OK	OK	OK	OK	OK	OK	OK	NO	B	Interior Zone 4
					OK	OK	OK	OK	OK	OK	NO	NO	NO	NO	C	
					OK	OK	OK	OK	OK	NO	NO	NO	NO	NO	D	
					OK	OK	OK	OK	OK	OK	OK	NO	NO	NO	B	End Zone 5
					OK	OK	OK	OK	NO	NO	NO	NO	NO	NO	C	
					OK	OK	OK	NO	NO	NO	NO	NO	NO	NO	D	
	D4	Staples: 16" o.c.	Studs	58	OK	OK	OK	OK	OK	OK	OK	OK	OK	OK	B	Interior Zone 4
					OK	OK	OK	OK	OK	OK	OK	NO	NO	NO	C	
					OK	OK	OK	OK	OK	NO	NO	NO	NO	NO	D	
					OK	OK	OK	OK	OK	OK	OK	OK	NO	NO	B	End Zone 5
					OK	OK	OK	OK	NO	NO	NO	NO	NO	NO	C	
					OK	OK	OK	NO	NO	NO	NO	NO	NO	NO	D	
	D4	Nails: 24" o.c.	Studs	36	OK	OK	OK	OK	OK	OK	NO	NO	NO	NO	B	Interior Zone 4
					OK	OK	OK	NO	NO	NO	NO	NO	NO	NO	C	
					OK	OK	NO	NO	NO	NO	NO	NO	NO	NO	D	
					OK	OK	OK	OK	NO	NO	NO	NO	NO	NO	B	End Zone 5
					OK	OK	NO	NO	NO	NO	NO	NO	NO	NO	C	
					OK	NO	NO	NO	NO	NO	NO	NO	NO	NO	D	
	D4.5DL	Nails: 16" o.c.	Studs	56	OK	OK	OK	OK	OK	OK	OK	OK	OK	OK	B	Interior Zone 4
					OK	OK	OK	OK	OK	OK	NO	NO	NO	NO	C	
					OK	OK	OK	OK	OK	NO	NO	NO	NO	NO	D	
					OK	OK	OK	OK	OK	OK	OK	OK	NO	NO	B	End Zone 5
					OK	OK	OK	OK	OK	NO	NO	NO	NO	NO	C	
					OK	OK	OK	NO	NO	NO	NO	NO	NO	NO	D	
	D5	Nails: 16" o.c.	Studs	40	OK	OK	OK	OK	OK	OK	OK	OK	NO	NO	B	Interior Zone 4
					OK	OK	OK	OK	NO	NO	NO	NO	NO	NO	C	
					OK	OK	OK	NO	NO	NO	NO	NO	NO	NO	D	
					OK	OK	OK	OK	OK	NO	NO	NO	NO	NO	B	End Zone 5
					OK	OK	NO	NO	NO	NO	NO	NO	NO	NO	C	
					OK	NO	NO	NO	NO	NO	NO	NO	NO	NO	D	
	D5	Staples: 16" o.c.	Studs	33	OK	OK	OK	OK	OK	NO	NO	NO	NO	NO	B	Interior Zone 4
					OK	OK	OK	NO	NO	NO	NO	NO	NO	NO	C	
					OK	OK	NO	NO	NO	NO	NO	NO	NO	NO	D	
					OK	OK	OK	OK	NO	NO	NO	NO	NO	NO	B	End Zone 5
					OK	NO	NO	NO	NO	NO	NO	NO	NO	NO	C	
					NO	NO	NO	NO	NO	NO	NO	NO	NO	NO	D	