



9TH EDITION (2026) FLORIDA WIND ZONE COMPLIANCE WORKSHEET, Height (h) < 30 ft

SOFFIT							Wind Speed - V _{ult} (mph) 3-second gust										Exposure	Zone	
Product	Substrate	Span (inch)	Wall Side Nailing	Center Nailing	Eave Side Nailing	Allowable Pressure (psf)	110	120	130	140	150	160	170	180	190	200			
Vinyl Carpentry Beaded Soffit (T2)	open studs	16	6" o.c.	N/A	6" o.c.	59	OK	OK	OK	OK	OK	OK	OK	OK	OK	OK	B	Interior Zone 4	
							OK	OK	OK	OK	OK	OK	OK	OK	NO	NO	C		
							OK	OK	OK	OK	OK	OK	OK	NO	NO	NO	D		
							OK	OK	OK	OK	OK	OK	OK	OK	OK	OK	OK	B	End Zone 5
							OK	OK	OK	OK	OK	OK	OK	OK	NO	NO	NO	C	
							OK	OK	OK	OK	OK	NO	NO	NO	NO	NO	D		
		24	6" o.c.	6" o.c.	62	OK	OK	OK	OK	OK	OK	OK	OK	OK	OK	OK	B	Interior Zone 4	
						OK	OK	OK	OK	OK	OK	OK	OK	OK	OK	NO	C		
						OK	OK	OK	OK	OK	OK	OK	NO	NO	NO	D			
						OK	OK	OK	OK	OK	OK	OK	OK	OK	OK	OK	B	End Zone 5	
						OK	OK	OK	OK	OK	OK	OK	OK	NO	NO	NO	C		
						OK	OK	OK	OK	OK	OK	NO	NO	NO	NO	D			
Vinyl Carpentry Ironmax Premium Soffit (D5)	open studs	16	10" o.c.	N/A	10" o.c.	38	OK	OK	OK	OK	OK	OK	OK	OK	NO	NO	B	Interior Zone 4	
							OK	OK	OK	OK	OK	NO	NO	NO	NO	NO	C		
							OK	OK	OK	NO	NO	NO	NO	NO	NO	NO	D		
							OK	OK	OK	OK	OK	OK	OK	NO	NO	NO	NO	B	End Zone 5
							OK	OK	OK	NO	NO	NO	NO	NO	NO	NO	C		
							OK	OK	NO	NO	NO	NO	NO	NO	NO	NO	D		
		24	10" o.c.	10" o.c.	10" o.c.	51	OK	OK	OK	OK	OK	OK	OK	OK	OK	OK	B	Interior Zone 4	
							OK	OK	OK	OK	OK	OK	OK	NO	NO	NO	C		
							OK	OK	OK	OK	OK	OK	NO	NO	NO	NO	D		
							OK	OK	OK	OK	OK	OK	OK	OK	NO	NO	NO	B	End Zone 5
							OK	OK	OK	OK	OK	NO	NO	NO	NO	NO	C		
							OK	OK	OK	OK	NO	NO	NO	NO	NO	NO	D		
Vinyl Carpentry Perimeter Triple 3-1/3 Soffit (T3-1/3)	sheathed	12	10" o.c.	N/A	10" o.c.	37	OK	OK	OK	OK	OK	OK	OK	NO	NO	NO	B	Interior Zone 4	
							OK	OK	OK	NO	NO	NO	NO	NO	NO	NO	C		
							OK	OK	OK	OK	OK	OK	NO	NO	NO	NO	D		
							OK	OK	OK	NO	NO	NO	NO	NO	NO	NO	B	End Zone 5	
							OK	OK	OK	NO	NO	NO	NO	NO	NO	NO	C		
							OK	OK	OK	NO	NO	NO	NO	NO	NO	NO	D		
	open studs	24	10" o.c.	10" o.c.	10" o.c.	44	OK	OK	OK	OK	OK	OK	OK	OK	OK	NO	B	Interior Zone 4	
							OK	OK	OK	OK	OK	OK	NO	NO	NO	NO	C		
							OK	OK	OK	OK	OK	OK	NO	NO	NO	NO	D		
							OK	OK	OK	OK	OK	OK	OK	NO	NO	NO	NO	B	End Zone 5
							OK	OK	OK	OK	NO	NO	NO	NO	NO	NO	C		
							OK	OK	OK	NO	NO	NO	NO	NO	NO	NO	D		
Vinyl Carpentry Triple 3-1/3 Soffit (T3-1/3)	open studs	16	10" o.c.	N/A	10" o.c.	46	OK	OK	OK	OK	OK	OK	OK	OK	OK	NO	B	Interior Zone 4	
							OK	OK	OK	OK	OK	OK	NO	NO	NO	NO	C		
							OK	OK	OK	OK	OK	OK	OK	NO	NO	NO	D		
							OK	OK	OK	OK	OK	OK	OK	OK	NO	NO	NO	B	End Zone 5
							OK	OK	OK	OK	OK	NO	NO	NO	NO	NO	C		
							OK	OK	OK	NO	NO	NO	NO	NO	NO	NO	D		
		24	10" o.c.	10" o.c.	10" o.c.	76	OK	OK	OK	OK	OK	OK	OK	OK	OK	OK	B	Interior Zone 4	
							OK	OK	OK	OK	OK	OK	OK	OK	OK	OK	C		
							OK	OK	OK	OK	OK	OK	OK	OK	OK	NO	D		
							OK	OK	OK	OK	OK	OK	OK	OK	OK	OK	B	End Zone 5	
							OK	OK	OK	OK	OK	OK	OK	OK	OK	NO	C		
							OK	OK	OK	OK	OK	OK	OK	NO	NO	NO	D		



9TH EDITION (2026) FLORIDA WIND ZONE COMPLIANCE WORKSHEET, Height (h) < 30 ft

SOFFIT							Wind Speed - V _{ult} (mph) 3-second gust										Exposure	Zone
Product	Substrate	Span (inch)	Wall Side Nailing	Center Nailing	Eave Side Nailing	Allowable Pressure (psf)	110	120	130	140	150	160	170	180	190	200		
Vinyl Carpentry Universal Soffit (T4)	open studs	16	12" o.c.	N/A	12" o.c.	32	OK	OK	OK	OK	OK	OK	NO	NO	NO	NO	B	Interior Zone 4
							OK	OK	OK	NO	NO	NO	NO	NO	NO	NO	C	
							OK	OK	NO	NO	NO	NO	NO	NO	NO	NO	D	
							OK	OK	OK	OK	NO	NO	NO	NO	NO	NO	B	End Zone 5
							OK	OK	NO	NO	NO	NO	NO	NO	NO	NO	C	
							OK	NO	NO	NO	NO	NO	NO	NO	NO	NO	D	
		24	12" o.c.	12" o.c.	12" o.c.	50	OK	OK	OK	OK	OK	OK	OK	OK	OK	OK	B	Interior Zone 4
							OK	OK	OK	OK	OK	OK	OK	NO	NO	NO	C	
							OK	OK	OK	OK	OK	OK	NO	NO	NO	NO	D	
							OK	OK	OK	OK	OK	OK	OK	NO	NO	NO	B	End Zone 5
							OK	OK	OK	OK	OK	NO	NO	NO	NO	NO	C	
							OK	OK	OK	OK	NO	NO	NO	NO	NO	NO	D	
Vinyl Carpentry Universal Soffit (D5)	open studs	8	8" o.c.	N/A	8" o.c.	48	OK	OK	OK	OK	OK	OK	OK	OK	OK	OK	B	Interior Zone 4
							OK	OK	OK	OK	OK	OK	OK	NO	NO	NO	C	
							OK	OK	OK	OK	OK	NO	NO	NO	NO	NO	D	
							OK	OK	OK	OK	OK	OK	OK	OK	NO	NO	B	End Zone 5
							OK	OK	OK	OK	NO	NO	NO	NO	NO	NO	C	
							OK	OK	OK	OK	NO	NO	NO	NO	NO	NO	D	
		16	16" o.c.	N/A	16" o.c.	33	OK	OK	OK	OK	OK	OK	NO	NO	NO	NO	B	Interior Zone 4
							OK	OK	OK	OK	NO	NO	NO	NO	NO	NO	C	
							OK	OK	OK	OK	NO	NO	NO	NO	NO	NO	D	
							OK	OK	OK	OK	OK	NO	NO	NO	NO	NO	B	End Zone 5
							OK	OK	NO	NO	NO	NO	NO	NO	NO	NO	C	
							OK	NO	NO	NO	NO	NO	NO	NO	NO	NO	D	



9TH EDITION (2026) FLORIDA WIND ZONE COMPLIANCE WORKSHEET, Height (h) < 30 ft

SOFFIT							Wind Speed - V _{ult} (mph) 3-second gust										Exposure	Zone
Product	Substrate	Span (inch)	Wall Side Nailing	Center Nailing	Eave Side Nailing	Allowable Pressure (psf)	110	120	130	140	150	160	170	180	190	200		
Wolverine Beaded Porch Panel (T2)	open studs	16	6" o.c.	N/A	6" o.c.	59	OK	OK	OK	OK	OK	OK	OK	OK	OK	OK	B	Interior Zone 4
							OK	OK	OK	OK	OK	OK	OK	OK	NO	NO	C	
							OK	OK	OK	OK	OK	OK	OK	NO	NO	NO	D	
							OK	OK	OK	OK	OK	OK	OK	OK	OK	OK	B	
		24	6" o.c.	6" o.c.	6" o.c.	62	OK	OK	OK	OK	OK	OK	OK	NO	NO	NO	C	End Zone 5
							OK	OK	OK	OK	OK	NO	NO	NO	NO	NO	D	
							OK	OK	OK	OK	OK	OK	OK	OK	OK	OK	B	
							OK	OK	OK	OK	OK	OK	OK	OK	OK	NO	C	
	sheathed	12	10" o.c.	N/A	10" o.c.	37	OK	OK	OK	OK	OK	OK	OK	NO	NO	NO	D	Interior Zone 4
							OK	OK	OK	OK	OK	NO	NO	NO	NO	NO	C	
							OK	OK	OK	OK	OK	NO	NO	NO	NO	NO	D	
							OK	OK	OK	OK	OK	OK	NO	NO	NO	NO	B	
							OK	OK	OK	OK	OK	NO	NO	NO	NO	NO	C	
							OK	OK	NO	NO	NO	NO	NO	NO	NO	NO	D	
Wolverine Triple 3-1/3 Soffit (T3-1/3)	open studs	24	10" o.c.	10" o.c.	10" o.c.	44	OK	OK	OK	OK	OK	OK	OK	OK	OK	NO	B	Interior Zone 4
							OK	OK	OK	OK	OK	NO	NO	NO	NO	NO	C	
							OK	OK	OK	OK	OK	NO	NO	NO	NO	NO	D	
							OK	OK	OK	OK	OK	OK	NO	NO	NO	NO	B	
							OK	OK	OK	OK	NO	NO	NO	NO	NO	NO	C	
							OK	OK	NO	NO	NO	NO	NO	NO	NO	NO	D	
							OK	OK	OK	OK	OK	OK	OK	OK	OK	OK	B	
							OK	OK	OK	OK	OK	NO	NO	NO	NO	NO	C	
	open studs	8	8" o.c.	N/A	8" o.c.	48	OK	OK	OK	OK	OK	OK	OK	NO	NO	NO	D	Interior Zone 4
							OK	OK	OK	OK	OK	NO	NO	NO	NO	NO	C	
							OK	OK	OK	OK	OK	OK	OK	OK	OK	OK	B	
							OK	OK	OK	OK	OK	NO	NO	NO	NO	NO	C	
							OK	OK	OK	OK	NO	NO	NO	NO	NO	NO	D	
							OK	OK	OK	OK	OK	OK	OK	OK	OK	OK	B	
Wolverine Double 5" Soffit (D5)	open studs	16	16" o.c.	N/A	16" o.c.	33	OK	OK	OK	OK	OK	OK	OK	NO	NO	NO	C	Interior Zone 4
							OK	OK	OK	OK	OK	NO	NO	NO	NO	NO	D	
							OK	OK	OK	OK	OK	NO	NO	NO	NO	NO	B	
							OK	OK	OK	OK	OK	NO	NO	NO	NO	NO	C	
							OK	OK	NO	NO	NO	NO	NO	NO	NO	NO	D	
		8	8" o.c.	N/A	8" o.c.	48	OK	OK	OK	OK	OK	OK	OK	NO	NO	NO	C	End Zone 5
							OK	OK	OK	OK	OK	NO	NO	NO	NO	NO	D	
							OK	OK	OK	OK	OK	OK	OK	OK	OK	OK	B	
							OK	OK	OK	OK	OK	NO	NO	NO	NO	NO	C	
							OK	OK	NO	NO	NO	NO	NO	NO	NO	NO	D	