







DETAIL A




LOW HEADROOM
TOP BRACKET




DETAIL B




DETAIL C




DETAIL D




DETAIL E




DETAIL F



DETAIL G




RESIDENTIAL & LIGHT
COMMERCIAL
For Low Headroom
With 2" Track and
Single End Stiles




COMMERCIAL
For Standard, High
& Vertical Lift
With 2" Track and
Single End Stiles

COMMERCIAL
For Standard, High
& Vertical Lift
With 3" Track and
Single End Stiles




DETAIL K

There should be a
space of maximum
1/2" between the roller
hub and the outside
edge of the roller
holder which is set by
the push nut.



ROLLER

2" Diameter Nominal
Eleven Ball Nylon or
Ten Ball Steel with
a Minimum Workable
Shaft Length Shown.




DETAIL H

NOTE: Details on some views omitted for clarity.
Double end stiles and end hardware may be
provided on wider or heavier doors.

FLAG BRACKET


BOLT
5/16 X 1 5/8" Lag Bolt
(4 per Flag Bracket).

BOLT & NUT
1/4-20 X 5/8" Track Bolt
& 1/4-20 Hex Washer Nut
(2 for Horizontal & 2 for
Vertical Track)




John E. Scates, P.E.
8811 Teel Pkwy #100-5175
Frisco, Texas 75036
Florida P.E. 51737
Texas P.E. 56308/F-2203

Printed copies of this document are not
considered signed and sealed and the signature
must be verified on any electronic copies.




COMMERCIAL HEAVY DUTY
For Standard, High &
Vertical Lift With 3" Track
and Double End Stiles



COMMERCIAL HEAVY DUTY
For Low Headroom With
3" Track and Double
End Stiles


ALTERNATE BOTTOM BRACKETS

NOTE: The bottom bracket tested (shown in DETAIL C) is the lightest bracket
available.




IMPACT RESISTANT

FL #16650.20




DESCRIPTION: 16' 2" PAN 2000 SERIES WIND LOAD SECTIONAL DOOR DESIGN PRESSURE +31.3/-34.9 PSF			
DRAWING NO.: WL-2000-0194-31-35	REV. L		
DRAWN BY: MVS	DATE DRAWN: 4/17/14	REV. DATE: 10/2/25	
MODEL(S): See Sheet 3			SHEET: 2 OF 4



MODEL NUMBERS

MODEL NUMBERS AVAILABLE
PAN C2011 SERIES
PAN C2015 SERIES
PAN C2411 SERIES
PAN C2415 SERIES
PAN C2511 SERIES
PAN C2410 & R2410 SERIES
PAN C2460 & R2460 SERIES
PAN C2461 & R2461 SERIES
PAN C2471 & R2471 SERIES
PAN C2472 & R2472 SERIES
PAN C2480 & R2480 SERIES
PAN C2481 & R2481 SERIES
PAN C2482 & R2482 SERIES
PAN R2560 SERIES
PAN R2561 SERIES
PAN R2571 SERIES
PAN R2572 SERIES
PAN R2580 SERIES
PAN R2581 SERIES
PAN R2582 SERIES




John E Scates, P.E.
8811 Teel Pkwy #100-5175
Frisco, Texas 75036
Florida P.E. 51737
Texas P.E. 56308/F-2203

Printed copies of this document are not considered signed and sealed and the signature must be verified on any electronic copies.

IMPACT RESISTANT

FL #16650.20



	DESCRIPTION: 16' 2" PAN 2000 SERIES WIND LOAD SECTIONAL DOOR DESIGN PRESSURE +31.3/-34.9 PSF		
	DRAWING NO.: WL-2000-0194-31-35	REV. L	
	DRAWN BY: MVS	DATE DRAWN: 4/17/14	REV. DATE: 10/2/25
	MODEL(S): See Sheet 3		SHEET: 3 OF 4



Direct Mounting Detail
Bracket Mount Shown, Reverse and Continuous Angle Mount, Reverse and Continuous Angle Clip Mount Also Approved As Alternate.

DIRECT MOUNTING					
Building Substrate	Fastener Type	Minimum Embedment	Minimum Fastener Length	Minimum Edge Distance	Minimum on Center Spacing
Southern Pine (SYP)	5/16" Dia. Lag Screw w/1-1/8" OD Flat Washer (shall conform to ANSI/ASME standard B18.2.1)	-	1-5/8"	1/2"	-
Spruce-Pine-Fur (SPF)	5/16" Dia. Lag Screw w/1-1/8" OD Flat Washer (shall conform to ANSI/ASME standard B18.2.1)	-	2-1/4"	1/2"	-
Min. 2500 PSI Concrete	3/8" Dia. Ankr-Tite CCAT w/1-1/8" OD Flat Washer (by Wej-It Fastening Systems)	2-3/8"	-	2-1/2"	6"
Min. 2500 PSI Concrete	1/4" Dia. Tapcon+ by ITW w/1-1/8" OD Flat Washer	2"	-	2-1/2"	5"
Min. 2500 PSI Concrete	1/4" Dia. Wedge-Bolt+ by Powers Fasteners w/1-1/8" OD Flat Washer	1-3/4"	-	2-1/2"	5"
Min. 2500 PSI Concrete	1/4" Dia. Red Head TruBolt wedge anchor by ITW w/1-1/8" OD Flat Washer	1-3/4"	-	2-1/2"	5"
1/8" GA Steel Minimum	5/16"-12 Tek Self-Drilling Screw w/1-1/8" OD Flat Washer	-	1"	-	-
3/16" GA Steel	Fillet Weld	See DASMA Technical Data Sheet TDS-161, section G			

NOTE: Doors are available with jamb brackets or commercial full angle. In either case the the maximum spacing noted on sheet 1 should be maintained for the brackets, clips and fasteners for direct mount.



John E. Scates, P.E.
8811 Teel Pkwy #100-5175
Frisco, Texas 75036
Florida P.E. 51737
Texas P.E. 56308/F-2203

Printed copies of this document are not considered signed and sealed and the signature must be verified on any electronic copies.

IMPACT RESISTANT

FL #16650.20

 320 Sycamore Wauseon, Ohio 43567 © Copyright 2014	DESCRIPTION: 16' 2" PAN 2000 SERIES WIND LOAD SECTIONAL DOOR DESIGN PRESSURE +31.3/-34.9 PSF		
	DRAWING NO.: WL-2000-0194-31-35		REV. L
	DRAWN BY: MVS	DATE DRAWN: 4/17/14	REV. DATE: 10/2/25
	MODEL(S): See Sheet 3		SHEET: 4 OF 4