



H3G2 Triple UnEqual Slider Op Window
107 1/2" x 59 1/2" Frame Size
Nail Fin Installation / Non-Impact

TEST REPORT SUMMARY:

- SINGLE UNIT, MAXIMUM BASIC UNIT FRAME SIZE:
107 1/2" (2731mm) x 59 1/2" (1511mm)
- OVERALL DESIGN PRESSURE: +50.13 / -55.14 psf
- RATING: LC-PG50
- STRUCTURAL TEST PRESSURE: +90.23 / -82.71 psf

CCL Listing# 436-H-682.02


ELEMENT, Test Report #: ESP020992P-1777

H3G2 Triple Slider Window Nail Fin Installation / WDMA
Instructions / Non-Impact

SHEET: 1 OF 2

EXPIRATION DATE: 9/25/2025

DRAWN BY: S.P.W.



INSTALLATION NOTES:

1. USE 2" x _ WOOD BUCK
2. 1/4" MAXIMUM SHIM SPACE AT HEAD, SILL, JAMBS, PLACE WOOD SHIMS EVERY 6-10"
3. APPLY A CONTINUOUS BEAD OF SEALANT BETWEEN THE NAIL FIN AND THE BUCK, ON ALL FOUR SIDES
4. INSTALL #8 X 1-1/4" PPH SCREWS SPACED 1-2" FROM EACH CORNER AND 6"-8" ON CENTER THEREAFTER THROUGH THE INTEGRAL NAIL FIN AND INTO THE FRAMING MATERIAL. ONE #10 X 2-1/2" PPH SS SCREW AT THE INACTIVE STILE LOCATIONS THROUGH THE HEAD AND SILL INTO THE BUCK
 - MINIMUM 3/8" EDGE DISTANCE
 - SILICONE SEAL OVER SCREW HEADS.
 - FULLY SEAL ALL GAPS AT EACH CORNER OF THE UNIT AND THE ROUGH OPENING
5. 1-1/8" MINIMUM FASTENER EMBEDMENT INTO FRAMING MATERIAL.
6. MAXIMUM BASIC UNIT FRAME SIZE: 107 1/2" (2731mm) x 59 1/2" (1511mm)
7. THIS INFORMATION DOES NOT APPLY TO MULLED UNITS

APPLIES TO LEFT OR RIGHT OPERATING WINDOW UNIT.

- Check rough opening for proper size, plumb, level and square.
- Make all necessary adjustments to ensure rough opening is plumb, level & square.
- Sill must be flat, level and capable of supporting the weight of the unit.
- Opening should allow a maximum of 1/4" shim space at head, sill and jambs.
- Wood buck, framing, fasteners, sealant and all wall system materials are provided by others.

Installation requirements may vary in particular locations and in other types of construction. Proper installation is essential, and Sierra Pacific Windows & Doors, recommends consultation with an AAMA Certified Installer, or other qualified, registered building professional before installation of any S.P.W. product. Proper installation of S.P.W. products is the responsibility of the installer. S.P.W. is not responsible for proper installation. S.P.W. is not responsible for the design of, conditions in, or performance of building construction beyond the perimeters of the S.P.W. units. S.P.W. is not responsible for proper integration of the S.P.W. units with the weather-repellent systems of the building.



H3G2 Triple UnEqual Slider Op Window
107 1/2" x 59 1/2" Frame Size
Nail Fin Installation / Non-Impact

CCL Listing# 436-H-682.02

ELEMENT, Test Report #: ESP020992P-1777

H3G2 Triple Slider Window Nail Fin Installation / WDMA
Instructions / Non-Impact

SHEET: 2 OF 2


EXPIRATION DATE: 9/25/2025

DRAWN BY: S.P.W.


TEST REPORT SUMMARY:

- SINGLE UNIT, MAXIMUM BASIC UNIT FRAME SIZE:
107 1/2" (2731mm) x 59 1/2" (1511mm)
- OVERALL DESIGN PRESSURE: +50.13 / -55.14 psf
- RATING: LC-PG50
- STRUCTURAL TEST PRESSURE: +90.23 / -82.71 psf

HEAD DETAIL




SILL DETAIL




MEETING RAIL DETAIL

HEAD DETAIL



SILL DETAIL



JAMB DETAIL