

# SERIES 4025A, NON-IMPACT RESISTANT SLIDING GLASS DOOR

1. GLAZING OPTIONS:
  1. 3/16" TEMPERED GLASS.
  2. 1/4" TEMPERED GLASS.
  3. 5/8" INSULATED GLASS (I.G.); (2) LITES OF 3/16" TEMPERED GLASS WITH A 1/4" AIR SPACE.
2. CONFIGURATIONS: SEE SHEET 3.
3. DESIGN PRESSURES: SEE TABLES 1-3 ON SHEET 2.
  - A. NEGATIVE DESIGN LOADS BASED ON TESTED PRESSURE AND GLASS TABLES ASTM E 1300.
  - B. POSITIVE DESIGN LOADS BASED ON WATER TEST PRESSURE AND GLASS TABLES ASTM E 1300.
  - C. DESIGN PRESSURES OF LESS THAN 40 PSF NOT APPLICABLE IN MIAMI-DADE COUNTY.
  - D. DESIGN LOADS ARE BASED ON ALLOWABLE STRESS DESIGN, ASD.
4. ANCHORAGE: THE ANCHORAGE METHODS SHOWN HAVE BEEN DESIGNED TO RESIST THE WINDLOADS CORRESPONDING TO THE REQUIRED DESIGN PRESSURE. THE 33-1/3% STRESS INCREASE HAS NOT BEEN USED IN THE DESIGN OF THIS PRODUCT. THE 1.6 LOAD DURATION FACTOR WAS USED FOR THE EVALUATION OF ANCHORS INTO WOOD. ANCHORS THAT COME INTO CONTACT WITH OTHER DISSIMILAR MATERIALS SHALL MEET THE REQUIREMENTS OF THE FLORIDA BUILDING CODE FOR CORROSION RESISTANCE.
5. MIAMI-DADE COUNTY APPROVED SHUTTERS ARE REQUIRED IN MIAMI-DADE COUNTY AND WHERE IMPACT RESISTANCE IS REQUIRED.
6. INSTALLATION SCREWS, FRAME AND PANEL CORNERS SEALED WITH NARROW JOINT SEALANT.
7. REFERENCES: TEST REPORTS FTL-3102, FTL-3116, FTL-3117, FTL-3596, FTL-4273, FTL-4275, FTL-4277, FTL-4278, FTL-4280, FTL-4285, FTL-4341, FTL-5095 AND FTL 18-8217.
  - >ELCO ULTRACON AND CRETEFLEX NOA'S
  - >ANSI/AF&PA NDS FOR WOOD CONSTRUCTION
  - >ALUMINUM DESIGN MANUAL
8. THIS PRODUCT HAS BEEN DESIGNED & TESTED TO COMPLY WITH THE REQUIREMENTS OF THE FLORIDA BUILDING CODE, INCLUDING THE HIGH VELOCITY HURRICANE ZONE (HVHZ).


GENERAL NOTES.....	1
GLAZING DETAILS.....	1
DESIGN PRESSURES.....	2
CONFIGURATIONS.....	3
ELEVATIONS.....	3
VERT. SECTIONS.....	4
HORIZ. SECTIONS.....	5-6
"X" & "O" CLIP INSTALL....	7
ANCHORAGE.....	8-9
EXTRUSIONS.....	10-11
PARTS LIST.....	12

TABLE 1A

Anchor Group	Anchor Type	Frame Member	Substrate	Min. Edge Distance	Min. O.C. Distance	Min. Embedment or Metal Thickness
A	1/4" 410 SS Elco CreteFlex®	Head / Sill	Southern Pine (SG = 0.55)	1"	1.687"	1-3/8"
		P-hook		1"	1"	1-3/8"
		Jamb		1"	1.594"	1-3/8"
	#12 Steel SMS (Gr. 5)	Head / Sill	Southern Pine (SG = 0.55) / 6063-T5 Aluminum	1"	1.687"	1-3/8" / 1/8"
		P-hook		1"	1"	1-3/8" / 1/8"
		Jamb		1"	1.594"	1-3/8" / 1/8"
B	1/4" Elco UltraCon®	Head / Sill	Concrete (min. 2.85 ksi)	1-3/4"	1.687"	1-3/4"
		P-hook	Concrete (min. 2.85 ksi)	1-1/4"	4"	1-3/8"
		Jamb	Hollow Block (ASTM C90)	2-1/2"	1.594"	1-1/4"
C	1/4" 410 SS Elco CreteFlex®	Head / Sill	Concrete (min. 3.35 ksi)	2-1/2"	1.687"	1-3/4"
		P-hook	Concrete (min. 3.35 ksi)	1-1/4"	3"	1-3/4"
		Jamb	Hollow Block (ASTM C90)	2-1/2"	1.594"	1-1/4"

- 1) ALL ANCHOR HEAD TYPES ARE APPLICABLE.
- 2) MIN. OF 3 THREADS BEYOND METAL SUBSTRATE.

DESIGN PRESSURE RATING	IMPACT RATING
SEE TABLES 1, 2 & 3 ON SHEET 2	NOT RATED FOR MISSILE IMPACT RESISTANCE



3/16" MONOLITHIC GLASS  
GLASS TYPE 1


1/4" MONOLITHIC GLASS  
GLASS TYPE 2

5/8" I.G. GLASS  
GLASS TYPE 3

Title: ALUMINUM SLIDING GLASS DOOR, NON-IMPACT		Drawn By: AGK			
Description: NOTES, GLAZING DETAILS & TABLE OF CONTENTS		Date: 4/12/19			
Revision: ORIGINAL ISSUE		Rev. By:	Rev. Date:	1070 TECHNOLOGY DRIVE N. VENICE, FL 34275 (941) 480-1600	
Series/Model: SGD-4025A	Scale: 9"=1'-0"	Sheet: 1 OF 12	Drawing No. SGD4025A		
				COPYRIGHT © 2019 PGT INDUSTRIES, INC. ALL RIGHTS RESERVED CERT. OF AUTH. #29296	
				A. LYNN MILLER, P.E. P.E.# 58705	


**COMPARATIVE ANALYSIS:** TABLE 1.  
 >EXTENDED SILL, 2 1/2" HIGH  
 >SINGLE/SINGLE INTERLOCK  
 >NO REINFORCEMENT (SEE SECTIONS ON SHEET 5)  
 GLASS TYPES:  
 1. 3/16" TEMPERED  
 2. 1/4" TEMPERED  
 3. 5/8" TEMPERED I.G. (3/16"T, 1/4"SPACE, 3/16"T)

NOM. PANEL WIDTH	GLASS	DOOR HEIGHT							
		80" (6 <sup>8</sup> )		84" (7 <sup>0</sup> )		90" (7 <sup>6</sup> )		96" (8 <sup>0</sup> )	
24" (2 <sup>0</sup> )	1,2	+65.0	-98.8	+65.0	-70.0	+64.6	-64.6	+60.0	-60.0
	3	+65.0	-107.1	+65.0	-80.0	+65.0	-73.8	+65.0	-68.6
30" (2 <sup>6</sup> )	1,2	+65.0	-82.7	+58.4	-58.4	+53.8	-53.8	+49.8	-49.8
	3	+65.0	-89.6	+65.0	-66.8	+61.4	-61.4	+56.9	-56.9
36" (3 <sup>0</sup> )	1,2	+65.0	-72.3	+50.9	-50.9	+46.7	-46.7	+43.1	-43.1
	3	+65.0	-78.3	+58.2	-58.2	+53.3	-53.3	+49.2	-49.2
42" (3 <sup>6</sup> )	1,2	+65.0	-65.1	+45.7	-45.7	+41.7	-41.7	+38.4	-38.4
	3	+65.0	-70.5	+52.2	-52.2	+47.7	-47.7	+43.9	-43.9
48" (4 <sup>0</sup> )	1,2	+60.0	-60.0	+42.0	-42.0	+38.2	-38.2	+35.0	-35.0
	3	+65.0	-65.0	+48.0	-48.0	+43.6	-43.6	+40.0	-40.0




**COMPARATIVE ANALYSIS:** TABLE 3.  
 >EXTENDED SILL, 2 1/2" HIGH  
 >SINGLE/DOUBLE INTERLOCK (OUTSIDE)  
 >FULL REINFORCEMENT (SEE SECTIONS ON SHEET 6)  
 GLASS TYPES:  
 2. 1/4" TEMPERED  
 3. 5/8" TEMPERED I.G. (3/16"T, 1/4"SPACE, 3/16"T)

NOM. PANEL WIDTH	GLASS	DOOR HEIGHT							
		80" (6 <sup>8</sup> )		84" (7 <sup>0</sup> )		90" (7 <sup>6</sup> )		96" (8 <sup>0</sup> )	
24" (2 <sup>0</sup> )	2	+65.0	-127.1	+65.0	-120.0	+65.0	-110.8	+65.0	-102.9
	3	+65.0	-130.0	+65.0	-130.0	+65.0	-120.0	+65.0	-111.4
30" (2 <sup>6</sup> )	2	+65.0	-106.3	+65.0	-100.2	+65.0	-92.2	+65.0	-85.3
	3	+65.0	-115.2	+65.0	-108.5	+65.0	-99.8	+65.0	-92.4
36" (3 <sup>0</sup> )	2	+65.0	-92.9	+65.0	-87.3	+65.0	-80.0	+65.0	-73.8
	3	+65.0	-100.6	+65.0	-94.5	+65.0	-86.7	+65.0	-80.0
42" (3 <sup>6</sup> )	2	+65.0	-78.4	+65.0	-78.4	+65.0	-71.6	+65.0	-65.8
	3	+65.0	-84.9	+65.0	-84.9	+65.0	-77.5	+65.0	-71.3
48" (4 <sup>0</sup> )	2	+60.0	-60.0	+60.0	-60.0	+60.0	-60.0	+60.0	-60.0
	3	+65.0	-65.0	+65.0	-65.0	+65.0	-65.0	+65.0	-65.0



**COMPARATIVE ANALYSIS:** TABLE 2.  
 >EXTENDED SILL, 2 1/2" HIGH  
 >SINGLE/SINGLE INTERLOCK  
 >FULL REINFORCEMENT (SEE SECTIONS ON SHEET 5)  
 GLASS TYPES:  
 1. 3/16" TEMPERED  
 2. 1/4" TEMPERED  
 3. 5/8" TEMPERED I.G. (3/16"T, 1/4"SPACE, 3/16"T)


NOM. PANEL WIDTH	GLASS	DOOR HEIGHT							
		80" (6 <sup>8</sup> )		84" (7 <sup>0</sup> )		90" (7 <sup>6</sup> )		96" (8 <sup>0</sup> )	
24" (2 <sup>0</sup> )	1,2,3	+65.0	-105.9	+65.0	-100.0	+65.0	-92.3	+65.0	-85.7
	1,2,3	+65.0	-88.6	+65.0	-83.5	+65.0	-76.8	+65.0	-71.1
30" (2 <sup>6</sup> )	1,2,3	+65.0	-77.4	+65.0	-72.7	+65.0	-66.7	+61.5	-61.5
	1,2,3	+65.0	-77.4	+65.0	-72.7	+65.0	-66.7	+61.5	-61.5
36" (3 <sup>0</sup> )	1,2,3	+65.0	-77.4	+65.0	-72.7	+65.0	-66.7	+61.5	-61.5
	1,2,3	+65.0	-77.4	+65.0	-72.7	+65.0	-66.7	+61.5	-61.5
42" (3 <sup>6</sup> )	1,2,3	+65.0	-65.3	+65.0	-65.3	+59.6	-59.6	+54.9	-54.9
	1,2,3	+65.0	-65.3	+65.0	-65.3	+59.6	-59.6	+54.9	-54.9
48" (4 <sup>0</sup> )	1,2,3	+50.0	-50.0	+50.0	-50.0	+50.0	-50.0	+50.0	-50.0
	1,2,3	+50.0	-50.0	+50.0	-50.0	+50.0	-50.0	+50.0	-50.0



SEE NOTES 1 & 2

SILL HEIGHT (IN.)	POS. DESIGN PRESS. (PSF)
2 1/2"	+65.0
1 3/4"	+35.3
INTERIOR SILL	SEE NOTE 2



FIG 1:



**NOTES:**


1. POSITIVE DESIGN PRESSURES SHOWN IN TABLES ARE BASED ON THE 2 1/2" HIGH SILL. POSITIVE DESIGN PRESSURE IS LIMITED TO 35.3 PSF WITH THE 1 3/4" SILL. NEGATIVE PRESSURES ARE UNCHANGED

2. INTERIOR SILL IS USED WHERE WATER RESISTANCE IS NOT REQUIRED OR OVERHANG IS PER FIG 1, IN WHICH CASE POSITIVE DESIGN PRESSURE EQUALS THE NEGATIVE DESIGN PRESSURE SHOWN IN TABLES 1 THROUGH 3 FOR THE RESPECTIVE SIZE.

Title: ALUMINUM SLIDING GLASS DOOR, NON-IMPACT		Drawn By: AGK			
Description: DESIGN PRESSURES		Date: 4/12/19			
Revision: ORIGINAL ISSUE		Rev. By: *	Rev. Date: *	1070 TECHNOLOGY DRIVE N. VENICE, FL 34275 (941) 480-1600	
Series/Model: SGD-4025A	Scale: 9"=1'-0"	Sheet: 2 OF 12	Drawing No. *	Rev: 0	COPYRIGHT © 2019 PGT INDUSTRIES, INC. ALL RIGHTS RESERVED CERT. OF AUTH. #29296
					A. LYNN MILLER, P.E. P.E.# 58705

CODE	PANEL TYPES	
A	R.H. INTERLOCK	LOCKSTILE
B	R.H. INTERLOCK	R.H. INTERLOCK
C	R.H. INTERLOCK	REVERSE ASTRAGAL
D	LOCKSTILE	R.H. INTERLOCK
E	L.H. INTERLOCK	R.H. INTERLOCK
F	L.H. INTERLOCK	L.H. INTERLOCK
G	LOCKSTILE	DOUBLE INTERLOCK
H	R.H. INTERLOCK	L.H. INTERLOCK
I	DOUBLE INTERLOCK	DOUBLE INTERLOCK
J	LOCKSTILE	STANDARD ASTRAGAL
K	L.H. INTERLOCK	LOCKSTILE
L	L.H. INTERLOCK	STANDARD ASTRAGAL
M	LOCKSTILE	L.H. INTERLOCK
N	STANDARD ASTRAGAL	L.H. INTERLOCK
P	R.H. INTERLOCK	FIXED LOCKSTILE

CODE	PANEL TYPES	
R	FIXED LOCKSTILE	L.H. INTERLOCK
S	FIXED LOCKSTILE	STANDARD ASTRAGAL
T	REVERSE ASTRAGAL	FIXED LOCKSTILE
U	REVERSE ASTRAGAL	LOCKSTILE
V	FIXED LOCKSTILE	FIXED LOCKSTILE
W	DOUBLE INTERLOCK	STANDARD ASTRAGAL
Y	FIXED LOCKSTILE	DOUBLE INTERLOCK
Z	LOCKSTILE	LOCKSTILE
YR	DOUBLE INTERLOCK	FIXED LOCKSTILE
GR	DOUBLE INTERLOCK	LOCKSTILE
LR	REVERSE ASTRAGAL	R.H. INTERLOCK
WR	STANDARD ASTRAGAL	DOUBLE INTERLOCK
DS	DOUBLE INTERLOCK	R.H. INTERLOCK
SD	L.H. INTERLOCK	DOUBLE INTERLOCK





**CONFIGURATION NOTES:**

1. MAXIMUM DAYLIGHT OPENING OF THE ADJACENT 48" NOMINAL WIDTH PANEL TYPES IS 44 3/16".
2. MAX. DLO HEIGHT = 91 1/4"
3. DOOR CONFIGURATIONS INCLUDE BY-PASS, POCKET AND ANY COMBINATION THEREOF (LIMITED TO EIGHT PANELS AND SEVEN TRACK FRAMES) FRAMES OVER 3-TRACKS ARE MADE UP OF THE APPROVED FRAME COMPONENTS SHOWN ON SHEET 9 OF THIS DOCUMENT.

**EXAMPLE MAXIMUM CONFIGURATIONS:**


- A. EIGHT PANELS ON FOUR TRACKS (CENTER MEET)
- B. FIVE PANELS ON FIVE TRACKS (BY-PASS)

TRACKS IN EXCESS OF THOSE REQUIRED FOR STRUCTURAL DOOR PANELS MAY BE USED FOR SCREENS.


Title: ALUMINUM SLIDING GLASS DOOR, NON-IMPACT		Drawn By: AGK			
Description: PANEL TYPES & EXAMPLE ELEVATIONS		Date: 4/12/19			
Revision: ORIGINAL ISSUE		Rev. By: *	Rev. Date: *	1070 TECHNOLOGY DRIVE N. VENICE, FL 34275 (941) 480-1600	
Series/Model: SGD-4025A	Scale: 1/4"=1'-0"	Sheet: 3 OF 12	Drawing No. *	Rev: 0	COPYRIGHT © 2019 PGT INDUSTRIES, INC. ALL RIGHTS RESERVED CERT. OF AUTH. #29296

A. LYNN MILLER, P.E. P.E.# 58705


DETAIL - B



DETAIL - D  
ANCHORAGE INTO WOOD



DETAIL - F







NOTES

- SEE TABLE 1A FOR ANCHOR TYPES, MINIMUM EDGE DISTANCES, MINIMUM EMBEDMENT, MINIMUM O.C. SPACING AND MINIMUM METAL THICKNESS.
- WOOD BUCKS DEPICTED IN THE SECTIONS ON THIS PAGE AS 1x ARE BUCKS WHOSE TOTAL THICKNESS IS LESS THAN 1 1/2". WOOD BUCKS DEPICTED AS 2x ARE 1 1/2" THICK OR GREATER. INSTALLATION TO THE SUBSTRATE OF WOOD BUCKS TO BE ENGINEERED BY OTHERS OR AS APPROVED BY AUTHORITY HAVING JURISDICTION. 1X WOOD BUCKS ARE OPTIONAL IF UNIT IS INSTALLED DIRECTLY TO SOLID CONCRETE OR CMU.
- FOR ATTACHMENT TO ALUMINUM: THE ALUMINUM STRUCTURAL MEMBER SHALL BE OF A SIZE TO PROVIDE FULL SUPPORT TO THE DOOR FRAME. SEE TABLE 1A FOR ADDITIONAL REQUIREMENTS
- IF SILL IS TIGHT TO SUBSTRATE, GROUT OR OTHER MATERIAL IS NOT REQUIRED. IF USED, NON-SHRINK, NON-METALLIC GROUT (3350 PSI MIN.), (DONE BY OTHERS) MUST FULLY SUPPORT THE ENTIRE LENGTH OF THE SILL THAT IS NOT TIGHT TO THE SUBSTRATE, AND TRANSFER SHEAR LOAD TO SUBSTRATE. IF SUBSTRATE IS WOOD, 30# FELT PAPER OR MASTIC IS REQUIRED BETWEEN THE GROUT AND WOOD SUBSTRATE, OR AS APPROVED BY THE AUTHORITY HAVING JURISDICTION.





DETAIL - C  
STANDARD SILL  
ANCHORAGE INTO WOOD

DETAIL - E  
EXTENDED SILL  
ANCHORAGE INTO CONCRETE



Title: ALUMINUM SLIDING GLASS DOOR, NON-IMPACT		Drawn By: AGK			
Description: VERTICAL SECTIONS WITH ANCHORAGE		Date: 4/12/19			
Revision: ORIGINAL ISSUE		Rev. By:	Rev. Date:	1070 TECHNOLOGY DRIVE N. VENICE, FL 34275 (941) 480-1600	
Series/Model: SGD-4025A	Scale: 6'-1'-0"	Sheet: 4 OF 12	Drawing No. SGD4025A	Rev: 0	COPYRIGHT © 2019 PGT INDUSTRIES, INC ALL RIGHTS RESERVED CERT. OF AUTH. #29296 A. LYNN MILLER, P.E. P.E.# 58705





**SINGLE/SINGLE INTERLOCK EXAMPLE FOR DESIGN PRESSURES:**  
 \*WITH REINFORCEMENT, SEE TABLE 2. WITHOUT REINFORCEMENT, SEE TABLE 1







**NOTES**  
 1. SEE TABLE 1A FOR ANCHOR TYPES, MINIMUM EDGE DISTANCES, MINIMUM EMBEDMENT, MINIMUM O.C. SPACING AND MINIMUM METAL THICKNESS.  
 2. WOOD BUCKS DEPICTED IN THE SECTIONS ON THIS PAGE AS 1x ARE BUCKS WHOSE TOTAL THICKNESS IS LESS THAN 1 1/2". WOOD BUCKS DEPICTED AS 2x ARE 1 1/2" THICK OR GREATER. INSTALLATION TO THE SUBSTRATE OF WOOD BUCKS TO BE ENGINEERED BY OTHERS OR AS APPROVED BY AUTHORITY HAVING JURISDICTION. 1X WOOD BUCKS ARE OPTIONAL IF UNIT IS INSTALLED DIRECTLY TO SOLID CONCRETE OR CMU.



Title: ALUMINUM SLIDING GLASS DOOR, NON-IMPACT		Drawn By: AGK		 1070 TECHNOLOGY DRIVE N. VENICE, FL 34275 (941) 480-1600	
Description: HORIZONTAL SECTIONS, TABLES 1-2		Date: 4/12/19			
Revision: ORIGINAL ISSUE		Rev. By:	Rev. Date:	COPYRIGHT © 2019 PGT INDUSTRIES, INC. ALL RIGHTS RESERVED CERT. OF AUTH. #29296	
Series/Model: SGD-4025A	Scale: 6"=1'-0"	Sheet: 5 OF 12	Drawing No. SGD4025A	Rev: 0	A. LYNN MILLER, P.E. P.E.# 58705



SINGLE/DOUBLE INTERLOCK EXAMPLE FULL REINFORCEMENT  
SEE TABLE 3 FOR DESIGN PRESSURES


NOTES  
SEE NOTES 1-3 ON SHEET 4



Title: ALUMINUM SLIDING GLASS DOOR, NON-IMPACT		Drawn By: AGK		 1070 TECHNOLOGY DRIVE N. VENICE, FL 34275 (941) 480-1600	
Description: HORIZONTAL SECTIONS, TABLE 3		Date: 4/12/19			
Revision: ORIGINAL ISSUE		Rev. By:	Rev. Date:	COPYRIGHT © 2019 PGT INDUSTRIES, INC. ALL RIGHTS RESERVED CERT. OF AUTH. #29296	
Series/Model: SGD-4025A	Scale: 6"=1'-0"	Sheet: 6 OF 12	Drawing No. SGD4025A	Rev: 0	A. LYNN MILLER, P.E. P.E.# 58705

(1) FIXED PANEL CLIP (TOP) INSTALLED ON EACH FIXED PANEL AT THE INTERLOCK POSITION TO ATTACH FIXED PANEL TO FRAME HEAD


(2) FIXED PANEL BRACKETS INSTALLED ON EACH FIXED PANEL TO ATTACH FIXED PANEL TO FRAME JAMB





(1) FIXED PANEL CLIP (BOTTOM) INSTALLED ON EACH FIXED PANEL AT THE INTERLOCK POSITION TO ATTACH FIXED PANEL TO FRAME SILL

FIXED PANELS


(1) TRACK CLIP ASSEMBLY INSTALLED ON EACH ACTIVE PANEL AT THE INTERCOCK POSITION TO SECURE THE ACTIVE PANEL TO IT'S RESPECTIVE SILL TRACK




OPERABLE PANELS

Title: ALUMINUM SLIDING GLASS DOOR, NON-IMPACT		Drawn By: AGK			
Description: TRACK & FIXED CLIPS INSTALLATION		Date: 4/12/19			
Revision: ORIGINAL ISSUE		Rev. By: *	Rev. Date: *	1070 TECHNOLOGY DRIVE N. VENICE, FL 34275 (941) 480-1600	
Series/Model: SGD-4025A	Scale: N.T.S.	Sheet: 7 OF 12	Drawing No. *	Rev: 0	COPYRIGHT © 2019 PGT INDUSTRIES, INC. ALL RIGHTS RESERVED CERT. OF AUTH. #29296
					A. LYNN MILLER, P.E. P.E.# 58705


MINIMUM ANCHOR QUANTITIES										TABLE 4.																	
DP TABLE REF. > GLASS TYPE >		TABLE 1. 1,2 OR 3			TABLE 2. 1,2 OR 3			TABLE 3. 2 OR 3																			
INTERLOCK & > REINFORCEMENT >		SSN (SEE NOTE 2)			SSR (SEE NOTE 2)			SDR (SEE NOTE 2)																			
ANCHOR GROUP		HEAD & SILL CLUSTER	JAMB		P-HOOK		HEAD & SILL CLUSTER	JAMB		P-HOOK																	
NOM. PANEL WIDTH x UNIT HT.	A	B	C	A	B	C	A	B	C	A	B	C															
24.000 x 80.000	C6	C6	C6	8	8	8	5	5	4	C6	C6	C6	8	8	8	4	5	4	C8	C8	C6	8	8	8	5	5	5
	C6	C6	C4	8	8	8	4	4	4	C6	C6	C6	8	8	8	4	5	4	C8	C8	C6	8	8	10	5	5	5
	C6	C6	C4	8	8	8	4	4	4	C6	C6	C6	8	8	8	4	5	4	C8	C8	C6	8	8	10	5	5	5
	C6	C6	C4	8	8	8	4	4	4	C6	C6	C6	8	8	8	4	5	4	C8	C8	C6	8	8	10	5	5	5
30.000 x 80.000	C6	C6	C6	8	8	8	5	5	4	C6	C6	C6	8	8	8	5	5	4	C8	C8	C6	8	10	10	6	6	5
	C6	C6	C4	8	8	8	4	4	4	C6	C6	C6	8	8	8	5	5	4	C8	C8	C6	8	10	10	6	6	5
	C6	C6	C4	8	8	8	4	4	4	C6	C6	C6	8	8	8	5	5	4	C8	C8	C6	8	10	10	6	6	5
	C6	C6	C4	8	8	8	4	4	4	C6	C6	C6	8	8	8	5	5	4	C8	C8	C6	8	10	10	6	6	5
36.000 x 80.000	C6	C6	C6	8	8	8	5	5	5	C6	C6	C6	8	8	8	5	5	5	C8	C8	C6	10	10	10	6	6	5
	C6	C6	C4	8	8	8	4	4	4	C6	C6	C6	8	8	8	5	5	5	C8	C8	C6	10	10	10	6	6	5
	C6	C6	C4	8	8	8	4	4	4	C6	C6	C6	8	8	8	5	5	5	C8	C8	C6	10	10	10	6	6	5
	C6	C6	C4	8	8	8	4	4	4	C6	C6	C6	8	8	8	5	5	4	C8	C8	C6	10	10	10	6	6	5
42.000 x 80.000	C6	C6	C4	8	8	8	5	5	5	C6	C6	C4	8	8	8	5	5	4	C6	C6	C6	10	10	10	6	6	5
	C4	C4	C4	8	8	8	4	4	4	C6	C6	C4	8	8	8	5	5	5	C6	C6	C6	10	10	10	6	6	6
	C4	C4	C4	8	8	8	4	4	4	C6	C6	C4	8	8	8	5	5	5	C6	C6	C6	10	10	10	6	6	6
	C4	C4	C4	8	8	8	4	4	4	C6	C6	C4	8	8	8	5	5	5	C6	C6	C6	10	10	10	6	6	6
48.000 x 80.000	C6	C6	C4	8	8	8	5	5	5	C4	C4	C4	8	8	8	4	4	4	C6	C6	C4	8	8	8	5	5	5
	C4	C4	C4	8	8	8	4	4	4	C4	C4	C4	8	8	8	4	5	4	C6	C6	C4	8	8	10	5	5	5
	C4	C4	C4	8	8	8	4	4	4	C6	C6	C4	8	8	8	5	5	5	C6	C6	C4	10	10	10	6	6	5
	C4	C4	C4	8	8	8	4	4	4	C6	C6	C4	8	8	8	5	5	5	C6	C6	C6	10	10	10	6	6	6



(4) ANCHOR CLUSTER - C4




(6) ANCHOR CLUSTER - C6




(8) ANCHOR CLUSTER - C8

NOTES:


- GLASS TYPES:  
1 - 3/16" TEMPERED  
2 - 1/4" TEMPERED  
3 - 5/8" TEMPERED I.G.
- TABLE ABBREVIATIONS:  
SSN - SINGLE/SINGLE WITH NO REINF. AT INTERLOCK & ASTRAGAL, (SHEET 5)  
SSR - SINGLE/SINGLE WITH FULL REINF. AT INTERLOCK & ASTRAGAL, (SHEET 5)  
SDR - SINGLE/DOUBLE WITH FULL REINF. AT INTERLOCK & ASTRAGAL, (SHEET 6)
- ANCHOR QUANTITIES BASED ON THE FOLLOWING SPACING:  
  
JAMBS AND P-HOOKS SPACING - 6" MAX. FROM CORNERS AND 28" MAX. O.C.  
  
HEAD AND SILL SPACING - 6" MAX. FROM CORNERS AND 22 5/16" MAX. O.C.
- INSTALL PER ANCHOR QUANTITIES OF TABLE 4, USING THE DIMENSIONAL CRITERIA OF NOTE 3. HEAD AND SILL CLUSTER ANCHORS ARE REQUIRED AT ASTRAGAL AND INTERLOCK LOCATIONS OF THEIR RESPECTIVE TRACK SECTIONS. SEE SHEET 9 FOR POTENTIAL ANCHOR LOCATIONS WITHIN HEAD, SILL AND JAMB TRACK SECTIONS.




Title: ALUMINUM SLIDING GLASS DOOR, NON-IMPACT		Drawn By: AGK		 ANTHONY LYNN MILLER LICENSE No. 58705 4/12/19 STATE OF FLORIDA PROFESSIONAL ENGINEER
Description: ANCHORAGE SPACING & QUANTITIES		Date: 4/12/19		
Revision: ORIGINAL ISSUE		Rev. By:	Rev. Date:	1070 TECHNOLOGY DRIVE N. VENICE, FL 34275 (941) 480-1600
Series/Model: SGD-4025A	Scale: 3"=1'-0"	Sheet: 8 OF 12	Drawing No. SGD4025A	Rev: 0
COPYRIGHT © 2019 PGT INDUSTRIES, INC. ALL RIGHTS RESERVED				CERT. OF AUTH. #29296
A. LYNN MILLER, P.E. P.E.# 58705				




ANCHOR LOCATION, TYP.



HEAD/SILL EXTERIOR




JAMB INTERIOR



JAMB EXTERIOR


HEAD/SILL INTERIOR

(5 - TRACK HEAD & SILL SHOWN)



EXAMPLE MULTI-PART EXTERIOR FRAME



(5 - TRACK HEAD & SILL SHOWN)




EXAMPLE MULTI-PART INTERIOR FRAME

NOTES ON POTENTIAL ANCHOR LOCATIONS:

1. ANCHOR CLUSTER AND QUANTITY INFORMATION FROM TABLE 4, SHEET 8, APPLIES AS THE MINIMUM REQUIREMENT FOR ALL TRACK CONFIGURATIONS. ANCHORS MAY BE STAGGERED WITHIN TRACK SECTIONS EXCEPT THAT THE ASTRAGAL AND INTERLOCK CLUSTERS MUST BE LOCATED IN THE TRACK ON WHICH ASTRAGAL AND/OR INTRLOCKS ARE POSITIONED WHEN THE DOOR(S) ARE IN THE CLOSED AND LOCKED POSITION. MINIMUM ON-CENTER DIMENSIONS FOR ANCHORS ARE 1.69" AT HEAD AND SILL AND 1.59" FOR JAMBS.
2. EMBEDMENT AND EDGE DISTANCES SHOWN FOR 2 TRACK FRAMES ON SHEETS 4-6 ARE ALSO APPLICABLE TO ALL MULTI-TRACK SECTIONS.

Title: ALUMINUM SLIDING GLASS DOOR, NON-IMPACT		Drawn By: AGK		 1070 TECHNOLOGY DRIVE N. VENICE, FL 34275 (941) 480-1600	 ANTHONY LYNN MILLER LICENSE No. 58705 STATE OF FLORIDA PROFESSIONAL ENGINEER A. LYNN MILLER, P.E. P.E.# 58705
Description: FRAME, POTENTIAL ANCHOR LOCATIONS		Date: 4/12/19			
Revision: ORIGINAL ISSUE		Rev. By:	Rev. Date:	COPYRIGHT © 2019 PGT INDUSTRIES, INC. ALL RIGHTS RESERVED CERT. OF AUTH. #29296	A. LYNN MILLER, P.E. P.E.# 58705
Series/Model: SGD-4025A	Scale: 3"=1'-0"	Sheet: 9 OF 12	Drawing No. SGD4025A		



111 I.G. TOP RAIL  
MAT'L: 6063-T5

11 MONO TOP RAIL  
MAT'L: 6063-T5

134 I.G. DOUBLE INTERLOCK

33 MONO DOUBLE INTERLOCK

101 I.G. LOCKSTILE

106 I.G. INTERLOCK

71 2-TRACK HEAD

115 I.G. BOTTOM RAIL

15 MONO BOTTOM RAIL  
MAT'L: 6063-T5


121 I.G. ASTRAGAL

24 MONO ASTRAGAL


1 MONO LOCK STILE

6 MONO INTERLOCK

73 2-TRACK JAMB




72 2-TRACK EXTERIOR SILL




74 2-TRACK INTERIOR SILL

45 REINFORCEMENT


46 REINFORCEMENT




77 FIXED PANEL CLIP, BOTTOM  
MAT'L: 6061-T6




76 FIXED PANEL CLIP, TOP  
MAT'L: 6061-T6




69 HOOKSTRIP  
MAT'L: 6063-T5



203 OPTIONAL SCREEN RAIL, POCKET  
MAT'L: 6063-T5




225 HI-RISE TRACK ADAPTER  
MAT'L: 6063-T5

















70 HI-RISE TRACK ADAPTER  
MAT'L: 6063-T5



NOTE: ALL MATERIAL IS 6063-T6 UNLESS OTHERWISE NOTED

Title: ALUMINUM SLIDING GLASS DOOR, NON-IMPACT		Drawn By: AGK		 ANTHONY LYNN MILLER LICENSE No. 58705 4/12/19 STATE OF FLORIDA PROFESSIONAL ENGINEER
Description: EXTRUSIONS		Date: 4/12/19		
Revision: ORIGINAL ISSUE		Rev. By:	Rev. Date:	1070 TECHNOLOGY DRIVE N. VENICE, FL 34275 (941) 480-1600
Series/Model: SGD-4025A	Scale: 6"=1'-0"	Sheet: 10 OF 12	Drawing No. SGD4025A	Rev. 0
				COPYRIGHT © 2019 PGT INDUSTRIES, INC. ALL RIGHTS RESERVED CERT. OF AUTH. #29296 A. LYNN MILLER, P.E. P.E.# 58705

ADDED FRAME COMPONENTS





NOTE: ALL MATERIAL IS 6063-T6 UNLESS OTHERWISE NOTED

Title: ALUMINUM SLIDING GLASS DOOR, NON-IMPACT		Drawn By: AGK			
Description: EXTRUSIONS CONTINUED		Date: 4/12/19			
Revision: ORIGINAL ISSUE		Rev. By: *	Rev. Date: *	1070 TECHNOLOGY DRIVE N. VENICE, FL 34275 (941) 480-1600	
Series/Model: SGD-4025A	Scale: 6"=1'-0"	Sheet: 11 OF 12	Drawing No. *	Rev: 0	COPYRIGHT © 2019 PGT INDUSTRIES, INC. ALL RIGHTS RESERVED CERT. OF AUTH. #29296

ITEM	PART #	DESCRIPTION	PGT#
1	708	LOCKSTILE, MONOLITHIC	69362
2		LATCH ASSEMBLY (LOCK)	7LOCK
3		LATCH ASSEMBLY (DUMMY)	7DUMMY
4		#10-32 X 1.25 PH. FL. MS (LATCH)	71114K
6	705	INTERLOCK (STD.), MONOLITHIC	69409
7	1119	#10 X .750 PH. PN. SMS - S.S.	7S134X
8		1/4-20 X 1.125 PH. PN. MS	71420X118PPMSX
9	1209	WSTP, .187 X 320 - PLE	6FELTK
11	706	TOP RAIL, MONOLITHIC	68172
12	1281	WSTP, .187 X .290 FIN SEAL	61281W
13	725B	TOP PANEL GUIDE	41801
15	707C	BOTTOM RAIL, MONOLITHIC	68173
17	726	BOTTOM PANEL GUIDE	41802
18	661	SINGLE ROLLER ASSY.	7SRAZ
19	661	SINGLE ROLLER ASSY. - S.S.	7SRAX
20	683	TANDEM ROLLER ASSY.	7683Z
21	683	TANDEM ROLLER ASSY. - S.S.	7683SS
23	609	ASTRAGAL, MONOLITHIC	68315
24	720	ASTRAGAL (H.D.), MONOLITHIC	69492
26	653	LATCH KEEPER	7SDKEEP
27	653	LATCH KEEPER - S.S.	7SDKEEPX
28		#8 X .312 PH. TR. SMS	78X56A
29	729	JAMB BUMPER	72087K
30		#6 X .375 PH. PN. SMS	76X38PPA
31	663/664	BUMPER SHIM (.030 OR .060)	41831
33	734	DOUBLE INTERLOCK (STD.), MONO.	69494
36	1007	GLAZING VINYL - 3/16	6T304
37		GLAZING VINYL - 1/4	614GLK
38		CARDINAL XL EDGE SPACER, 5/16" STAINLESS STEEL	
39		3/16" TEMPERED GLASS	
40		1/4" TEMPERED GLASS	
42	645	ADD-ON STILE (OXO ONLY)	69112
45	755	1/2 X 1 5/8 REINF. - ALUM	6755M
46	1214	1/2 X 1 1/4 REINF. - ALUM.	61214M
49	749	REINFORCEMENT SPRING CLIP	7BRKTM25
51	1040	MORTICE LOCK (DEAD LATCH)	71040
52	1040-2	MORTICE LOCK (DEAD LATCH) S.S.	71040X
53		CYLINDER/HOUSING ASSY. (MORTICE)	70288K
54	1016	#8 X .625 PH. FL. SMS	7858ZA
55	657	BACKING PLATE (MORTICE)	41830N
56	1045	MORTICE HANDLE SET	71045
57		COVER PLATE	7VT43
58	659	MORTICE LATCH KEEPER	7SDSP5X1
60	1239	3/16" APPLIED MUNTIN	68421

ITEM	PART #	DESCRIPTION	PGT#
62	522	COLONIAL INTERSECTION	41630
63	124	APPLIED COLONIAL MUNTIN	66631
64	1240	1/16 X 1 FLATBAR	68926T52
66	754	TRACK CLIP GUIDE	41754B/W
67	756	TRACK CLIP COVER	6756B/W
68		#6 X 3/8 PP SMS (18-8 SS)	76X38PPAX
69	740	HOOKSTRIP (P-HOOK)	63713
70	722A	HIGH-RISE TRACK ADAPTER	69371
71	702	2-TRACK HEAD	68179
72	703B	2-TRACK EXTERIOR SILL	6703B
73	704	2-TRACK JAMB	68180
74	637	2-TRACK INTERIOR SILL	68275
76	717	FIXED PANEL CLIP, TOP	7LA13A
77	717B	FIXED PANEL CLIP, BOTTOM	7717FPCA
78	646	FIXED PANEL BRACKET	41814
90	1136	#6 X 1/2 PP SMS	76X12A
101	736	LOCKSTILE, I.G. GLASS	60392
106	735	INTERLOCK (STD.) I.G. GLASS	60393
111	618	TOP RAIL, I.G. GLASS	69088
115	619	BOTTOM RAIL, I.G. GLASS	69089
121	737	ASTRAGAL, I.G. GLASS	60394
130		5/8" I.G. GLASS; 3/16" TEMPERED 1/4" SPACE, 3/16" TEMPERED	
131	1006	GLAZING VINYL - INSULATED GLASS	658GLK
134	745	DOUBLE INTERLOCK (STD.), I.G. GLASS	60551
201	629	1 - TRACK HEAD, POCKET DOOR	68176
202	628	1 - TRACK JAMB, POCKET DOOR	6628
203	666	OPT. SCREEN RAIL, POCKET DOOR	61394
204	627	1 - TRACK SILL, EXT. POCKET DOOR	68178M
208	631	3 - TRACK HEAD	68182
209	632	3 - TRACK JAMB	68183
210	633	3 - TRACK SILL, EXT. W/ SCREEN RAIL	68184M
211	613	ADD-ON TRACK HEAD	68187
212	614	ADD-ON TRACK FOR FRAME HEAD	68185
213	617	2 - TRACK FRAME JAMB, ADD-ON	68188
214	615	3 - TRACK SILL, ADD-ON	68189M
215	616	ADD-ON TRACK W/ SCREEN FOR SILL	68190M
216	634	ADD-ON HEAD	68186
217	635	ADD-ON SILL	68191M
218	638	LOW-RISE 2 - TRACK SILL, EXTERIOR	68952M
220	636	1 - TRACK SILL, INTERIOR	68274M
222	671	LOW-RISE 1 - TRACK SILL, EXTERIOR	60803M
225	732	HIGH-RISE TRACK ADAPTER	68313M

Title: ALUMINUM SLIDING GLASS DOOR, NON-IMPACT		Drawn By: AGK			
Description: PARTS LIST		Date: 4/12/19			
Revision: ORIGINAL ISSUE		Rev. By:	Rev. Date:	1070 TECHNOLOGY DRIVE N. VENICE, FL 34275 (941) 480-1600	
Series/Model: SGD-4025A	Scale: N.T.S.	Sheet: 12 OF 12	Drawing No. SGD4025A	Rev. 0	COPYRIGHT © 2019 PGT INDUSTRIES, INC. ALL RIGHTS RESERVED CERT. OF AUTH. #29296
					A. LYNN MILLER, P.E. P.E.# 58705