
1ST COAST 26 Ga. STEEL PBR ROOF PANEL

36" RIBBED ROOF PANEL INSTALLED DIRECTLY OVER STEEL PURLINS OR INSTALLED OVER EXISTING PBR PANEL OVER STEEL PURLINS

FIELD INSTALLATION



#10x3/4" HiLo HWH SCREW WITH WEATHER-SEAL WASHER AT OVER-LAPPING PANEL SEAMS, 12" O.C. #10x1 1/2" HiLo HWH SCREW-WITH WEATHER-SEAL WASHER, 12" O.C. STEEL PURLINS (16 Ga, 50 ksi MIN) SPACED 60" MAX. O.C.

SECTION A-A

MAX UPLIFT PRESSURE 62.5 Psf

GENERAL NOTES:

- 1. PBR PANEL MAY BE INSTALLED DIRECTLY TO STEEL PURLINS, OR INSTALLED OVER EXISTING PBR PANELS.
- 2. IF INSTALLED OVER EXISTING PANELS, THE EXISTING SCREWS AND ANY DEBRIS MUST BE REMOVED FROM THE EXISTING ROOF. ANY CORROSION IN THE EXISTING ROOF MUST BE TREATED WITH A RUST INHIBITOR PER FBC 1521.8.
- 3. AT PANEL BUTT JOINTS, PANELS ARE OVERLAPPED 2", SEALED WITH BUTYL TAPE, AND FASTENED WITH #10x1 1/2" HiLo HWH SCREWS 3" O.C.
- 4. ROOF SLOPE IS LIMITED PER THE REQUIREMENTS OF FBC SECTION 1507.4.2.
- 5. FLASHING AND TRIM TO BE INSTALLED PER THE MANUFACTURER'S STANDARD INSTALLATION DETAILS, TO MEET THE REQUIREMENTS OF FBC SECTION 1503.

PH: (561) 629-7288 w.1stcoastmrs.com

SUPPLY ROOFING COAST METAL

186 STATE ROAD 207 EAST PALATKA, FL 32131


1ST COAST 1CPBR

SHEET:

1ST COAST 26 Ga. STEEL PBR ROOF PANEL

36" RIBBED ROOF PANEL INSTALLED DIRECTLY OVER STEEL PURLINS OR INSTALLED OVER EXISTING PBR PANEL OVER STEEL PURLINS

PERIMETER & CORNER INSTALLATION



#10x3/4" HiLo HWH SCREW WITH WEATHER-SEAL WASHER AT OVER-LAPPING PANEL SEAMS, 12" O.C. #10x1 1/2" HiLo HWH SCREW-WITH WEATHER-SEAL WASHER, 12" O.C. -STEEL PURLINS (16 Ga, 50 ksi MIN) SPACED 60" MAX. O.C.

SECTION A-A

MAX UPLIFT PRESSURE

130 Psf

GENERAL NOTES:

- 1. PBR PANEL MAY BE INSTALLED DIRECTLY TO STEEL PURLINS, OR INSTALLED OVER EXISTING PBR PANELS.
- 2. IF INSTALLED OVER EXISTING PANELS, THE EXISTING SCREWS AND ANY DEBRIS MUST BE REMOVED FROM THE EXISTING ROOF. ANY CORROSION IN THE EXISTING ROOF MUST BE TREATED WITH A RUST INHIBITOR PER FBC 1521.8.
- 3. AT PANEL BUTT JOINTS, PANELS ARE OVERLAPPED 2", SEALED WITH BUTYL TAPE, AND FASTENED WITH #10x1 1/2" HiLo HWH SCREWS 3" O.C.
- 4. ROOF SLOPE IS LIMITED PER THE REQUIREMENTS OF FBC SECTION 1507.4.2.
- 5. FLASHING AND TRIM TO BE INSTALLED PER THE MANUFACTURER'S STANDARD INSTALLATION DETAILS, TO MEET THE REQUIREMENTS OF FBC SECTION 1503.

NO NO STATE OF THE PROPERTY OF SCOTT WOLTERS FL PE# 62354

PH: (561) 629-7288 w.1stcoastmrs.com

ROOFING COAST METAL


SUPPLY


186 STATE ROAD 207 EAST PALATKA, FL 32131



1ST COAST 26 Ga. STEEL PBR ROOF PANEL

36" RIBBED ROOF PANEL INSTALLED DIRECTLY OVER STEEL PURLINS OR INSTALLED OVER EXISTING PBR PANEL OVER STEEL PURLINS





OVERLAP DETAIL (1 RIB)



COAST METAL ROOFING SUPPLY