

NOTE:
GLASS CAPACITIES ON THIS SHEET ARE
BASED ON ASTM E1300-16 (3 SEC. GUSTS)

WDW. WIDTH	WDW. HEIGHT
19- 1/ 8"	53- 1/ 8"
26- 1/ 2"	53- 1/ 8"
32"	53- 1/ 8"
37"	53- 1/ 8"
42"	46- 3/ 4"
48"	40- 7/ 8"
53- 1/ 8"	37"

MAXIMUM DESIGN LOAD RATING = + 70.0 PSF
(FOR SIZES SHOWN OR SMALLER) - 70.0 PSF

THESE WINDOWS ARE RATED FOR LARGE & SMALL MISSILE IMPACT.
SHUTTERS ARE NOT REQUIRED.

ECO-GUARD SERIES-560
ALUMINUM PROJECT-OUT WINDOW

APPROVAL APPLIES TO SINGLE UNITS OR SIDE BY SIDE
COMBINATIONS OF PROJECTED/PROJECTED OR PROJECTED WITH
OTHER WINDOW TYPES IN MODULES OF TWO OR MORE WINDOWS
USING FBC HVHZ APPROVED MULLIONS IN BETWEEN.
LOWER DESIGN PRESSURE FROM WINDOWS OR MULLION APPROVAL
WILL APPLY TO ENTIRE SYSTEM.

THIS PRODUCT HAS BEEN DESIGNED AND TESTED TO COMPLY WITH THE
REQUIREMENTS OF THE FLORIDA BUILDING CODE INCLUDING HIGH VELOCITY
HURRICANE ZONE (HVHZ).

1BY OR 2BY WOOD BUCKS & BUCK FASTENERS BY OTHERS, MUST BE
DESIGNED AND INSTALLED ADEQUATELY TO TRANSFER APPLIED PRODUCT LOADS
TO THE BUILDING STRUCTURE.

ANCHORS SHALL BE CORROSION RESISTANT, SPACED AS SHOWN ON DETAILS
AND INSTALLED PER MANUF'S INSTRUCTIONS. SPECIFIED EMBEDMENT TO BASE
MATERIAL SHALL BE BEYOND WALL DRESSING OR STUCCO.


A LOAD DURATION INCREASE IS USED IN DESIGN OF ANCHORS INTO WOOD ONLY.

ALL SHIMS TO BE HIGH IMPACT, NON-METALLIC AND NON-COMPRESSIBLE.


MATERIALS INCLUDING BUT NOT LIMITED TO STEEL/METAL SCREWS, THAT
COME INTO CONTACT WITH OTHER DISSIMILAR MATERIALS SHALL MEET THE
REQUIREMENTS OF THE FLORIDA BLDG. CODE & ADOPTED STANDARDS.

THIS PRODUCT APPROVAL IS GENERIC AND DOES NOT PROVIDE INFORMATION
FOR A SITE SPECIFIC PROJECT, i.e. LIFE SAFETY OF THIS PRODUCT, ADEQUACY
OF STRUCTURE RECEIVING THIS PRODUCT AND SEALING AROUND OPENING FOR
WATER INFILTRATION RESISTANCE ETC.
CONDITIONS NOT SHOWN IN THIS DRAWING ARE TO BE ANALYZED SEPARATELY,
AND TO BE REVIEWED BY BUILDING OFFICIAL.

DESIGN LOAD SHOWN ARE BASED ON 'ALLOWABLE STRESS DESIGN (ASD)'.




TYPICAL ELEVATION




SETTING BLOCKS AT
LAM. GLASS AND INSUL. LAM. GLASS NOTCH
GLAZING BEAD LEG TO CLEAR BLOCKS


WDW. HEIGHT UP TO	NO. OF KEEPERS AT SASH
26"	2
38- 3/ 8"	3
50- 5/ 8"	4
53- 1/ 8"	4




TYPICAL ELEVATION



GLASS TYPE 'A'



GLASS TYPE 'AA'



GLASS TYPE 'B'

GLAZING OPTIONS

SEALED: 06-15-2026

FL#41651.1



JAVAD AHMAD PE, inc
7875 NW 12th St., Suite 102 Doral,
FL 33126
Ph: (305) 424-8001
support@ja-pe.com


CONSULTING • STRUCTURAL DESIGN • FACADES • BUILDING ENVELOPE • SYSTEM DESIGN • PRODUCT APPROVALS


drawing no.	JA-1844-24	drawn by:	MA
date:	12/31/2024	check by:	BS
REVISION			
No.	DATE	BY	DESCRIPTION

SERIES 560 : ECO-GUARD ALUMINUM AWNING WINDOW
(L.M.I.)
LARGE MISSILE IMPACT RATED



ECO WINDOW SYSTEMS, LLC.
8502 N.W. 80th ST. MEDLEY, FL 33166
TEL. (305) 885-5299 FAX. (305) 885-5902









WOOD BUCKS AND METAL STRUCTURE NOT BY 'ECO WDW.'
MUST SUSTAIN LOADS IMPOSED BY GLAZING SYSTEM
AND TRANSFER THEM TO THE BUILDING STRUCTURE.

TYPICAL ANCHORS: SEE ELEV. FOR SPACING

Anchor Type	Frame Member	Substrate	Min. Edge Distance	Min. Embedment or Metal Thickness
1/4" DeWalt UltraCon+	All	Southern Pine (SG = 0.55)	1"	1-1/2"
	All	Thru 1BY Buck into Concrete (min. 3 ksi)	2-1/2"	1-1/4"
	Jambs	Thru 1BY Buck into Hollow or Filled Block (ASTM C90, min. 2 ksi)	2-1/2"	1-1/4"
	All	Concrete (min. 3 ksi)	2-1/2"	1-1/4"
	Jambs	Hollow or Filled Block (ASTM C90, min. 2 ksi)	2-1/2"	1-1/4"
#14 SMS or Self Drilling Screws (Gr. 2)	All	Aluminum 1/8" Thk. Min. (6063-T5)	3/4"	(3) Threads min. beyond metal thickness
	All	Steel 1/8" Thk. Min. (min. 36 ksi)	3/4"	(3) Threads min. beyond metal thickness
#12 SMS or Self Drilling Screws (Gr. 2)	All	FBC Approved Mullions	3/4"	(3) Threads min. beyond metal thickness
	All	Aluminum 1/8" Thk. Min. (6063-T5) (No Shim Space)	3/4"	(3) Threads min. beyond metal thickness
	All	Steel 1/8" Thk. Min. (min. 36 ksi) (No Shim Space)	3/4"	(3) Threads min. beyond metal thickness

1. STEEL IN CONTACT WITH ALUMINUM TO BE PLATED OR PAINTED
2. ALL ANCHOR HEAD TYPES ARE ACCEPTABLE



SEALED: 06-15-2026

FL#41651.1



JAVAD AHMAD PE, inc
7875 NW 12th St., Suite 102 Doral,
FL 33126
Ph: (305) 424-8001
support@ja-pe.com

CONSULTING • STRUCTURAL DESIGN • FACADES • BUILDING ENVELOPE • SYSTEM DESIGN • PRODUCT APPROVALS




drawing no.	MA	drawn by:	BS
JA-1844-24			
date:	REVISION	DESCRIPTION	
12/31/2024	BY		
	DATE		
	No		

SERIES 560 - ECO-GUARD ALUMINUM AWNING WINDOW
(L.M.I.)
LARGE MISSILE IMPACT RATED



ECO WINDOW SYSTEMS, LLC.
8502 N.W. 80th ST. MEDLEY, FL 33166
TEL. (305) 885-5299 FAX. (305) 885-5902





SEALED: 06-15-2026

FL#41651.1



JAVAD AHMAD PE, inc

7875 NW 12th St., Suite 102 Doral,
FL 33126

Ph: (305) 424-8001

support@ja-pe.com


CONSULTING • STRUCTURAL DESIGN • FACADES • BUILDING ENVELOPE • SYSTEM DESIGN • PRODUCT APPROVALS

drawing no.	JA-1844-24	MA
date:	12/31/2024	BS
revision	by	description
No.	DATE	

SERIES 560 : ECO-GUARD ALUMINUM AWNING WINDOW
(L.M.I.)
LARGE MISSILE IMPACT RATED








ECO WINDOW SYSTEMS, LLC.
8502 N.W. 80th ST. MEDLEY, FL 33166
TEL. (305) 885-5299 FAX. (305) 885-5902



03

03 of 06



INSTALLATION DETAILS WITH FLUSH FRAME ADAPTER

SEALED: 06-15-2026

FL#41651.1



JAVAD AHMAD PE, inc
7875 NW 12th St., Suite 102 Doral, FL 33126
Ph: (305) 424-8001
support@ja-pe.com

CONSULTING • STRUCTURAL DESIGN • FACADES • BUILDING ENVELOPE • SYSTEM DESIGN • PRODUCT APPROVALS

drawing no.	JA-1844-24	MA
date:	12/31/2024	BS
REVISION		
No.	DATE	BY
		DESCRIPTION









SERIES 560 : ECO-GUARD ALUMINUM AWNING WINDOW (L.M.I.)

LARGE MISSILE IMPACT RATED



ECO WINDOW SYSTEMS, LLC.
8502 N.W. 80th ST. MEDLEY, FL 33166
TEL. (305) 885-5299 FAX. (305) 885-5902





ITEM #	PART #	QUANTITY	DESCRIPTION	MATERIAL	MANF./SUPPLIER/REMARKS
1	E501	4	FRAME HEAD/SILL/JAMB	6063 - T6	-
2	E502	4	VENT	6063 - T6	-
3	FY108	AS REQD.	GLAZING BEAD (LAM. GLASS)	6063 - T6	-
3A	E505	AS REQD.	GLAZING BEAD (INSUL. LAM. GLASS)	6063 - T6	-
4	E508	AS REQD.	SNUBBER - VENT, FULL LENGTH	6063 - T6	-
4A	E509	AS REQD.	SNUBBER - FRAME, FULL LENGTH	6063 - T6	-
5	E506	OPTIONAL	SCREEN FRAME	6063 - T6	-
7	#10 X 1-1/4"	AS REQD.	FRAME AND VENT ASSEMBLY SCREWS	-	H WS SMS
8	E203	AS REQD.	BULB WEATHERSTRIPPING, DUROMETER 65	SANTOPRENE	ULTRAFAB
9	E203	AS REQD.	GLAZING BEAD BULB, DUROMETER 65	SANTOPRENE	ULTRAFAB
10	35.12.00.400	2/ VENT	4 BAR HINGES	ST. STEEL	TRUTH, INSTALLED WITH (2) #10 X 5/8" SDS
11	13096.92	1	MULTI POINT LOCK SYSTEM	-	TRUTH
12	31964.92	AS REQD.	KEEPER	STEEL	TRUTH
13	52.13.012	1/ VENT	ROTO OPERATOR	ZAMAK/STL.	TRUTH, AT 12" FROM ENDS
14	PSJ40-SS	2/ CORNER	FRAME/VENT CORNER KEY	ST. STEEL	-
15	FY120	AS REQD.	FLUSH FRAME ADAPTER	6063-T6	OPTIONAL
16	-	2	ANTI SAG SKATE, AT 4-1/2" FROM EACH END	NYLON	M&M PLASTICS
17	#10 X 1-1/4"	2/ SKATE	FH SDS SKATE SCREWS	-	-
18	#8 X 3/4"	AS REQD.	FH SMS SNUBBER SCREWS	-	IN PARIS 2" APART, PAIRS SPACED AT 7-3/4" O.C.
19	-	AS REQD.	SETTING BLOCOK, 3/16" X 3/4" X 4" LONG	EPDM	DUROMETER 80±5 SHORE A
20	FLB-50	-	GLASS SPACER - 1/8" HIGH	SILICONE	FRANK LOWE
21	-	-	INSUL. GLASS SPACER	VARIOUS	VARIOUS

SEALANT:

ALL JOINTS AND FRAME CONNECTIONS SEALED WITH SCHNEE-MOREHEAD SM5504 SEAM SEALER. PERIMETER CAULKING SICAFLEX 15LM ON EXTERIOR ONLY.

LOCKS:

MULTIPOINT LOCK SYSTEMS # 13096.92 BY 'TRUTH' AT FRAME JAMB.
LOCK OPERATOR #24.33.XX.004 AT 8-1/2" FROM SILL FASTENED TO JAMBS WITH (2) #10 X 5/8" PH SMS. LOCK BAR SECURED TO JAMB WITH LOCK GUIDES #33489.00.0001 SPACED AT 12-3/4" O.C. MAX. EACH GUIDE FASTENED WITH (2) #10 X 1" PH SMS.

STAINLESS STEEL KEEPERS #31964.92 AT VENT EACH FASTENED WITH (2) #10 X 5/8" P FH SMS SEE CHART ON SHEET 1 FOR QUANTITIES.

HINGES:

4 BAR ST/ST HINGES #35.12.00.400 BY 'TRUTH' LOCATED AT TOP AND BOTTOM CORNERS FASTENED WITH (2) #10 X 5/8" PH SELF DRILLING SCREWS EACH

OPERATOR:

SINGLE ARM ROTO OPERATOR #52.13.012 BY 'TRUTH' LOCATED AT MIDSPAN OF FRAME SILL FASTENED WITH (6) # 10 X 1" PH SMS. OPERATOR TRACK #30175 AT BOTTOM RAIL FASTENED WITH (2) #10 X 1" PH SMS.

ANTI-SAG SKATES:

VINYL ANTI-SAG SKATES BY 'M&M PLASTICS' (2) AT BOTTOM RAIL AT 4-1/2" FROM ENDS EACH FASTENED WITH (2) #10 X 1-1/4" FH SDS.



JAVAD AHMAD PE, inc

7875 NW 12th St., Suite 102 Doral,
FL 33126

Ph: (305) 424-8001

support@ja-pe.com


CONSULTING • STRUCTURAL DESIGN • FACADES • BUILDING ENVELOPE • SYSTEM DESIGN • PRODUCT APPROVALS

drawing no.	MA	drawn by:	BS	check by:
date:	JA-1844-24	12/31/2024	REVISION	DESCRIPTION
			DATE	BY
			No	

SERIES 560 : ECO-GUARD ALUMINUM AWINING WINDOW (L.M.I.)
LARGE MISSILE IMPACT RATED



ECO WINDOW SYSTEMS, LLC.
8502 N.W. 80th ST. MEDLEY, FL 33166
TEL. (305) 885-5299 FAX. (305) 885-5902




SEALED: 06-15-2026


FL#41651.1

05

05 of 06



VENT CORNERS



FRAME CORNERS

SEALED: 06-15-2026

FL#41651.1



JAVAD AHMAD PE, inc
 7875 NW 12th St., Suite 102 Doral,
 FL 33126
 Ph: (305) 424-8001
 support@ja-pe.com

CONSULTING • STRUCTURAL DESIGN • FACADES • BUILDING ENVELOPE • SYSTEM DESIGN • PRODUCT APPROVALS

SERIES 560 : ECO-GUARD ALUMINUM AWNING WINDOW
 (L.M.I.)
 LARGE MISSILE IMPACT RATED



ECO WINDOW SYSTEMS, LLC.
 8502 N.W. 80th ST. MEDLEY, FL 33166
 TEL. (305) 885-5289 FAX. (305) 885-5902



drawing no.	JA-1844-24	drawn by:	MA
date:	12/31/2024	check by:	BS
REVISION			
No.	DATE	BY	DESCRIPTION