

GP P&S ROOFING UNDERLAYMENT:

INSTALLATION INSTRUCTIONS

Surface Preparation: Ensure the roof deck is clean, dry, and free from debris, dust, or any contaminants that could compromise adhesion. Remove any protrusions or sharp objects that might puncture the underlayment.

Starting Point: Begin the installation at the eave edge of the roof, ensuring the underlayment is parallel to the roof edge.

Application: Remove the release liner from the adhesive side of the underlayment. Press the underlayment firmly onto the deck, smoothing out any wrinkles or air pockets. Overlap each new course of underlayment by 4 inches to ensure a proper water-tight seal. The overlap should run in the direction of water flow.

Sealing: After pressing the underlayment into place, make sure the seams and overlaps are sealed by pressing them down firmly.

Termination: At the ridge or roof peak, cut the underlayment to fit and press the edges to ensure a complete seal.

Precautions: Temperature Considerations: Install the underlayment when temperatures are between 40°F and 120°F (4°C to 49°C) to achieve optimal adhesion. GP P&S ROOFING UNDERLAYMENT is designed to withstand high temperatures up to 260°F (126°C) after installation.

The underlayment must be installed in accordance with the provisions of FBC Sections 1507 and 1518.

Exposure Limitations: Do not leave the underlayment exposed for more than 90 days before applying the final roofing material.

Safety Measures: Always use appropriate fall protection, gloves, and eye protection while working on the roof to ensure safe installation.

Warranty: GP P&S ROOFING UNDERLAYMENT comes with a 30-year limited lifetime warranty, covering defects in materials and workmanship. For detailed warranty information, please refer to the product documentation.

Storage and Handling: Storage Conditions: Store the rolls upright in a cool, dry place, away from direct sunlight and heat sources.

Stacking: Avoid stacking heavy items on top of the rolls to prevent deformation.

Release Liner: Ensure the release liner remains intact until installation to protect the adhesive surface from contaminants.

Compatibility: GP P&S ROOFING UNDERLAYMENT is compatible with a variety of roofing materials, including asphalt shingles, metal roofing, tile, and slate. Always check compatibility with the roofing manufacturer's guidelines before installation.

Safety Information: Use protective gloves, eye protection, and appropriate clothing during installation. Ensure all local building codes and regulations are followed during installation.

FOR MORE INFORMATION, visit our website www.greenproventures.com, or contact our support team at info@greenproventures.com.