



NOTES

1. NON-IMPACT RESISTANT OPTION - .125" MINIMUM DSB GLAZING MEETS UNIFORM STATIC DESIGN PRESSURES SHOWN ON THIS DRAWING. GLAZING SHALL HAVE A MAXIMUM HEIGHT OF 6.70" AND A MAXIMUM LENGTH OF 24.00". GLAZING IS NOT IMPACT RESISTANT AND DOES NOT MEET THE REQUIREMENTS FOR WIND-BORNE DEBRIS REGIONS.
2. IMPACT RESISTANT GLAZING OPTION - IMPACT RESISTANT GLAZING SYSTEM MAY BE INSTALLED IN INTERMEDIATE SECTIONS (WITH OR WITHOUT DECORATIVE INSERTS). GLAZING SHALL BE 1/4" POLYCARBONATE. MAXIMUM GLAZING DIMENSIONS SHALL BE 11" x 17", FASTENED WITH A MINIMUM #8 X 1" SMS: 3X ALONG THE HORIZONTAL AND 2X ALONG THE VERTICAL.
3. ALUMINUM FULL VIEW OPTION - ALUMINUM FULL VIEW SECTION MAY REPLACE ANY SECTION EXCEPT TOP AND BOTTOM PANELS. ALUMINUM FULL VIEW SECTION SHALL HAVE RAILS AND STILES OF EXTRUDED ALUMINUM ALLOY 6063-T6 AND .125" MINIMUM DSB GLAZING INSTALLED WITH ALUMINUM RETAINERS IN ORDER TO MEET UNIFORM STATIC DESIGN PRESSURES SHOWN ON THIS DRAWING. AFV PANEL SIZE IS 51.5"x21.9" (MAX). GLAZING IS NOT IMPACT RESISTANT AND DOES NOT MEET THE REQUIREMENTS FOR WIND-BORNE DEBRIS REGIONS.
4. MINIMUM OF 1" OVERLAP ON BOTH JAMBS REQUIRED TO MEET NEGATIVE DESIGN PRESSURES.
4. SLIDE LOCKS REQUIRED.
5. SECTION STEEL TO HAVE THE FOLLOWING MINIMUM THICKNESS:
401, 402 - 20 GA
403, 404 - 24 GA
405, 406 - 25 GA
7. THE DESIGN OF THE SUPPORTING STRUCTURAL ELEMENTS SHALL BE THE RESPONSIBILITY OF THE PROFESSIONAL OF RECORD FOR THE BUILDING OR STRUCTURE AND IN ACCORDANCE WITH CURRENT BUILDING CODES FOR THE LOADS LISTED ON THIS DRAWING.
8. TRACK CLIPS SHALL BE LOCATED WITH CENTERLINE OF BOTTOM CLIP SPACED 10" MAX FROM BOTTOM OF TRACK AND REMAINING TRACK CLIPS SPACED AT 24" O.C. MAX. SPACING BETWEEN TOP TRACK CLIP AND SPLICE PLATE SHALL BE 30" O.C. MAX.
9. WHEN MOUNTING TO WOOD, DOOR JAMB TO BE MINIMUM 2x6 STRUCTURAL GRADE LUMBER. REFER TO JAMB CONNECTION SUPPLEMENT FOR ATTACHMENT TO SUPPORTING STRUCTURE.

SUPERIMPOSED DESIGN PRESSURE LOADS ON SUPPORTING STRUCTURE

MAX DOOR WIDTH	DOOR HEIGHT	MAX UNIFORM LOAD EACH JAMB (PLF)
9'-4"	ALL	+132.1/-151.3

STATIC PRESSURE RATINGS	APPROVED SIZES
DESIGN PRESSURE(PSF): +28.4/-32.2	MAX WIDTH: 9'-4"
	MAX HEIGHT: 24'-1"
IMPACT/CYCLIC RATED: YES	MAX SECTION HEIGHT: 24'






























J. CHRISTIAN VOELKEL, PE
407 Navarre Street
Gulf Breeze, FL 32561
FL PE 82229
TX PE 133174

Digitally signed
by John Voelkel
Date:
2026.07.10
16:00:09 -05'00'

NOTE: (4) SECTION SOLID DOOR SHOWN. SEE SHEET 2 FOR U-BAR LOCATIONS ON DOORS WITH OTHER SECTION QUANTITIES AND SEE NOTES 1 & 2 THIS SHEET FOR GLAZING OPTIONS.

COMPLIES WITH THE REQUIREMENTS OF IBC/IRC 2024.
COMPLIES WITH THE CURRENT EDITION OF THE FLORIDA BUILDING CODE.

THE DRAWINGS AND ALL OTHER INFORMATION CONTAINED HEREIN ARE THE CONFIDENTIAL AND PROPRIETARY PROPERTY OF OVERHEAD DOOR CORPORATION AND ITS AFFILIATED COMPANIES. THIS DRAWING AND INFORMATION, IN WHOLE OR IN PART, MAY NOT BE COPIED IN ANY MANNER OR DISCLOSED TO ANYONE WITHOUT THE PRIOR WRITTEN CONSENT OF OVERHEAD DOOR CORPORATION. NO DISCLOSURE OF ANY OF THIS DRAWING OR INFORMATION IS INTENDED TO OPERATE AS A LICENSE OR AUTHORIZATION TO USE IT FOR ANY PURPOSE WITHOUT THE SPECIFIC WRITTEN CONSENT OF OVERHEAD DOOR CORPORATION.										
			TOLERANCES UNLESS OTHERWISE SPECIFIED		FINISH	The Genuine. The Original.	NAME		DATE	
			HOLE DIAMETER	WHOLE NUMBERS:	N/A		LEWISVILLE, TEXAS	DRAWN BY:	1/29/2026	
			UNDER .251 +.004/-0.003	± .25	UNIT OF MEASURE			MATERIAL:		S WOLFF
			.251 TO .500 +.006/-0.003	± .1						
			OVER .500 +.008/-0.003	± .03						
		FRACTIONS	± .010	EA		N/A	CHECKED BY:		-	
		± 1/16	± .5°		T CLARK					
							-			
								-		
REF DWG	USED ON	ASME Y14.100 AND Y14.5 APPLY, UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN U.S. CUSTOMARY UNITS.								
						</				



SEAL ON PAGE 1

STATIC PRESSURE RATINGS	APPROVED SIZES
DESIGN PRESSURE(PSF): +28.4/−32.2	MAX WIDTH: 9'−4"
	MAX HEIGHT: 24'−1"
IMPACT/CYCLIC RATED: YES	MAX SECTION HEIGHT: 24'

J. CHRISTIAN VOELKEL, PE
407 Navarre Street
Gulf Breeze, FL 32561
FL PE 82229
TX PE 133174

THE DRAWINGS AND ALL OTHER INFORMATION CONTAINED HEREIN ARE THE CONFIDENTIAL AND PROPRIETARY PROPERTY OF OVERHEAD DOOR CORPORATION AND ITS AFFILIATED COMPANIES. THIS DRAWING AND INFORMATION, IN WHOLE OR IN PART, MAY NOT BE COPIED IN ANY MANNER OR DISCLOSED TO ANYONE WITHOUT THE PRIOR WRITTEN CONSENT OF OVERHEAD DOOR CORPORATION. NO DISCLOSURE OF ANY OF THIS DRAWING OR INFORMATION IS INTENDED TO OPERATE AS A LICENSE OR AUTHORIZATION TO USE IT FOR ANY PURPOSE WITHOUT THE SPECIFIC WRITTEN CONSENT OF OVERHEAD DOOR CORPORATION.									
		 THIRD ANGLE PROJECTION	TOLERANCES UNLESS OTHERWISE SPECIFIED		FINISH	The Genuine. The Original.  LEWISVILLE, TEXAS	NAME	DATE	DRAWING TITLE: WINDLOAD OPTION CODE 2064 SERIES 401/402/403/404/405/406, 28.4"-32.2 PSF, 9'-4" MAX
			HOLE DIAMETER	WHOLE NUMBERS: ± .25 .251 TO .500 ± .006/-0.003 OVER .500 ± .008/-0.003	.X ± .1 .XX ± .03 .XXX ± .010		N/A	S WOLFF	
		ASME Y14.100 AND Y14.5 APPLY, UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN U.S. CUSTOMARY UNITS	FRACTIONS ± 1/16	ANGLES: ± .5°	UNIT OF MEASURE	N/A	CHECKED BY: T CLARK	-	DRAWING NUMBER: 4-41347
REF DWG	USED ON				EA		APPROVED BY: -	-	SCALE: N/A SHEET 2 OF 3

THE DRAWINGS AND ALL OTHER INFORMATION CONTAINED HEREIN ARE THE CONFIDENTIAL AND PROPRIETARY PROPERTY OF OVERHEAD DOOR CORPORATION AND ITS AFFILIATED COMPANIES. THIS DRAWING AND INFORMATION, IN WHOLE OR IN PART, MAY NOT BE COPIED IN ANY MANNER OR DISCLOSED TO ANYONE WITHOUT THE PRIOR WRITTEN CONSENT OF OVERHEAD DOOR CORPORATION. NO DISCLOSURE OF ANY OF THIS DRAWING OR INFORMATION IS INTENDED TO OPERATE AS A LICENSE OR AUTHORIZATION TO USE IT FOR ANY PURPOSE WITHOUT THE SPECIFIC WRITTEN CONSENT OF OVERHEAD DOOR CORPORATION.									
		 THIRD ANGLE PROJECTION	TOLERANCES UNLESS OTHERWISE SPECIFIED		FINISH N/A	 The Genuine. The Original. LEWISVILLE, TEXAS	NAME S WOLFF	DATE 1/29/2026	DRAWING TITLE WINDLOAD OPTION CODE 2064 SERIES 401/402/403/404/405/406, 28.4"-32.2 PSF, 9'-4" MAX
			HOLE DIAMETER UNDER .251 +.004/-0.003 .251 TO .500 +.006/-0.003 OVER .500 +.008/-0.003	WHOLE NUMBERS: ± .25 .X ± .1 .XX ± .03 .XXX ± .010 ANGLES: ± .5°	UNIT OF MEASURE EA		LEWISVILLE, TEXAS	CHECKED BY: T CLARK	
REF DWG	USED ON	ASME Y14.100 AND Y14.5 APPLY. UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN U.S. CUSTOMARY UNITS.	FRACTIONS ± 1/16		MATERIAL: N/A	APPROVED BY: -	SHEET 3 OF 3		