


NOTES

1. STANDARD GLAZING OPTION - .125" MINIMUM DSB GLAZING MEETS UNIFORM STATIC DESIGN PRESSURES SHOWN ON THIS DRAWING. GLAZING SHALL HAVE A MAXIMUM HEIGHT OF 6.70" AND A MAXIMUM LENGTH OF 24.00". GLAZING IS NOT IMPACT RESISTANT AND DOES NOT MEET THE REQUIREMENTS FOR WIND-BORNE DEBRIS REGIONS.
2. ALUMINUM FULL VIEW OPTION - ALUMINUM FULL VIEW SECTION MAY REPLACE ANY SECTION EXCEPT TOP AND BOTTOM PANELS. ALUMINUM FULL VIEW SECTION SHALL HAVE RAILS AND STILES OF EXTRUDED ALUMINUM ALLOY 6063-T6 WITH A 2-1/4" INTEGRAL FIN AND .125" MINIMUM DSB GLAZING INSTALLED WITH ALUMINUM RETAINERS IN ORDER TO MEET UNIFORM STATIC DESIGN PRESSURES SHOWN ON THIS DRAWING. AFV PANEL SIZE IS 57.5"x21.9" (MAX). GLAZING IS NOT IMPACT RESISTANT AND DOES NOT MEET THE REQUIREMENTS FOR WIND-BORNE DEBRIS REGIONS.
3. MINIMUM OF 1" OVERLAP ON BOTH JAMBS REQUIRED TO MEET NEGATIVE DESIGN PRESSURES.
4. SLIDE LOCKS REQUIRED.
5. SECTION STEEL TO HAVE THE FOLLOWING MINIMUM THICKNESS:
401, 402 - 20 GA
403, 404 - 24 GA
405, 406 - 25 GA
6. THE DESIGN OF THE SUPPORTING STRUCTURAL ELEMENTS SHALL BE THE RESPONSIBILITY OF THE PROFESSIONAL OF RECORD FOR THE BUILDING OR STRUCTURE AND IN ACCORDANCE WITH CURRENT BUILDING CODES FOR THE LOADS LISTED ON THIS DRAWING.
7. TRACK CLIPS SHALL BE LOCATED WITH CENTERLINE OF BOTTOM CLIP SPACED 10" MAX FROM BOTTOM OF TRACK AND REMAINING TRACK CLIPS SPACED AT 24" O.C. MAX. SPACING BETWEEN TOP TRACK CLIP AND SPLICE PLATE SHALL BE 30" O.C. MAX.
8. WHEN MOUNTING TO WOOD, DOOR JAMB TO BE MINIMUM 2x6 STRUCTURAL GRADE LUMBER. REFER TO JAMB CONNECTION SUPPLEMENT FOR ATTACHMENT TO SUPPORTING STRUCTURE.


SUPERIMPOSED DESIGN PRESSURE LOADS ON SUPPORTING STRUCTURE

MAX DOOR WIDTH	DOOR HEIGHT	MAX UNIFORM LOAD EACH JAMB (PLF)
10'-4"	ALL	+81.9/-93.7


STATIC PRESSURE RATINGS	APPROVED SIZES
DESIGN PRESSURE(PSF): +15.9/-18.2	MAX WIDTH: 10'-4"
	MAX HEIGHT: 24'-1"
IMPACT/CYCLIC RATED: NO	MAX SECTION HEIGHT: 24'



NOTE: (4) SECTION SOLID DOOR SHOWN. SEE SHEET 2 FOR U-BAR LOCATIONS ON DOORS WITH OTHER SECTION QUANTITIES AND SEE NOTES 1 & 2 THIS SHEET FOR GLAZING OPTIONS.




REVISIONS				
ER	REV	DESCRIPTION	DATE	APPROVAL
WL020	-	INITIAL DRAWING	1/29/26	SW
WL020	A	ADDED FBC NOTE	6/30/26	RW







Digitally signed by John Voelkel
Date: 2026.07.10 15:57:16 -05'00'

COMPLIES WITH THE REQUIREMENTS OF IBC/IRC 2024.
COMPLIES WITH THE CURRENT EDITION OF THE FLORIDA BUILDING CODE.

THE DRAWINGS AND ALL OTHER INFORMATION CONTAINED HEREIN ARE THE CONFIDENTIAL AND PROPRIETARY PROPERTY OF OVERHEAD DOOR CORPORATION AND ITS AFFILIATED COMPANIES. THIS DRAWING AND INFORMATION, IN WHOLE OR IN PART, MAY NOT BE COPIED IN ANY MANNER OR DISCLOSED TO ANYONE WITHOUT THE PRIOR WRITTEN CONSENT OF OVERHEAD DOOR CORPORATION. NO DISCLOSURE OF ANY OF THIS DRAWING OR INFORMATION IS INTENDED TO OPERATE AS A LICENSE OR AUTHORIZATION TO USE IT FOR ANY PURPOSE WITHOUT THE SPECIFIC WRITTEN CONSENT OF OVERHEAD DOOR CORPORATION.										
			TOLERANCES UNLESS OTHERWISE SPECIFIED		FINISH	The Genuine. The Original.		NAME	DATE	DRAWING TITLE:
			HOLE DIAMETER	WHOLE NUMBERS:	N/A		LEWISVILLE, TEXAS	DRAWN BY:	1/29/2026	WINDOWLOAD, OPTION CODE 2071
			UNDER .251 +.004/--.003	± .25				S WOLFF		SERIES 401-402/403/404/405/406,
			.251 TO .500 +.006/--.003	.X ± .1						15.9"-18.2 PSF, 10"-4" MAX
			OVER .500 +.008/--.003	.XX ± .03	UNIT OF MEASURE	MATERIAL:		CHECKED BY:	-	
			FRACTIONS	.XXX ± .010		N/A		T CLARK		DRAWING NUMBER
			± 1/16	ANGLES: ± .5°	EA			APPROVED BY:	-	D-413151
								-	-	SCALE: N/A
REF DWG	USED ON									SHEET 1 OF 3
		ASME Y14.100 AND Y14.5 APPLY, UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN U.S. CUSTOMARY UNITS.								





J. CHRISTIAN VOELKEL, PE
407 Navarre Street
Gulf Breeze, FL 32561
FL PE 82229
TX PE 133174

THE DRAWINGS AND ALL OTHER INFORMATION CONTAINED HEREIN ARE THE CONFIDENTIAL AND PROPRIETARY PROPERTY OF OVERHEAD DOOR CORPORATION AND ITS AFFILIATED COMPANIES. THIS DRAWING AND INFORMATION, IN WHOLE OR IN PART, MAY NOT BE COPIED IN ANY MANNER OR DISCLOSED TO ANYONE WITHOUT THE PRIOR WRITTEN CONSENT OF OVERHEAD DOOR CORPORATION. NO DISCLOSURE OF ANY OF THIS DRAWING OR INFORMATION IS INTENDED TO OPERATE AS A LICENSE OR AUTHORIZATION TO USE IT FOR ANY PURPOSE WITHOUT THE SPECIFIC WRITTEN CONSENT OF OVERHEAD DOOR CORPORATION.																			
		THIRD ANGLE PROJECTION		TOLERANCES UNLESS OTHERWISE SPECIFIED				FINISH	The Genuine. The Original.		NAME		DATE		DRAWING TITLE:				
				HOLE DIAMETER				N/A			LEWISVILLE, TEXAS		DRAWN BY: S WOLFF		1/29/2026		DRAWING TITLE: WINDLOAD, OPTION CODE 2071		
		ASME Y14.100 AND Y14.5 APPLY, UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN U.S. CUSTOMARY UNITS		UNDER .251 +.004/- .003				WHOLE NUMBERS: ± .25		UNIT OF MEASURE		MATERIAL:		CHECKED BY: T CLARK		-		SERIES 401/402/403/404/405/406, 15.9"-18.2" PSF, 10'-4" MAX	
				.251 TO .500 +.006/- .003				.X X.X ± .03				N/A		APPROVED BY:		-		DRAWING NUMBER D-413151	
				OVER .500 +.008/- .003				.XXX ANGLES: ± .010		EA								SCALE: N/A SHEET 3 OF 3	
REF DWG	USED ON			FRACTIONS ± 1/16				± .5"											