


'CLASSIC' RAISED PANEL EMBOSS DOORS								
MODELS	24 GA	24 GA INS	25 GA	25 GA INS	24 GA	24 GA INS	25 GA	25 GA INS
CLOPAY	84A, 94, 4F*	94V	73, 75	1500, 190	96	96V	75L, 76	76V
IDEAL	--	--	--	--	--	--	--	--
HOLMES	48B	--	42B	55S	--	--	--	--
SHORT PANEL					LONG PANEL			

* - MODEL 4F IS FLUSH





'CARRIAGE HOUSE' RAISED PANEL EMBOSS DOORS					DOOR HEIGHT		# OF SECTIONS
MODELS	25 GA	25 GA INS	25 GA	25 GA INS			
CLOPAY 'GALLERY'	GD5S, GR5S	GD5SV, GR5SV	GD5L, GR5L	GD5LV, GR5LV	UP TO 7'0"		4
HOLMES 'ARTISTRY'	AR5S	AR5SV	AR5L	AR5LV	7'3" TO 8'9"		5
					9'0" TO 10'6"		6
					10'9" TO 12'3"		7
					12'6" TO 14'0"		8
IDEAL 'CARRIAGE HOUSE'	ED5S	ED5SV	ED5L	ED5LV	14'3" TO 15'9"		9
					16'0"		10
					MAX SECTION HEIGHT: 21"		

SHEET 1 OF 2

REV	DATE	DESCRIPTION
08	05/19/05	UPDATED CODE REF.
09	09/26/05	ADDED ROLLER OPTION
10	11/30/07	ADDED 76V, EXTENDED HEIGHTS, COMBINED CLOPAY, HOLMES, AND IDEAL M/N
11	08/08/08	ADDED M/N 42B, 48B, 55S
12	10/21/08	ADDED M/N 4F
13	12/2009	ADDED 'CARRIAGE HOUSE' EMBOSS DOORS.
14	08/2010	REVISED MODEL TABLES.
15	01/2012	REVISED WIND SPEED TABLE FOR ASCE7-10.
16	04/2012	ADDED IMPACT RESISTANT OPTION.
17	11/09/20	UPDATED TITLE BLOCK AND REMOVED WIND CHART.
18	07/20/22	ADDED 94V.
19	02/23/24	ADDED M/N 96, 96V.
20	08/06/26	UPDATED MODEL TABLE.




'CLASSIC' SHORT RAISED-PANEL SHOWN. LONG 'CLASSIC' AND SHORT 'CARRIAGE HOUSE' ARE ALSO APPROVED.



DESIGN LOADS: +25.0 P.S.F. & -32.0 P.S.F.
TEST LOADS: +37.5 P.S.F. & -48.0 P.S.F.

SEE SHEET TWO FOR
IMPACT RESISTANT CONSTRUCTION DETAIL "A"
AND STANDARD CONSTRUCT DETAIL "B";
TRACK AND JAMB DETAILS.



Jim Wheeler

DESIGN ENGINEER: JAMES D WHEELER, P.E.
FLORIDA P.E. #91932

Clopay
CORPORATION

8585 DUKE BLVD.
MASON, OH 45040
(513) 770-4800

Clopay Corporation All Rights Reserved.

MANUFACTURING PRODUCT CODE PAN-2F151	WINDLOAD RATING W4	MAX. DOOR SIZE: 9'W x 16'H
DATE: 9/23/96	DESCRIPTION: CLASSIC AND CH RP STEEL PAN SINGLE-CAR, 9'W +25/-32 PSF	
DRAWN BY: MWW	B	DRAWING NUMBER: 300159
CHECKED BY:		VER: IBC


FLORIDA PRODUCT APPROVAL 48397.4

'CLASSIC' RAISED PANEL EMBOSS DOORS								
MODELS	24 GA	24 GA INS	25 GA	25 GA INS	24 GA	24 GA INS	25 GA	25 GA INS
CLOPAY	34A, 94, 4F*	94V	73, 75	1500, 190	96	96V	75L, 76	76V
IDEAL	--	--	--	--	--	--	--	--
HOLMES	48B	--	42B	55S	--	--	--	--
SHORT PANEL					LONG PANEL			

* - MODEL 4F IS FLUSH

'CARRIAGE HOUSE' RAISED PANEL EMBOSS DOORS				
MODELS	25 GA	25 GA INS	25 GA	25 GA INS
CLOPAY 'GALLERY'	GD5S, GR5S	GD5SV, GR5SV	GD5L, GR5L	GD5LV, GR5LV
HOLMES 'ARTISTRY'	AR5S	AR5SV	AR5L	AR5LV
IDEAL 'CARRIAGE HOUSE'	ED5S	ED5SV	ED5L	ED5LV
SHORT PANEL			LONG PANEL	

IMPACT RESISTANT ASSEMBLY DETAILS
DRAWING 300159-A




IMPACT-RESISTANT CONSTRUCTION:
SOLID DOORS (NO GLAZING) OR DOORS WITH OPTIONAL IMPACT-RESISTANT GLAZING ARE IMPACT-RESISTANT. OPTIONAL INJECTION-MOLDED POLYCARBONATE FRONT FRAME AND GLAZING IS GE LEXAN SLX2432T, AN APPROVED CC2 PLASTIC IN ACCORDANCE WITH IBC/FBC 2606.
THE ENTIRE DOOR ASSEMBLY INSTALLED IN COMPLIANCE WITH THIS SECTION MEETS THE WIND LOAD REQUIREMENTS OF THE FLORIDA BUILDING CODE AND INTERNATIONAL BUILDING CODE AND MEETS THE IMPACT-RESISTANT REQUIREMENTS (REF. CHAPTER 16 FBC/IBC).

PREPARATION OF JAMBS BY OTHERS.

VERTICAL JAMB ATTACHMENT (WOOD FRAME BUILDINGS):
3/8"x3" LAG SCREWS ON 24" CENTERS. 1-1/8" O.D. WASHER REQUIRED. LAG SCREWS MAY BE COUNTERSUNK (BUT NOT REQUIRED) TO PROVIDE A FLUSH MOUNTING SURFACE. HORIZONTAL JAMBS DO NOT TRANSFER LOAD.


VERTICAL JAMB ATTACHMENT (C-90 BLOCK OR 2,000 PSI MIN. CONCRETE COLUMN):
3/8"x3" SLEEVE ANCHOR BOLTS ON 24" CENTERS (2,000 PSI MIN. CONCRETE). WASHERS INCLUDED WITH SLEEVE ANCHORS.
OR
1/4"x3" TAPCON SCREWS ON 24" CENTERS (2,000 PSI MIN. CONCRETE) OR 16" CENTERS (C-90 BLOCK), 1" O.D. WASHERS REQUIRED WITH TAPCONS.
ANCHORS MAY BE COUNTERSUNK (BUT NOT REQUIRED) TO PROVIDE A FLUSH MOUNTING SURFACE. HORIZONTAL JAMBS DO NOT TRANSFER LOAD.

OTHER JAMB CONFIGURATIONS: REFER TO DASMA TDS-161. A LICENSED DESIGN PROFESSIONAL MAY ALSO BE EMPLOYED TO APPROVE ALTERNATE FASTENERS AND/OR JAMB CONFIGURATIONS.




NOTE: THE DESIGN OF THE SUPPORTING STRUCTURAL ELEMENTS SHALL BE THE RESPONSIBILITY OF THE PROFESSIONAL OF RECORD FOR THE BUILDING OR STRUCTURE AND IN ACCORDANCE WITH CURRENT BUILDING CODES FOR THE LOADS LISTED ON THE DRAWING.

NOTE: TRACK CONFIGURATION ABOVE THE DOOR OPENING DOES NOT AFFECT THE WIND LOAD RATING OF THIS DOOR.



NOTE: DOUBLE TRACK LOW HEADROOM AVAILABLE. 3" TRACK AVAILABLE AS NEEDED.



DESIGN LOADS: +25.0 P.S.F. & -32.0 P.S.F.
TEST LOADS: +37.5 P.S.F. & -48.0 P.S.F.

Clopay
CORPORATION

8585 DUKE BLVD.
MASON, OH 45040
(513) 770-4800

DESIGN ENGINEER: JAMES D WHEELER, P.E.
FLORIDA P.E. #91932

Clopay Corporation All Rights Reserved.

MANUFACTURING PRODUCT CODE
PAN-2F151

DATE: 9/23/96

DRAWN BY: MWW

CHECKED BY:

WINDLOAD RATING
W4

DESCRIPTION:

CLASSIC AND CH RP STEEL PAN
SINGLE-CAR, 9'W +25/-32 PSF

B

DRAWING NUMBER:
300159

VER:

IBC