




1. EVALUATED FOR USE IN LOCATIONS ADHERING TO THE FLORIDA BUILDING CODE AND WHERE PRESSURE REQUIREMENTS AS DETERMINED BY ASCE 7, MINIMUM DESIGN LOADS FOR BUILDINGS AND OTHER STRUCTURES, DOES NOT EXCEED THE DESIGN PRESSURES LISTED.
2. HURRICANE PROTECTIVE SYSTEM (SHUTTERS) IS NOT REQUIRED.
3. IN THE HVHZ, FACTORY PRIMED DOORS MUST BE PAINTED IN ACCORDANCE WITH SECTION 2220 OF THE FBC.



		DESIGN PRESSURE RATING		WHERE WATER INFILTRATION PERFORMANCE IS REQUIRED TO BE 15% OF DESIGN PRESSURE	
CONFIG	MAX WIDTH	INSWING	OUTSWING	INSWING	OUTSWING
X	40"	+80.0 / -80.0	+80.0 / -80.0	+19.0 / -19.0	+55.0 / -55.0

WHERE WATER INFILTRATION PERFORMANCE IS
REQUIRED TO BE 15% OF DESIGN PRESSURE



DATE:	6/10/06		
SCALE:	N.T.S.		
DWG. BY:	SWS		
CHK. BY:			
DRAWING NO.:	DWG-MA-FL0150-06		
SHEET	1	OF	2

