

## Product Evaluation Report

Report No.: **FL-15210.14**

Date: **July 2, 2026**

| Product Category | Sub Category                      | Manufacturer                                                                           | Product Name                                                                                                   |
|------------------|-----------------------------------|----------------------------------------------------------------------------------------|----------------------------------------------------------------------------------------------------------------|
| Exterior Doors   | Swinging Exterior Door Assemblies | Plastpro, Inc.<br>5200 W. Century Blvd.<br>Los Angeles, CA 90045<br>Phone 440.969.9773 | Smooth / Wood Grain / White Wood Grain<br>Rustic / Mahogany<br>Series O Fiberglass Door<br>Outswing - "Impact" |

**Scope:** Product Evaluation report issued by R W Building Consultants, Inc. & Lyndon F. Schmidt, P.E. (System ID # 1998) for Plastpro Inc., based on Rule Chapter No. 61G20-3, Method 1D of the State of Florida Product Approval, Department of Business & Professional Regulation.

RW Building Consultants and Lyndon F. Schmidt, P.E. do not have nor will acquire financial interest in the company manufacturing or distributing the product or in any other entity involved in the approval process of the product named herein.

### Limitations:

- This product has been evaluated and is in compliance with the 9th Edition (2026) Florida Building Code structural requirements including the "High Velocity Hurricane Zone".
- Product anchors shall be as listed and spaced as shown on details. Anchor embedment to base material shall be beyond wall dressing or stucco.
- When used in the "HVBH" this product complies with Section 1626 of the Florida Building Code and does not require an impact resistant covering.
- When used in areas outside of the "HVBH" requiring wind borne debris protection this product complies with FBC Sections 1609.1.2 & R301.2.1.2 and does not require an impact resistant covering. This product meets missile level "D" and includes Wind Zone 4 as defined in ASTM E 1996.
- For 2x stud framing construction, anchoring of these units shall be the same as that shown for 2x buck masonry construction.
- Site conditions that deviate from the details of drawing FL-15210.14 require further engineering analysis by a licensed engineer or registered architect.
- Outswing configurations meet water infiltration requirements for "HVBH".
- See drawing FL-15210.14 for size and design pressure limitations.

### Supporting Documents:

- |                                                                                                                                                                                                                                                                   |                                                                                                                                                                                                                                     |                                                                                                                                                                                 |                                                                                                                                                              |
|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>1. Test Report No.</b><br>TEL 01390568<br>TEL 01391846<br>ETC-05-255-16776.0<br><br>ETC-06-255-17412.0<br>ETC-07-209-19303.0<br>ETC-08-209-20609.1                                                                                                             | <b>Test Standard</b><br>TAS 201-94, 202-94 & 203-94<br>TAS 201-94, 202-94 & TAS 203-94<br>ASTM D 635-98, 638-03, 1929-96 & 2843-99<br>ASTM G 26-95<br>ASTM E 84-05<br>ASTM D 635-98, 1929-96 & 2843-99<br>ASTM D 638-03 & G 155-05a | <b>Testing Laboratory</b><br>Testing Evaluation Lab., Inc.<br>Testing Evaluation Lab., Inc.<br>ETC Laboratories<br><br>ETC Laboratories<br>ETC Laboratories<br>ETC Laboratories | <b>Signed by</b><br>William Shelton, P.E.<br>William Shelton, P.E.<br>Joseph L. Doldan, P.E.<br><br>Joseph L. Doldan, P.E.<br>Ben Meunier<br>Gurjinder Dhami |
| <b>2. Drawing No.</b><br>No. FL-15210.14                                                                                                                                                                                                                          | <b>Prepared by</b><br>RW Building Consultants, Inc. (#9813)                                                                                                                                                                         |                                                                                                                                                                                 | <b>Signed &amp; Sealed by</b><br>Lyndon F. Schmidt, P.E.                                                                                                     |
| <b>3. Calculations</b><br>Anchoring                                                                                                                                                                                                                               | <b>Prepared by</b><br>RW Building Consultants, Inc. (#9813)                                                                                                                                                                         |                                                                                                                                                                                 | <b>Signed &amp; Sealed by</b><br>Lyndon F. Schmidt, P.E.                                                                                                     |
| <b>4. Quality Assurance</b><br>Certificate of Participation issued by National Accreditation and Management Institute, certifying that Plastpro, Inc. is manufacturing products within a quality assurance program that complies with ISO/IEC 17020 and Guide 53. |                                                                                                                                                                                                                                     |                                                                                                                                                                                 |                                                                                                                                                              |

Digitally signed by Lyndon F Schmidt  
Date: 2026.07.28 13:34:55 -04'00'

LYNDON F. SCHMIDT, State of Florida, Professional Engineer, License No. 43409  
This item has been digitally signed and sealed by L. F. Schmidt on 7-28-26.  
Printed copies of this document are not considered signed and sealed and the signature must be verified on any electronic copies.

**THIS PRODUCT APPROVAL IS VALID ONLY FOR THE STATE OF FLORIDA**