

Certificate of Authorization No. 29824 17520 Edinburgh Dr Tampa, FL 33647 (813) 480-3421

EVALUATION REPORT

2010 FLORIDA BUILDING CODE

Issued October 23, 2014

Manufacturer: EAGLE ROOFING PRODUCTS FLORIDA LLC

1575 E CR 478

Sumterville, FL 33585 (800) 400-4235

http://www.eagleroofing.com

Manufacturing Plants: Sumterville, FL

Quality Assurance: Architectural Testing, Inc. (QUA1844)

SCOPE

Category: Roofing Subcategory: Roofing Tiles

Code Sections: 1507.3.5, 1507.3.7, 1523.6.5.2, 1523.6.5.2.2, 1523.6.5.2.3

Properties: Physical Properties, Attachment Requirements, Wind Driven Rain, Static Uplift

Resistance

PRODUCT DESCRIPTION

Capistrano

Profile: ASTM C 1492, TAS 112, high profile, concrete roof tile

Description: TAS 112 type 1a, high profile, interlocking class III concrete tile

Dimensions: 17.0" x 12.25" x 3.0"




Figure 1. Capistrano



Malibu

Profile: ASTM C 1492, TAS 112, medium profile, concrete roof tile **Description:** TAS 112 type 1b, low profile, interlocking class III concrete tile

Dimensions: 17.0" x 12.375" x 2.125"




Figure 2. Malibu

Bel Air

Profile: ASTM C 1492, TAS 112, flat profile, concrete roof tile

Description: TAS 112 type 3a, flat profile, interlocking class III concrete tile

Dimensions: 17.0" x 12.375" x 1.25"




Figure 3. Bel Air



APPLICATION METHOD

Eagle Hybrid Installation for Capistrano, Malibu, and Bel Air Concrete Roof Tile						
Slope:	Limited to slopes 3:12 or greater in the HVHZ; Outside the HVHZ, shall be in accordance with the recommendations of the FRSA/TRI 07320/8-05 or RAS 118.					
Roof Deck:	Solid or closely fitted min. 15/32-inch plywood sheathing for new and existing construction at max. 24 in. span; In the HVHZ, new construction shall be min. 19/32 in. plywood at max. 24 in. span; Designed by others in accordance with FBC requirements.					
Underlayment:	Installed in accordance with FBC requirements. In the HVHZ, the minimum underlayment shall be Hot Mop 30/90 installed as described in RAS 118 Section 3.01.					
Attachment:	A minimum 6-inch x1-inch x 1-inch paddy of Dow TILE BOND™ shall be placed within the 3-inch head lap as shown in Figure 4 thru Figure 6. The upper tile shall be set immediately into the adhesive paddy. All tiles shall be secured by two (2) #8 x min. 3-inch Simpson Strong-Tie Quik Drive WSCD Roof Tile Screws with sufficient length to penetrate through the plywood deck a minimum 1/2-inch and located into the factory located fastener holes. All penetrations in the underlayment shall be sealed in accordance with RAS 118 (HVHZ) and FRSA/TRI 07320/8-05 (non-HVHZ).					




Figure 4. Adhesive Paddy Location for Capistrano






Figure 5. Adhesive Paddy Location for Malibu




Figure 6. Adhesive Paddy Location for Bel Air

ERP14001 FL17326 Page 3 of 6



Data for Attachment Calculations									
Roof Tile	Nominal Weight (W) and Dimensions (I x w)			Aerodynamic Multipliers λ (ft ³)	Restoring Moments due to Gravity - M _g (ft-lbf) Direct Deck				
	W (lbf)	L (ft)	w (ft)	Direct Deck Application	3":12"	4":12"	5":12"	6":12"	≥7":12"
Capistrano	9.7	1.42	1.02	0.30	6.83	6.75	6.65	6.52	6.38
Malibu	9.2	1.42	1.03	0.31	6.47	6.37	6.24	6.09	5.93
Bel Air	11.8	1.42	1.03	0.29	8.27	8.15	8.00	7.81	7.61

Attachment Resistance Expressed as a Moment Hybrid installation system								
Roof Tile		Fastener ¹		Adhesive			M (6, 11, 6)	
	Туре	Count	Size	Adhesive	Paddy Size ²	Paddy Weight ²	M _f (ft-lbf)	
Capistrano	Screw	2	#8	Dow TILE BOND™	6"x1"x1"	13.7g	47	
Malibu	Screw	2	#8	Dow TILE BOND™	6"x1"x1"	10.4g	73	
Bel Air	Screw	2	#8	Dow TILE BOND™	6"x1"x1"	10.4g	66	

Notes: 1) Simpson Strong-Tie Quik Drive WSCD Roof Tile Screw shall be min. 3-inch with sufficient length to penetrate through the plywood deck a min. 1/2-inch

LABELING

1) All tiles shall bear the identifiable marking of the manufacturer's name or logo as follows:




ERP14001 FL17326 Page 4 of 6

²⁾ Minimum dimensions and weight for adhesive application



LIMITATIONS

- 1) Fire Classification is not within the scope of this evaluation.
- 2) Installation of the evaluated products shall comply with FBC Section 1507.3, FRSA/TRI 07320/8-05, and the manufacturer's published application instructions. Installations in the HVHZ shall comply with RAS 118.
- 3) All products listed in this report shall be manufactured under a quality assurance program in compliance with Rule 61G20-3.
- 4) Installation of the evaluated products shall be limited to projects in areas subjected to weathering indices of 50 or greater as illustrated in ASTM C 1492-03, figure 1 (see below).



REFERENCES

<u>Entity</u>	Report No.	Standard	Year
American Test Lab of South Florida Inc (TST3782)	RT0610.01-14	TAS 112	1995
American Test Lab of South Florida Inc (TST3782)	RT0610.01-14	ASTM C 1492	2003
American Test Lab of South Florida Inc (TST3782)	RT0610.02-14	TAS 112	1995
American Test Lab of South Florida Inc (TST3782)	RT0610.02-14	ASTM C 1492	2003
American Test Lab of South Florida Inc (TST3782)	RT0610.03-14	TAS 112	1995
American Test Lab of South Florida Inc (TST3782)	RT0610.03-14	ASTM C 1492	2003
American Test Lab of South Florida Inc (TST3782)	RT0603.01-13	TAS 101/TAS 102	1995
PRI Construction Materials Technologies	ERPF-057-02-01	TAS 101/TAS 102	1995
PRI Construction Materials Technologies	ERPF-058-02-01	TAS 101/TAS 102	1995
PRI Construction Materials Technologies	ERPF-059-02-01	TAS 100	1995
PRI Construction Materials Technologies	ERPF-060-02-01	TAS 100	1995
PRI Construction Materials Technologies	ERPF-061-02-01	TAS 100	1995



COMPLIANCE STATEMENT

The products evaluated herein by Zachary R Priest P.E. have demonstrated compliance with the 2010 Florida Building Code as evidenced in the referenced documents submitted by the named manufacturer.



Zachary R. Priest, P.E. Florida Registration No. 74021 Organization No. ANE9641

CERTIFICATION OF INDEPENDENCE

CREEK Technical Services, LLC does not have, nor will it acquire, a financial interest in any company manufacturing or distributing products under this evaluation.

CREEK Technical Services, LLC is not owned, operated, or controlled by any company manufacturing or distributing products under this evaluation.

Zachary R. Priest, P.E. does not have, nor will acquire, a financial interest in any company manufacturing or distributing products under this evaluation.

Zachary R. Priest, P.E. does not have, nor will acquire, a financial interest in any other entity involved in the approval process of the product.

END OF REPORT

ERP14001 FL17326 Page 6 of 6