

398 E. Dania Beach Blvd. Suite 338 Dania Beach, FL 33004 954.399.8478 PH 954.744.4738 FX contact@buildingdrops.com

Product Evaluation Report

of

Continental Glass System, LLC.

Series 200 Aluminum Curtain Wall - LMI

for

Florida Product Approval

FL# FL19734

Report No. 4239

Current Florida Building Code

Method: 1 - A (Certificate)

Category: Panel Walls
Sub – Category: Curtain Wall

Product: Series 200 Aluminum Curtain Wall - LMI

Material: Aluminum

Product Dimensions: See Installation Drawing CGS122

Prepared For:

Continental Glass Systems, LLC. 325 West 74 Place Hialeah, FL 33014

Prepared by:

Hermes F. Norero, P.E.

Florida Professional Engineer # 73778 Date: 03/11/2016

Contents:

Evaluation Report Pages 1-3



Certificate of Authorization: 29578

FL# FL19734 Date: 03/11/2016 Report No: 4239

Manufacturer: Continental Glass Systems, LLC.

Product Category: Panel Walls

Product Sub-Category: Curtain Wall

Compliance Method: State Product Approval Method (1)(a)

Product Name: Series 200 Aluminum Curtain Wall - LMI

(Impact)

Scope: This is a Product Evaluation Report issued by Hermes F. Norero, P.E. (FL # 73778) for Continental

Glass Systems, LLC. based on Method 1a of the State of Florida Product Approval, Florida Department of Business and Professional Regulation - Florida Building Commission.

Hermes F. Norero, P.E. does not have nor will acquire financial interest in the company manufacturing or distributing the product or in any other entity involved in the approval process of the product named herein.

This product has been evaluated for use in locations adhering to the current Florida Building Code.

See Installation Instructions **CGS122**, signed and sealed by Hermes F. Norero, P.E. (FL # 73778) for specific use parameters.

Limits of Use:

- 1. This product has been evaluated and is in compliance with the current Florida Building Code, including the "High Velocity Hurricane Zone" (HVHZ).
- 2. Product anchors shall be as listed and spaced as shown on details. Anchor embedment into substrate material shall be beyond wall dressing or stucco.
- 3. When used in areas requiring wind borne debris protection this product complies with Chapter 16 of the current Florida Building Code for Large Missile Impact and <u>does not</u> require an impact resistant covering.
- 4. Site conditions that deviate from the details of drawing **CGS122** require further engineering analysis by a licensed engineer or registered architect.
- 5. See Installation Instructions **CGS122** for size and design pressure limitations.

Certificate of Authorization: 29578

FL# FL19734 Date: 03/11/2016 Report No: 4239

Quality Assurance:

The manufacturer has demonstrated compliance of products in accordance with the Florida Building Code for manufacturing under a quality assurance program audited by an approved quality assurance entity through **National Accreditation & Management Institute** (FBC Organization #: QUA1789).

Performance Standards:

The product described herein has been tested per:

• TAS 201-94

• TAS 202-94

TAS 203-94

AAMA 501-05

Referenced Data:

1. Product Testing performed by **Blackwater Testing Inc.**

(FBC Organization # TST10394)

Report #: BT-CON-15-015 Report Date: 02/11/2016

2. Certification Agency

National Accreditation & Management Institute

(FBC Organization #: CER1773)

3. Material Certification

Miami-Dade County RER-Product Control Section NOA

Vanceva Storm (aka Saflex CP) Interlayer by Eastman Chemical Co.

Installation:

Refer to Installation Instructions (**CGS122**) for anchor types, quantities, spacing and more details of the installation requirements.

Design Pressure: Refer to Installation Instructions (**CGS122**) for design pressures based on sizes and reinforcements.