

# **BUILDING DROPS**

A Perfect Solution in Every Drop! Certificate of Authorization: 29578 398 E. Dania Beach Blvd. Suite 338 Dania Beach, FL 33004 954.399.8478 PH 954.744.4738 FX contact@buildingdrops.com

## **Product Evaluation Report**

of

The Tapco Group 7" Shingles Vinyl Siding

for

## **Florida Product Approval**

## FL# FL20403

## Report No. 7611

### **Current Florida Building Code**

Method: Category: Sub – Category: 1 – D (Engineering Evaluation) Panel Walls Siding


Product: Material: Product Dimensions: 7" Shingles Vinyl Siding Vinyl See Installation Instructions, TTG021

## **Prepared For:**

The Tapco Group 200 Shotwell Drive Franklin, Ohio 45005

Prepared by: Hermes F. Norero, P.E. Florida Professional Engineer # 73778 Date: 05/24/2021

Contents: Evaluation Report Pages 1 – 4



Hermes F. Norero, P.E. Florida P.E. No. 73778



Product Name:	7" Shingles Vinyl Siding
Compliance Method:	State Product Approval Method (1)(d)
Product Sub-Category:	Siding
Product Category:	Panel Walls
Manufacturer:	The Tapco Group

Scope:This is a Product Evaluation Report issued by Hermes F. Norero, P.E. (FL # 73778) for The Tapco<br/>Group based on Method 1d of the State of Florida Product Approval, Department of Business and<br/>Professional Regulation - Florida Building Commission.

Hermes F. Norero, P.E. does not have nor will acquire financial interest in the company manufacturing or distributing the product or in any other entity involved in the approval process of the product named herein.

This product has been evaluated for use in locations adhering to the current Florida Building Code.

See Installation Instructions **TTG021**, signed and sealed by Hermes F. Norero, P.E. (FL # 73778) for specific use parameters.

#### Limits of Use:

- 1. This product has been evaluated and is in compliance with the current Florida Building Code, <u>excluding</u> the "High Velocity Hurricane Zone" (HVHZ).
- 2. Product anchors shall be as listed and spaced as shown on details. Anchor embedment into substrate material shall be beyond wall dressing or stucco.
- 3. Site conditions that deviate from the details of Installation Instructions **TTG021** require further engineering analysis by a licensed engineer or registered architect.
- 4. See Installation Instructions **TTG021** for size and design pressure limitations.



Quality Assurance:	ssurance: The manufacturer has demonstrated compliance of siding products in Accordance with	
	Florida Building Code and State Rule for manufacturing under a quality assurance program	
	audited by an approved quality assurance entity through Intertek Testing Services NA, Inc	
	QA Entity (FBC Organization #: QUA1673)	

**Performance Standards:** The product described herein has been tested per:

- ASTM D3679-17
- TAS 202-94
- TAS 203-94
- Referenced Data:1.Product Testing performed by Architectural Testing, Inc.<br/>(FBC Organization # TST1558)<br/>Report #: E8400.01-109-40,Report Date: 10/13/15
  - 2. Quality Assurance Intertek Testing Services NA, Inc. - QA Entity (FBC Organization # QUA1673)

### Installation:

Refer to Installation Instructions (**TTG021**) for further installation details, anchor spacing, and limitations of use.

### **Design Pressure:**

Refer to Installation Instructions (**TTG021**) for allowable design pressures based on panel height and width.



### **Equivalence of Test Standard Editions:**

Various test standard(s) have been evaluated for differences in test methodology, if any, between tested editions of the test standards listed below and those editions referenced in the current Florida Building Code. The manufacturer has tested their products to the following test standard edition(s):

1) ASTM D3679-09

Chapter 35 of the current Florida Building Code references the following editions of the above mentioned test standards:

1) ASTM D3679-17

After review of the above mentioned referenced standards and editions, it has been found that no significant technical changes have been made to the test standards that would affect the results. All referenced standards have been found to be equivalent.