



**Product Evaluation Report**

**Report No.: FL-21142.11**

**Date: July 2, 2026**

| Product Category | Sub Category                      | Manufacturer                                                                               | Product Name                                                                                                            |
|------------------|-----------------------------------|--------------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------------------------------------------|
| Exterior Doors   | Swinging Exterior Door Assemblies | Therma Tru Corporation<br>118 Industrial Drive<br>Edgerton, OH 43517<br>Phone 419.298.1740 | Fiber-Classic and Smooth-Star<br>Wood Edge Glazed Fiberglass Single Door<br>w/ Sidelite(s)<br>Inswing/Outswing "Impact" |

**Scope:** This is a Product Evaluation report issued by R W Building Consultants, Inc. and Lyndon F. Schmidt, P.E. for Therma Tru Corporation based on Rule Chapter No. 61G20-3, Method 1D of the State of Florida Product Approval, Department of Business & Professional Regulation.

RW Building Consultants and Lyndon F. Schmidt, P.E. do not have nor will acquire financial interest in the company manufacturing or distributing the product or in any other entity involved in the approval process of the product named herein.

**Limitations:**

1. This product has been evaluated and is in compliance with the 9th Edition (2026) Florida Building Code (FBC) structural requirements including the "High Velocity Hurricane Zone" (HVHZ).
2. Product anchors shall be as listed and spaced as shown on details. Anchor embedment to base material shall be beyond wall dressing or stucco.
3. When used in the "HVHZ" this product complies with section 1626 of the FBC and does not require an impact resistant covering.
4. When used in areas outside of the "HVHZ" requiring wind borne debris protection, this product complies with FBC Sections 1609.1.2 & R301.2.1.2 and does not require an impact resistant covering. This product meets missile level "D" and includes Wind Zone 4 as defined in ASTM E 1996.
5. For 2x stud framing construction, anchoring of these units shall be the same as that shown for 2x buck masonry construction.
6. Site conditions that deviate from the details of drawing FL-21142.11 require further engineering analysis by a licensed engineer or registered architect.
7. This product meets water infiltration requirements for the "HVHZ".
8. Outswing configurations using Coastal Sill (items #19) & Composite Sill (item #16) under active doors meet water infiltration requirements for "HVHZ". All other configurations do not meet the water infiltration requirements for the "HVHZ" and shall be installed only in non-habitable areas or at habitable locations protected by an overhang or canopy such that the angle between the edge of canopy or overhang to sill is less than 45 degrees.
9. See drawing FL-21142.11 for size and design pressure limitations.

**Supporting Documents:**

- |                                                                                                                                                                                                                                                                           |                                                                                                               |                                                                                 |                                                                        |
|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|---------------------------------------------------------------------------------------------------------------|---------------------------------------------------------------------------------|------------------------------------------------------------------------|
| 1. <b>Test Report No.</b><br>TEL 01460105.1<br>TEL 01462264                                                                                                                                                                                                               | <b>Test Standard</b><br>TAS 202-94, TAS 201/203-94<br>TAS 202-94, TAS 201/203-94                              | <b>Testing Laboratory</b><br>Testing Evaluation Labs<br>Testing Evaluation Labs | <b>Signed by</b><br>L.F. Schmidt, P.E. (2009)<br>William Shelton, P.E. |
| 2. <b>Miami-Dade NOA</b><br>25-0904.04<br>26-0625.05                                                                                                                                                                                                                      | <b>Material</b><br>Saflex PVB Interlayers (Eastman Chemical Co.)<br>Trosifol/Butacite (Kuraray America, Inc.) |                                                                                 |                                                                        |
| 3. <b>Drawing No.</b><br>No. FL-21142.11                                                                                                                                                                                                                                  | <b>Prepared by</b><br>RW Building Consultants, Inc. (#9813)                                                   |                                                                                 | <b>Signed &amp; Sealed by</b><br>Lyndon F. Schmidt, P.E.               |
| 4. <b>Calculations</b><br>Anchoring<br>ASTM E1300 Glass Load                                                                                                                                                                                                              | <b>Prepared by</b><br>RW Building Consultants, Inc. (#9813)<br>RW Building Consultants, Inc. (#9813)          |                                                                                 | <b>Signed &amp; Sealed by</b><br>Lyndon F. Schmidt, P.E.               |
| 5. <b>Quality Assurance</b><br>Certificate of Participation issued by National Accreditation and Management Institute, certifying that Therma Tru Corporation is manufacturing products within a quality assurance program that complies with ISO/IEC 17020 and Guide 53. |                                                                                                               |                                                                                 |                                                                        |

Digitally signed by Lyndon F Schmidt  
Date: 2026.08.07 13:26:34 -04'00'

LYNDON F. SCHMIDT, State of Florida, Professional Engineer, License No. 43409  
This item has been digitally signed and sealed by L. F. Schmidt on 8-07-26.  
Printed copies of this document are not considered signed and sealed and the signature must be verified on any electronic copies.  
**THIS PRODUCT APPROVAL IS VALID ONLY FOR THE STATE OF FLORIDA**